

# 2017 APOLLO ARCHITECTURE

## MTB



29" DUAL SUSPENSION

27.5" DUAL SUSPENSION

29" HARDTAIL

27.5" HARDTAIL

FAT BIKE

26" WS RECREATIONAL

## ROAD



CARBON

ALLOY

TT/TRI

ROAD DISC

## LIFESTYLE



TRANSFER

TRACE

EXCEED

E-BIKE

HYBRID

CLASSIC

CRUISER

TANDEM

FOLDING

## YOUTH



24" YOUTH

# 2017 MTB DESIGN PHILOSOPHY

## HARDTAIL

29"



XPERT 10



XPERT 20



XPERT 30

**ALL  
AROUND**

27.5"

ASPIRE 10



ASPIRE 20



ASPIRE 30



## MTB RIDING STYLE AND CHARACTERISTICS

### ALL AROUND

Entry level price point  
Solid alloy frame  
Double wall rims  
Quality brakes & shifting  
80mm suspension travel  
Oversized handlebar and stem  
Choose between 29" and 27.5"

# DUAL SUSPENSION



XPERT 40



XPERT D 10



XPERT D 20



ARCTEC D 9

**XC**

**TRAIL**

ASPIRE 40



ASPIRE D 20



ASPIRE D 30



ARCTEC D 7



## XC

- 100mm to 120mm travel
- 29" wheels
- Light weight
- Faster rolling tyres
- Aggressive race geometry

## TRAIL

- Longer travel suspension 120mm to 140mm
- 27.5" wheels
- Slacker head tube angle
- Long top tube length
- Wider, more aggressive tyres

# DUAL/SUSPENSION

## DESIGN PHILOSOPHY

XC

29"


*XC ready 100mm to  
120mm travel*

*Faster rolling tyres*

*Aggressive race geometry  
for better power-to-ground  
and handling*

*Lightweight design*





TRAIL

**27.5"**

*Trail ready 120mm  
to 140mm travel*

*Wider, more aggressive tyres*

*Trail ready handling with  
slacker head tube and longer  
top tube*

*Durable trail-ready  
construction*

# ARCTEC D 9

29" CARBON DUAL SUSPENSION - 1 X 12 SPEED

MTB

ROAD

LIFESTYLE

YOUTH



## KEY FEATURES

29" 120mm light weight carbon XC full suspension frame

Rock Shox RS1 ACS Front Suspension, Air with Lockout.

DT Swiss XR-1501 wheelset with Boost 110mm front and 148mm rear hubs.

New SRAM XO/XX Eagle 1 x 12 speed.

Rock Shox Reverb Stealth hydraulic dropper post.

New SRAM Level Ultimate hydraulic disc brakes, with 180mm front and 160mm rear rotors

Veetire Rail Tracker 29" x 2.20" Folding Tubeless ready

15mm Front Axle, with Sealed bearing hubs with 12mm thru axle rear.

## CODES

	S	M	L
Matte nude carbon / gloss red / gloss white	17156	17157	17158

## GEOMETRY

	S	M	L
STACK	589	598	607
REACH	387	412	429
STAND OVER HEIGHT	n/a	n/a	n/a
EFFECTIVE TOP TUBE	561	583	603
SEAT TUBE (CENTRE TO TOP)	394	445	483
SEAT ANGLE	73.5°	74.0°	74.0°
HEAD TUBE LENGTH	95	105	115
HEAD ANGLE	68.0°	68.0°	68.0°
WHEEL BASE	1105	1131	1149
CHAIN STAY LENGTH	440	440	440
BB DROP	40	40	40
FORK RAKE	51	51	51
AXLE TO CROWN	520	520	520
REAR DROPOUT SPACING	148	148	148

## SPECIFICATIONS

**FRAME** Hi modulus carbon 29" suspension frame, 120mm travel, tapered 1 1/8-1.5 head tube, BB91 press fit bottom bracket, boost 12x148, post mount rear brake calliper.

**FORK** Rock Shox RS1 carbon upside down suspension fork. Tapered alloy steerer, RSA Thru Axle w/51mm offset, single air, 120mm travel, rebound adjust, mag lowers, remote lockout

**REAR SHOCK** Rockshox Monarch RT

**HEADSET** A-head semi integrated, for tapered 1.8-1.5 head tube, semi cartridge bearings with 8mm cone spacer

**HANDLEBAR** Answer Pro taper carbon SL. 720mm extra wide flat bar, 31.8mm, sweep: 8°

**GRIP** Ultra light foam racing grips

**HEAD STEM** Factor 31.8mm 4 bolt stem, Ext:S/ M=90mm, L=100mm,

**CRANKSET** SRAM XO-1 Eagle press fit 12 speed 34T L: S/M/L=175mm

**BOTTOM BRACKET** BB91 press fit cartridge bearings

**PEDALS** NIL

**F. DERAILLEUR** N/A

**R. DERAILLEUR** SRAM XX-1 Eagle 12 speed

**SHIFT LEVERS** SRAM XO-1 Eagle 12 speed trigger shifter

**CASSETTE** SRAM XG 1295 12 speed 10-50T

**CHAIN** Sram XO-1 Eagle

**BRAKES** SRAM Level Ultimate hydraulic disc brakes, 180mm front 160mm rear rotors

**WHEELS** 29" DT XR 1501 Spline alloy tubeless ready 29er wheelset

**TYRES** Veetire Rail Tracker 29 x 2.2" 72TPI Folding

**SADDLE** Prologo X Zero with Tirox rail custom design

**SEATPOST/ CLAMP** Rock Shox Reverb Post 31.6mm, Quick release seat post clamp

**EXTRAS** N/A



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

29" 120mm light weight carbon XC full suspension frame

Manitou Marvel Comp Air Suspension fork, QR15 axle, with tapered steer tube.

Boost 110mm front and 148mm rear hubs.

Sun Ringle Helix Tubeless ready rim with STANS NO TUBES rim tape.

SRAM GX 1 x 11 shifting with SRAM narrow wide crank

KS LEV INTEGRA dropper post

SRAM GUIDE R hydraulic disc brakes, with 180mm front and 160mm rear rotors

Veetire Rail Tracker 29" x 2.20" Folding Tubeless ready XC tyres

Oversized alloy handlebar and A-head stem.

15mm Front Axle, with Sealed bearing hubs with 12mm thru axle rear.

## CODES

	S	M	L
Matte nude carbon / gloss fluoro green / gloss red	17159	17160	17161

## GEOMETRY

	S	M	L
STACK	589	598	607
REACH	387	412	429
STAND OVER HEIGHT	n/a	n/a	n/a
EFFECTIVE TOP TUBE	561	583	603
SEAT TUBE (CENTRE TO TOP)	394	445	483
SEAT ANGLE	73.5°	74.0°	74.0°
HEAD TUBE LENGTH	95	105	115
HEAD ANGLE	68.0°	68.0°	68.0°
WHEEL BASE	1105	1131	1149
CHAIN STAY LENGTH	440	440	440
BB DROP	40	40	40
FORK RAKE	51	51	51
AXLE TO CROWN	520	520	520
REAR DROPOUT SPACING	148	148	148

## SPECIFICATIONS

<b>FRAME</b>	Hi modulus carbon 29" suspension frame, 120mm travel, tapered 1 1/8-1.5 head tube, BB91 press fit bottom bracket, boost 12x148, post mount rear brake calliper.	<b>GRIP</b>	Ultra light foam racing grips	<b>CASSETTE</b>	SRAM XG 1150 11 speed 10-42T
<b>FORK</b>	Rock Shox Reba, 120mm travel with QR15 Thru Axle	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext:S/ M=90mm, L=100mm,	<b>CHAIN</b>	KMC-X11
<b>REAR SHOCK</b>	Rockshox Monarch RT	<b>CRANKSET</b>	SRAM GX-1001 Press fit, 11 speed X-Sync 30T L: S=170mm, M/L =175mm	<b>BRAKES</b>	SRAM Guide R hydraulic disc brakes, 180mm front 160mm rear rotors
<b>HEADSET</b>	A-head semi integrated, for tapered 1.8-1.5 head tube, cartridge bearings with 8mm cone spacer	<b>BOTTOM BRACKET</b>	BB91 press fit cartridge bearings	<b>WHEELS</b>	29" Sun Ringle Helix TR25 Tubeless ready, 32 hole, 15mm Thru Axle, 32 hole rear with 12mm x 148 through axle
<b>HANDLEBAR</b>	Factor butted alloy flat bar bore: 31.8mm W: 700mm, sweep: 9°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Veetire Rail Tracker 29 x 2.2" 72TPI Folding
		<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Factor MTB team saddle
		<b>R. DERAILLEUR</b>	SRAM GX-1 11 speed	<b>SEATPOST/ CLAMP</b>	KS LEV INTEGRA Dropper Post 31.6mm, Quick release seat post clamp
		<b>SHIFT LEVERS</b>	SRAM GX-1 11 speed trigger shifter	<b>EXTRAS</b>	N/A

# XPERT D 10

29" DUAL SUSPENSION - 1 X 11 SPEED

MTB

ROAD

LIFESTYLE

YOUTH



## KEY FEATURES

29" 120mm light weight Alloy XC full suspension frame

Manitou Marvel Ltd Air Suspension fork, QR15 axle, with Tapered steer tube

Boost 110mm front and 148mm rear hubs with new double wall Weinmann alloy rim.

SRAM NX 1 x 11, with NX RD, crank and shifters

SRAM Level hydraulic disc brakes, with 180mm front and rear rotors

Veetire Rail Tracker 29" x 2.20" XC tyres.

Oversized alloy handlebar and A-head stem.

15mm Front Axle, with Sealed bearing hubs with 12mm thru axle rear.

## CODES

	S	M	L
Matte black / gloss chrome / gloss red	17162	17163	17164

## GEOMETRY

	S	M	L
STACK	598	598	607
REACH	391	412	429
STAND OVER HEIGHT	n/a	n/a	n/a
EFFECTIVE TOP TUBE	562	583	603
SEAT TUBE (CENTRE TO TOP)	394	445	483
SEAT ANGLE	74.0°	74.0°	74.0°
HEAD TUBE LENGTH	105	105	115
HEAD ANGLE	68.0°	68.0°	68.0°
WHEEL BASE	1113	1131	1149
CHAIN STAY LENGTH	440	440	440
BB DROP	40	40	40
FORK RAKE	51	51	51
AXLE TO CROWN	520	520	520
REAR DROPOUT SPACING	148	148	148

## SPECIFICATIONS

<b>FRAME</b>	Alloy 29er Suspensopn frame. Tapered 1-1/8 to 1.5 head tube, 120mm Travel	<b>GRIP</b>	Ultra light hex shaped foam racing grips	<b>CASSETTE</b>	SRAM 11 speed cassette 11 - 42T
<b>FORK</b>	Manitou Marvel Comp 29 tapered alloy steerer, 120mm travel with QR15 Thru Axle	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext:S/ M=75mm, L=90mm	<b>CHAIN</b>	KMC-X11
<b>REAR SHOCK</b>	Rockshox Monarch RT	<b>CRANKSET</b>	SRAM NX 11 speed 28T, L: S = 170mm, M/L =175mm	<b>BRAKES</b>	Sram Level hydraulic disc brakes, 180mm front 180mm rear rotors
<b>HEADSET</b>	A-head semi integrated, for tapered 1.8-1.5 head tube, semi cartridge bearings with 8mm cone spacer	<b>BOTTOM BRACKET</b>	BB91 press fit cartridge bearings	<b>WHEELS</b>	29" 32 hole F/V double wall alloy rims with eyelets, stainless spokes
<b>HANDLEBAR</b>	Factor butted alloy flat bar bore: 31.8mm W: 700mm, sweep: 9°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Veetire Rail Tracker 29 x 2.2" 27TPI
		<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Factor MTB sport saddle
		<b>R. DERAILLEUR</b>	SRAM NX 11 speed	<b>SEATPOST/ CLAMP</b>	Factor 31.6mm alloy, micro adjust with twin bolt head, L:400mm
		<b>SHIFT LEVERS</b>	SRAM NX 11 speed	<b>EXTRAS</b>	N/A





MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

27.5" plus Carbon Full Suspension frame. 130mm rear wheel travel.

Boost 110mm/148mm front and rear hubs.

Manitou Magnum Comp fork, 27.5" plus, 140mm Travel

SRAM GX/X1, 1 x 11 shifting.

KS LEV INTEGRA seat post.

SRAM GUIDE R hydraulic disc brakes.

Veetire Rail Bull Dozer 27.5" x 2.80" Folding Tubeless ready 120 TPI

Tubeless ready Sun Ringle DUROC 40 rim

### CODES

	S	M	L
Matte nude carbon / gloss black	17141	17142	17143

### GEOMETRY

	S	M	L
STACK	607	626	626
REACH	411	434	451
STAND OVER HEIGHT	n/a	n/a	n/a
EFFECTIVE TOP TUBE	585	613	630
SEAT TUBE (CENTRE TO TOP)	380	430	492
SEAT ANGLE	74.0°	74.0°	74.0°
HEAD TUBE LENGTH	95	115	115
HEAD ANGLE	68.0°	68.0°	68.0°
WHEEL BASE	1136	1165	1185
CHAIN STAY LENGTH	447	447	447
BB DROP	48	48	48
FORK RAKE	51	51	51
AXLE TO CROWN	531	531	531
REAR DROPOUT SPACING	148	148	148

### SPECIFICATIONS

<b>FRAME</b>	27.5" Plus Carbon Dual Suspension Frame, UD carbon, 120mm (5") travel. 1-1/8-1.5" head tube, 12x148mm Boost	<b>HEAD STEM</b>	Factor 3D forged stem, 31.8mm 4 bolt stem, Ext: S/M/L=45mm	<b>CHAIN</b>	KMC X-11
<b>FORK</b>	Manitou Magnum Comp, Tapered alloy steerer, 140mm travel with Q15 Thru Axle	<b>CRANKSET</b>	SRAM GX-1201 Press fit 1x 11 speed crank 28T L: S=170mm, M/L=175mm	<b>BRAKES</b>	SRAM Guide R hydraulic disc brakes, 180mm front 160mm rear rotors
<b>REAR SHOCK</b>	Rockshox Monarch RT	<b>BOTTOM BRACKET</b>	BB91 press fit cartridge bearings	<b>WHEELS</b>	27.5" Sun Ringle Duroc 40 tubeless ready 32h, 12 x 148mm rear and 15mm Thru Axle front hub
<b>HEADSET</b>	A-head semi integrated, for tapered 1.8-1.5 head tube, cartridge bearings	<b>PEDALS</b>	Nil	<b>TYRES</b>	Veetire Bull Dozer 27 x 2.8, 120 TPI, tubeless ready, folding.
<b>HANDLEBAR</b>	Factor alloy riser bar 31.8mm W: 740mm, sweep: 5°	<b>F. DERAILLEUR</b>	Nil	<b>SADDLE</b>	Factor MTB sport saddle
<b>GRIP</b>	Low profile Kraton rubber lock on grips	<b>R. DERAILLEUR</b>	SRAM X-11 speed	<b>SEATPOST/CLAMP</b>	KS LEV Dropper Post 31.6mm, Quick release seat post clamp
		<b>SHIFT LEVERS</b>	SRAM X-11 speed trigger shifter	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	SRAM 11 speed cassette 10 - 42T		

MTB

ROAD

LIFESTYLE

YOUTH



## KEY FEATURES

Apollo's 27.5" x 140mm travel, floating pivot enduro full suspension, Tapered H/T, 12 x 142mm Rear dropout.

Manitou Minute Pro 140mm Travel Suspension fork, with lockout and tapered steer tube.

SRAM GX, 1 x 11 shifting.

Kenda 27.5 x 2.35 Nevegal tyres.

Sealed bearing hubs with Sun Ringle Helix Tubeless ready rims and Stans No tubs rim tape.

SRAM Guide R Hydraulic Brakes, 180mm Front and 160mm rear.

QR15 Front Axle and Syntace X-12 Rear Axle.

## CODES

	S	M	L
Matte Black / Matte Red	17144	17145	17146

## GEOMETRY

	S	M	L
STACK	597	601	620
REACH	403	427	451
STAND OVER HEIGHT	n/a	n/a	n/a
EFFECTIVE TOP TUBE	580	605	640
SEAT TUBE (CENTRE TO TOP)	390	432	483
SEAT ANGLE	73.5°	73.5°	73.0°
HEAD TUBE LENGTH	115	120	140
HEAD ANGLE	66.3°	66.3°	66.3°
WHEEL BASE	1178	1204	1242
CHAIN STAY LENGTH	450	450	450
BB DROP	20	20	20
FORK RAKE	42	42	42
AXLE TO CROWN	535	535	535
REAR DROPOUT SPACING	142	142	142

## SPECIFICATIONS

<b>FRAME</b>	27.5" Floating shock dual suspension frame, 6061 alloy with 130mm (5") travel. 1-1/8-1.5" head tube, BB91 Press fit bottom bracket, 12x142mm rear axle, internal cable routing
<b>FORK</b>	Manitou Minute Pro Tapered alloy steerer, 140mm travel with Q15 Thru Axle
<b>REAR SHOCK</b>	Rockshox Monarch RT
<b>HEADSET</b>	A-head semi integrated, for tapered 1.8-1.5 head tube, cartridge bearings
<b>HANDLEBAR</b>	Factor alloy riser bar 31.8mm W: 740mm, sweep: 5°

<b>GRIP</b>	Low profile Kraton rubber lock on grips
<b>HEAD STEM</b>	Factor 3D forged stem, 31.8mm 4 bolt stem, Ext: S/M/L=45mm
<b>CRANKSET</b>	SRAM S-1000 Press fit 1x 11 speed crank 28T L: S=170mm, M/L =175mm
<b>BOTTOM BRACKET</b>	BB91 press fit cartridge bearings
<b>PEDALS</b>	Nil
<b>F. DERAILLEUR</b>	Nil
<b>R. DERAILLEUR</b>	SRAM GX 11 speed
<b>SHIFT LEVERS</b>	SRAM GX 11 speed trigger shifter

<b>CASSETTE</b>	SRAM 11 speed cassette 10 - 42T
<b>CHAIN</b>	KMC X-11
<b>BRAKES</b>	SRAM Guide R hydraulic disc brakes, 180mm front 160mm rear rotors
<b>WHEELS</b>	27.5" Sun Ringle Helix 25 tubeless ready 32h, 12 x 142mm rear and 15mm Thru Axle front hub
<b>TYRES</b>	Kenda Nevegal 27 x 2.35, 66 TPI, folding.
<b>SADDLE</b>	Factor MTB sport saddle
<b>SEATPOST/CLAMP</b>	KS ETEN Dropper Post 31.6mm, Quick release seat post clamp
<b>EXTRAS</b>	N/A

# ASPIRE D 20

MTB

ROAD

LIFESTYLE

YOUTH



## KEY FEATURES

Apollo's 27.5" x 140mm travel, floating pivot enduro full suspension, Tapered H/T, 12 x 142mm Rear dropout.

Manitou Minute Ltd 140mm Travel Suspension fork, with lockout and tapered steer tube.

SRAM NX 1 x 11 shifting

Kenda 27.5 x 2.35 Nevegal tyres.

Sealed bearing hubs with Sun Ringle rims.

SRAM Level Hydraulic Brakes, 180mm Front and 160mm rear.

QR15 Front Axle and Syntace X-12 Rear Axle.

## CODES

	S	M	L
Matte Black / Matte Blue / Matte Red	17147	17148	17149

## GEOMETRY

	S	M	L
STACK	597	601	620
REACH	403	427	451
STAND OVER HEIGHT	n/a	n/a	n/a
EFFECTIVE TOP TUBE	580	605	640
SEAT TUBE (CENTRE TO TOP)	390	432	483
SEAT ANGLE	73.5°	73.5°	73.0°
HEAD TUBE LENGTH	115	120	140
HEAD ANGLE	66.3°	66.3°	66.3°
WHEEL BASE	1178	1204	1242
CHAIN STAY LENGTH	450	450	450
BB DROP	20	20	20
FORK RAKE	42	42	42
AXLE TO CROWN	535	535	535
REAR DROPOUT SPACING	142	142	142

## SPECIFICATIONS

<b>FRAME</b>	27.5" Floating shock dual suspension frame, 6061 alloy with 130mm (5") travel. 1-1/8-1.5" head tube, BB91 Press fit bottom bracket, 12x142mm rear axle, internal cable routing	<b>GRIP</b>	Low profile Kraton rubber lock on grips	<b>CASSETTE</b>	SRAM 11 speed cassette 11 - 42T
<b>FORK</b>	Manitou Minute Comp. Tapered alloy steerer, 140mm travel with QR15 Thru Axle	<b>HEAD STEM</b>	Factor 3D forged stem, 31.8mm 4 bolt stem, Ext: S/M/L=45mm	<b>CHAIN</b>	KMC X-11
<b>REAR SHOCK</b>	Rockshox Monarch R	<b>CRANKSET</b>	SRAM NX 11 speed 28T, L: S = 170mm, M/L = 175mm	<b>BRAKES</b>	Sram Level hydraulic disc brakes, 180mm front 160mm rear rotors
<b>HEADSET</b>	A-head semi integrated, for tapered 1.8-1.5 head tube, cartridge bearings	<b>BOTTOM BRACKET</b>	BB91 press fit cartridge bearings	<b>WHEELS</b>	27.5" Sun Ringle Inferno 25mm wide alloy 32h welded alloy rims. 12 x 142mm rear hub and 15mm Thru Axle front hub
<b>HANDLEBAR</b>	Factor alloy riser bar 31.8mm W: 740mm, sweep: 5°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda Nevegal 27 x 2.35, 66 TPI, folding.
		<b>F. DERAILLEUR</b>	Nil	<b>SADDLE</b>	Factor MTB sport saddle
		<b>R. DERAILLEUR</b>	SRAM NX 11 speed	<b>SEATPOST/CLAMP</b>	31.6mm alloy, micro adjust, L:400mm. Quick release seat post clamp
		<b>SHIFT LEVERS</b>	SRAM NX 11 speed	<b>EXTRAS</b>	N/A

MTB

ROAD

LIFESTYLE

YOUTH



### KEY FEATURES

29" A-Grade Super-Light weight carbon, with tapered head tube and Syntax X-12 rear dropout.

Hutchinson Black Mamba 29" x 2.0" MTB tyres

DT SWISS XR-1501 Spline wheelset.

Sram XX 1 x 11 Shifting.

Rockshox RS1 ACS Front Suspension, Air with Lockout.

Shimano XTR Hydraulic disc brakes with 160mm rotors

Oversized Answer Protaper Carbon handlebar and A-head stem.

15mm Front Axle

Syntax X-12 Rear axle and dropout.

### CODES

	S	M	L
Matte Nude Carbon / Gloss Red / Gloss White	16293	16294	16295

### GEOMETRY

	S	M	L
STACK	617	636	641
REACH	404	405	420
EFFECTIVE TOP TUBE	593	606	628
SEAT TUBE (CENTRE TO TOP)	382	452	487
SEAT ANGLE	73.0°	72.5°	72.0°
HEAD TUBE LENGTH	100	120	125
HEAD ANGLE	72.0°	72.0°	72.0°
WHEEL BASE	1062	1075	1097
CHAIN STAY LENGTH	435	435	435
BB DROP	60	60	60
FORK RAKE	51	51	51
AXLE TO CROWN	505	505	505
REAR DROPOUT SPACING	12 x 142	12 x 142	12 x 142

### SPECIFICATIONS

<b>FRAME</b>	Hi modulus Carbon 29er frame with tapered 1 1/8-1.5 head tube, BB91 press fit bottom bracket, 12 x142mm Syntax rear Thru Axle, direct mount front derailleur, post mount rear brake calliper	<b>GRIP</b>	Ultra light foam racing grips	<b>BRAKES</b>	Shimano XTR BR-M985 with 6 bolt rotors
<b>FORK</b>	Rock Shox RSA carbon upside down suspension fork. Tapered alloy steerer, RSA Thru Axle w/51mm offset, single air, 100mm travel, rebound adjust, mag lowers, remote lockout	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext:S/ M=90mm, L=100mm,	<b>WHEELS</b>	DT XR 1501 Spline alloy tubeless ready 29er wheelset with welded rims, 28 hole 3 cross front and rear. Precision DT hubs with sealed bearings, DT competition straight pull spokes. Thru Axle front hub to suit Rock shox RSA forks, 12 x 142mm rear axle 1520g
<b>REAR SHOCK</b>	N/A	<b>CRANKSET</b>	SRAM XX-1 press fit 11 speed 32T L: S/M/ L=175mm	<b>TYRES</b>	Hutchinson Black Mamba tubeless ready 29 x 2.0', 127tpi folding
<b>HEADSET</b>	A-head semi integrated, for tapered 1.8-1.5 head tube, semi cartridge bearings with 8mm cone spacer	<b>BOTTOM BRACKET</b>	BB91 press fit cartridge bearings	<b>SADDLE</b>	Prologo X Zero with Tirox rail custom design
<b>HANDLEBAR</b>	Answer Pro taper carbon SL. 720mm extra wide flat bar, 31.8mm, sweep: 8°	<b>PEDALS</b>	NIL	<b>SEATPOST/ CLAMP</b>	Answer carbon SL 27.2mm twin bolt micro adjust 400mm
		<b>F. DERAILLEUR</b>	N/A	<b>EXTRAS</b>	N/A
		<b>R. DERAILLEUR</b>	SRAM XX-1 11 speed		
		<b>SHIFT LEVERS</b>	SRAM XX-1 11 speed trigger shifter		
		<b>CASSETTE</b>	SRAM XG 1080 11 speed 10-42T		
		<b>CHAIN</b>	KMC-X11 SL		



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

29" Light weight carbon, with tapered head tube and Syntace X-12 rear dropout.

Hutchinson Python 2, 29" x 2.25" MTB tyres, with double wall Weinmann rims.

Sun Ringle Helix Tubeless ready rim with STANS NO TUBES rim tape.

SRAM GX-11 x 11 Shifting.

Manitou Marvel Comp Air Suspension fork, QR15 axle, with tapered steer tube.

Hayes Radar Hydraulic disc brakes with 160mm L-Series rotors

Oversized Alloy handlebar and A-head stem.

15mm Front Axle, with sealed bearing hubs.

Syntace X-12 Rear axle and dropout.

CODES	S	M	L
Gloss Blue / Gloss Red / Gloss Black	16296	16297	16298

GEOMETRY	S	M	L
STACK	617	636	641
REACH	404	405	420
EFFECTIVE TOP TUBE	593	606	628
SEAT TUBE (CENTRE TO TOP)	382	452	487
SEAT ANGLE	73.0°	72.5°	72.0°
HEAD TUBE LENGTH	100	120	125
HEAD ANGLE	72.0°	72.0°	72.0°
WHEEL BASE	1062	1075	1097
CHAIN STAY LENGTH	435	435	435
BB DROP	60	60	60
FORK RAKE	51	51	51
AXLE TO CROWN	505	505	505
REAR DROPOUT SPACING	12 x 142	12 x 142	12 x 142

## SPECIFICATIONS

<b>FRAME</b>	Hi modulus carbon 29er frame with tapered 1 1/8-1.5 head tube, BB91 press fit bottom bracket, direct mount front derailleur, 12x142 Syntace rear through axle, post mount rear brake calliper.	<b>GRIP</b>	Ultra light foam racing grips	<b>BRAKES</b>	Hayes Radar hydraulic disc brakes with lever adjust, 160mm rotors
<b>FORK</b>	Manitou Marvel Comp 29 tapered alloy steerer, Absolute plus ISO air dampening, 100mm travel with QR15 Thru Axle, rebound adjust, mag lowers	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext:S/ M=90mm, L=100mm,	<b>WHEELS</b>	Sun Ringle Helix Tubeless ready sleeved rim with Stans rim tapes, 32 hole high flange front with 15mm Thru Axle 32 hole rear with 12mm x 142 through axle rear with premium cartridge sealed bearings
<b>REAR SHOCK</b>	N/A	<b>CRANKSET</b>	SRAM GX-1001 Press fit, 11 speed X-Sync 30T L: S=170mm, M/L =175mm	<b>TYRES</b>	Hutchinson Python 2 tubeless ready folding bead 29 x 2.1 127TPI
<b>HEADSET</b>	A-head semi integrated, for tapered 1.8-1.5 head tube, cartridge bearings with 8mm cone spacer	<b>BOTTOM BRACKET</b>	BB91 press fit cartridge bearings	<b>SADDLE</b>	Factor MTB team saddle
<b>HANDLEBAR</b>	Factor butted alloy flat bar bore: 31.8mm W: 700mm, sweep: 9°	<b>PEDALS</b>	Low profile high impact resin	<b>SEATPOST/ CLAMP</b>	Factor 27.2mm alloy, micro adjust with twin bolt head, L:400mm
		<b>F. DERAILLEUR</b>	N/A	<b>EXTRAS</b>	N/A
		<b>R. DERAILLEUR</b>	SRAM GX-11 11 speed		
		<b>SHIFT LEVERS</b>	SRAM GX-11 11 speed trigger shifter		
		<b>CASSETTE</b>	SRAM XG 1150 11 speed 10-42T		
		<b>CHAIN</b>	KMC-X11		



### KEY FEATURES

29" light weight Butted Alloy MTB specific frame.

Kenda 29" x 2.1" MTB tyres, with new double wall Weinmann rims.

1 x 10 speed shifting, with Sunrace 11-42T cassette and 28T Alloy narrow/wide chainring

Rock Shox XC30 100mm travel front suspension with hydraulic lockout

Promax ST hydraulic disc brakes front and rear.

Oversized alloy handlebar and A-head stem.

### CODES

	S	M	L	XL
Matte Black / Gloss Fluoro Green / Gloss Black	17165	17166	17167	17168

### GEOMETRY

	S	M	L	XL
STACK	609	618	632	642
REACH	389	406	410	427
STAND OVER HEIGHT	421	440	468	492
EFFECTIVE TOP TUBE	575	595	615	635
SEAT TUBE (CENTRE TO TOP)	400	430	480	520
SEAT ANGLE	73.0°	73.0°	72.0°	72.0°
HEAD TUBE LENGTH	100	110	120	130
HEAD ANGLE	69.0°	69.0°	70.0°	70.0°
WHEEL BASE	1092	1110	1114	1131
CHAIN STAY LENGTH	435	435	435	435
BB DROP	60	60	60	60
FORK RAKE	51	51	51	51
AXLE TO CROWN	510	510	510	510
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Double butted 6061 alloy 29er frame. Fluted head tube, formed stays for added rigidity with taper wall technology	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext:S/ M=75mm, L=90mm, XL=105mm,	<b>CHAIN</b>	KMC X-10
<b>FORK</b>	Rockshox XC30 29", 100mm travel. Coil spring, alloy crown and magnesium lowers	<b>CRANKSET</b>	Samox TAF26 28T L: S=170mm, M/ L=175mm	<b>BRAKES</b>	Promax Solve ST hydraulic disc brakes with reach adjust, 160mm rotors
<b>REAR SHOCK</b>	N/A	<b>BOTTOM BRACKET</b>	SRAM splined sealed cartridge bottom bracket	<b>WHEELS</b>	29" Weinmann U-26 alloy double wall disc rim, 32 hole F/V, anodised disc hubs and stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda 29 x 2.1", wire bead
<b>HANDLEBAR</b>	Factor butted alloy flat bar bore: 31.8mm W: 700mm, sweep: 9°	<b>F. DERAILLEUR</b>	Nil	<b>SADDLE</b>	Factor MTB sport saddle
<b>GRIP</b>	Ultra light hex shaped foam racing grips	<b>R. DERAILLEUR</b>	SRAM X-5	<b>SEATPOST/ CLAMP</b>	27.2mm alloy, micro adjust with twin bolt head, L:400mm
		<b>SHIFT LEVERS</b>	Sram X5 Trigger, 10 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Sunrace CSMS3 10 speed cassette 11 - 42T		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

29" MTB specific Alloy Frame

Kenda 29" x 2.1" MTB tyres, with new double wall Weinmann rims.

Oversized 31.8mm alloy handlebar

Oversized 31.8mm alloy A-head stem.

27 Speed SRAM X5/X7 shifting.

Suntour XCT 100mm travel front suspension with hydraulic lockout.

Promax ST Hydraulic disc brakes front and rear.

### CODES

	S	M	L	XL
Matte Black / Gloss Fluoro Orange / Gloss Black	17169	17170	17171	17172

### GEOMETRY

	S	M	L	XL
STACK	609	618	632	642
REACH	389	406	410	427
STAND OVER HEIGHT	421	440	468	492
EFFECTIVE TOP TUBE	575	595	615	635
SEAT TUBE (CENTRE TO TOP)	400	430	480	520
SEAT ANGLE	73.0°	73.0°	72.0°	72.0°
HEAD TUBE LENGTH	100	110	120	130
HEAD ANGLE	69.0°	69.0°	70.0°	70.0°
WHEEL BASE	1092	1110	1114	1131
CHAIN STAY LENGTH	435	435	435	435
BB DROP	60	60	60	60
FORK RAKE	51	51	51	51
AXLE TO CROWN	510	510	510	510
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Butted 6061 alloy disc specific 29er frame with taper wall technology and integrated head tube	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext:S/ M=75mm, L=90mm, XL=105mm,	<b>CHAIN</b>	KMC Z-99
<b>FORK</b>	Suntour XCT-HLO, 100mm travel with hydraulic lockout and preload, 51mm offset, alloy crown and lowers.	<b>CRANKSET</b>	Suntour XCM 414, 44 x 32 x 22T L: S=170mm, M/L/XL=175mm	<b>BRAKES</b>	Promax Solve ST hydraulic disc brakes with reach adjust, 160mm rotors
<b>REAR SHOCK</b>	N/A	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	29" Weinmann U-26 alloy double wall disc rim, 32 hole F/V, anodised disc hubs and stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda 29 x 2.1", wire bead
<b>HANDLEBAR</b>	Factor butted alloy flat bar bore: 31.8mm W: 700mm, sweep: 9°	<b>F. DERAILLEUR</b>	SRAM X-5	<b>SADDLE</b>	Factor MTB sport saddle
<b>GRIP</b>	Ultra light hex shaped foam racing grips	<b>R. DERAILLEUR</b>	SRAM X-7	<b>SEATPOST/ CLAMP</b>	Alloy 27.2mm alloy, L:400mm, micro adjust with quick release clamp
		<b>SHIFT LEVERS</b>	SRAM X-5	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	SRAM cassette 11 - 34T		



### KEY FEATURES

- 29" MTB specific Alloy Frame
- Upgraded Kenda 29" x 2.1" MTB tyres, with new double wall Weinmann rims.
- Oversized 31.8mm alloy A-head stem
- Oversized 31.8mm handlebar.
- 24 Speed Shimano Rapid-Fire shifting.
- Suntour XCT 100mm travel front suspension with hydraulic lockout.
- Upgraded Promax ST Hydraulic disc brakes front and rear.
- Selle Royal saddle for maximum riding comfort
- New reinforced resin pedals

### CODES

	S	M	L	XL
Matte Black / Matte White / Matte Red	17173	17174	17175	17176
Gloss Blue / Gloss Black / Gloss Red	17177	17178	17179	17180

### GEOMETRY

	S	M	L	XL
STACK	599	609	627	642
REACH	392	409	411	427
STAND OVER HEIGHT	413	432	464	489
EFFECTIVE TOP TUBE	575	595	615	635
SEAT TUBE (CENTRE TO TOP)	400	430	480	520
SEAT ANGLE	73.0°	73.0°	72.0°	72.0°
HEAD TUBE LENGTH	100	110	125	140
HEAD ANGLE	69.0°	69.0°	70.0°	70.0°
WHEEL BASE	1102	1123	1123	1144
CHAIN STAY LENGTH	450	450	450	450
BB DROP	60	60	60	60
FORK RAKE	51	51	51	51
AXLE TO CROWN	500	500	500	500
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Butted 6061 alloy disc specific 29er frame with taper wall technology and integrated head tube	<b>HEAD STEM</b>	Forged alloy A-head Bore: 31.8mm Ext: S/M=75mm, L=90mm, XL=105mm	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	Suntour XCT-HLO, 100mm travel with hydraulic lockout and preload, 51mm offset, alloy crown and lowers.	<b>CRANKSET</b>	Suntour XCT 42 x 32 x 22T L: S/M=170mm, L/XL=175mm	<b>BRAKES</b>	Promax Solve ST hydraulic disc brakes with reach adjust, 160mm rotors
<b>REAR SHOCK</b>	N/A	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	29" Weinmann U-26 alloy double wall disc rim, 32 hole A/V, anodised disc hubs and stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda 29 x 2.1", wire bead
<b>HANDLEBAR</b>	Alloy flat bar bore: 31.8mm W: 620mm, sweep: 9°	<b>F. DERAILLEUR</b>	Shimano FD-TY700	<b>SADDLE</b>	Factor MTB sport saddle
<b>GRIP</b>	Kraton rubber closed end grips	<b>R. DERAILLEUR</b>	Shimano Acera	<b>SEATPOST/CLAMP</b>	Alloy 27.2mm alloy, L:400mm, micro adjust with quick release clamp
		<b>SHIFT LEVERS</b>	Shimano Altus 24 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano HG-200 8 speed cassette 12-32T		





MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

29" MTB specific Alloy Frame

Kenda 29" x 2.1" MTB tyres, with new double wall Weinmann rims.

Oversized 31.8mm alloy A-head stem

Oversized 31.8mm handlebar.

21 speed Shimano EZ-Fire shifting.

80mm travel front suspension with lockout.

Tektro Mechanical Disk brakes front and rear with 160mm rotors

Selle Royal saddle for maximum riding comfort.

New reinforced resin pedals

### CODES

	S	M	L	XL
Matte Black / Matte Red / Matte White	17181	17182	17183	17184
Gloss Charcoal / Gloss Black / Gloss White	17185	17186	17187	17188

### GEOMETRY

	S	M	L	XL
STACK	599	609	627	642
REACH	392	409	411	427
STAND OVER HEIGHT	413	432	464	489
EFFECTIVE TOP TUBE	575	595	615	635
SEAT TUBE (CENTRE TO TOP)	400	430	480	520
SEAT ANGLE	73.0°	73.0°	72.0°	72.0°
HEAD TUBE LENGTH	100	110	125	140
HEAD ANGLE	69.0°	69.0°	70.0°	70.0°
WHEEL BASE	1102	1123	1123	1144
CHAIN STAY LENGTH	450	450	450	450
BB DROP	60	60	60	60
FORK RAKE	51	51	51	51
AXLE TO CROWN	500	500	500	500
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Butted 6061 alloy disc specific 29er frame with taper wall technology and integrated head tube	<b>HEAD STEM</b>	Forged alloy A-head Bore: 31.8mm Ext: S/M=90mm, L/XL=105mm	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	29" suspension fork, 80mm travel, coil spring, alloy crown and alloy lowers.	<b>CRANKSET</b>	Cold forged 42 x 32 x 22T L=170mm	<b>BRAKES</b>	Tektro MD-M280 mechanical disc brakes with 160mm rotors
<b>REAR SHOCK</b>	N/A	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	29" Weinmann X-M1 alloy double wall disc rim, 32 hole A/V, anodised disc hubs and stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda 29 x 2.1", wire bead
<b>HANDLEBAR</b>	Alloy flat bar bore: 31.8mm W: 640mm, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano TY-500	<b>SADDLE</b>	Factor MTB sport saddle
<b>GRIP</b>	Kraton rubber closed end grips	<b>R. DERAILLEUR</b>	Shimano Altus 21 speed	<b>SEATPOST/CLAMP</b>	Alloy 27.2mm alloy, L:350mm, micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-41 21 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano HG-20 7 speed cassette 12-28T		

MTB

ROAD

LIFESTYLE

YOUTH



## KEY FEATURES

27.5" Light weight carbon, with tapered head tube and Syntax X-12 rear dropout.

Hutchinson Python 2, 27.5" x 2.25" MTB tyres

Sun Ringle Helix Tubeless ready rim with STANS NO TUBES rim tape.

SRAM GX-11 x 11 Shifting.

Manitou Marvel Comp Air Suspension fork, QR15 axle, with Tapered steer tube.

Hayes Radar Hydraulic disc brakes with 160mm L-Series rotors

Oversized Alloy handlebar and A-head stem.

15mm Front Axle, with sealed bearing hubs.

Syntax X-12 Rear axle and dropout.

## CODES

	S	M	L	XL
Gloss Blue / Gloss Red / Gloss Black	16334	16335	16336	16337

## GEOMETRY

	S	M	L	XL
STACK	594	596	613	627
REACH	382	419	438	453
EFFECTIVE TOP TUBE	552	590	614	639
SEAT TUBE (CENTRE TO TOP)	356	432	483	532
SEAT ANGLE	74.0°	74.0°	74.0°	73.5°
HEAD TUBE LENGTH	105	105	120	135
HEAD ANGLE	70.0°	70.5°	71.0°	71.0°
WHEEL BASE	1052	1085	1105	1124
CHAIN STAY LENGTH	430	430	430	430
BB DROP	52	52	52	52
FORK RAKE	44	44	44	44
AXLE TO CROWN	490	490	490	490
REAR DROPOUT SPACING	12 x 142	12 x 142	12 x 142	12 x 142

## SPECIFICATIONS

<b>FRAME</b>	Hi Modulus 27.5" carbon frame with tapered 1 1/8-1.5 head tube, BB91 press fit bottom bracket, 12 x 142 syntaxe rear through axle, direct mount front derailleur, post mount rear brake calliper
<b>FORK</b>	Manitou Marvel Comp 27 tapered alloy steerer, QR 15 Thru Axle, absolute plus ISO air dampening, 100mm travel, rebound adjust, mag lowers
<b>REAR SHOCK</b>	N/A
<b>HEADSET</b>	A-head semi integrated, for tapered 1.8-1.5 head tube, sealed cartridge bearings with 8mm cone spacer
<b>HANDLEBAR</b>	Factor alloy flat bar bore: 31.8mm W: 700mm, sweep: 9°

<b>GRIP</b>	Ultra light foam racing grips
<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext:S=90, M=100mm, L/XL=110mm
<b>CRANKSET</b>	SRAM GX-1001 Press fit, 11 speed X-Sync 30T L: S=170mm, M/L/XL=175mm
<b>BOTTOM BRACKET</b>	BB91 press fit cartridge bearings
<b>PEDALS</b>	Low profile high impact resin
<b>F. DERAILLEUR</b>	N/A
<b>R. DERAILLEUR</b>	SRAM GX-11 speed
<b>SHIFT LEVERS</b>	SRAM GX-11 speed trigger shifter
<b>CASSETTE</b>	SRAM XG 1150 11 speed 10-42T
<b>CHAIN</b>	KMC-X11

<b>BRAKES</b>	Hayes Radar hydraulic disc brakes with lever adjust, 160mm rotors
<b>WHEELS</b>	Custom Sun Ringle Helix tubeless ready 32h eyeleted sleeved alloy rims with Stans rim tapes. QR rear with 5 premium sealed cartridge bearings and 15mm Thru Axle front hub with premium cartridge sealed bearings.
<b>TYRES</b>	Hutchinson Python 2 27 x 2.25", tubeless ready folding bead 127tpi
<b>SADDLE</b>	Factor MTB team saddle
<b>SEATPOST/ CLAMP</b>	Alloy two bolt micro adjust, 27.2mm, L:400mm
<b>EXTRAS</b>	N/A



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

27.5" MTB specific Alloy Frame

Kenda 27.5" x 2.1" MTB tyres, with double wall Weinmann rims.

1 x 10 speed shifting, with Sunrace 11-42T cassette and 28T Alloy narrow/wide chainring

Upgrade Rock Shox XC-30 120mm travel fork with lockout.

Oversized 31.8mm alloy A-head stem

Oversized 31.8mm handlebar.

New Promax ST Hydraulic disc brakes front and rear.

New Weinmann double wall alloy rims.

New reinforced resin pedals

### CODES

	S	M	L
Matte Black / Gloss Black	17189	17190	17191

### GEOMETRY

	S	M	L
STACK	610	614	633
REACH	399	412	447
STAND OVER HEIGHT	436	462	495
EFFECTIVE TOP TUBE	585	600	640
SEAT TUBE (CENTRE TO TOP)	410	460	510
SEAT ANGLE	73.0°	73.0°	73.0°
HEAD TUBE LENGTH	115	120	140
HEAD ANGLE	68.5°	68.5°	68.5°
WHEEL BASE	1099	1119	1160
CHAIN STAY LENGTH	440	440	440
BB DROP	45	45	45
FORK RAKE	42	42	42
AXLE TO CROWN	510	510	510
REAR DROPOUT SPACING	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Lightweight 27.5" double butted alloy disc specific frame with integrated head tube, snake stays and replaceable derailleur hanger	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext: S/M/L=45mm	<b>CHAIN</b>	KMC X-10
<b>FORK</b>	Rock Shox XC-30 27.5", 120mm travel with hydraulic lockout and preload	<b>CRANKSET</b>	Samox TAF26 28T L: S=170mm, M/L=175mm	<b>BRAKES</b>	Promax Solve ST hydraulic disc brakes with reach adjust, 160mm rotors
<b>REAR SHOCK</b>	N/A	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	27.5" Weinmann U-26 alloy 32 hole F/V double wall disc specific rims, alloy disc hubs and stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda 27 x 2.35" wire bead
<b>HANDLEBAR</b>	Alloy low riser, W: 700mm, R: 15mm, bore: 31.8mm, sweep: 5°	<b>F. DERAILLEUR</b>	Nil	<b>SADDLE</b>	Factor MTB sport saddle
<b>GRIP</b>	Ultra light hex shaped foam grip	<b>R. DERAILLEUR</b>	Sram X5	<b>SEATPOST/CLAMP</b>	Alloy two bolt micro adjust, 27.2mm, L:350mm
		<b>SHIFT LEVERS</b>	Sram X5 Trigger, 10 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Sunrace CSMS3 10 speed cassette 11 - 42T		



### KEY FEATURES

27.5" MTB specific Alloy Frame

Kenda 27.5" x 2.1" MTB tyres, with double wall Weinmann rims.

24 Speed Shimano Rapid-Fire shifting with Cassette

Oversized 31.8mm alloy A-head stem

Oversized 31.8mm handlebar.

RST Gila 100mm travel front suspension.

New Promax ST Hydraulic disc brakes front and rear.

New Weinmann double wall alloy rims.

New reinforced resin pedals

Selle Royal saddle for maximum riding comfort.

### CODES

	XS	S	M	L	XL
Matte Black / Matte Charcoal / Matte Red	17192	17193	17194	17195	17196
Gloss Black / Gloss White / Gloss Blue	17197	17198	17199	17200	17201

### GEOMETRY

	XS	S	M	L	XL
STACK	593	607	619	630	647
REACH	370	375	396	412	426
STAND OVER HEIGHT	406	438	456	481	512
EFFECTIVE TOP TUBE	540	555	585	605	630
SEAT TUBE (CENTRE TO TOP)	355	410	440	480	530
SEAT ANGLE	74.0°	73.5°	73.0°	73.0°	72.5°
HEAD TUBE LENGTH	110	125	135	145	160
HEAD ANGLE	69.0°	69.0°	69.5°	70.0°	70.5°
WHEEL BASE	1056	1078	1094	1108	1121
CHAIN STAY LENGTH	440	440	440	440	440
BB DROP	45	45	45	45	45
FORK RAKE	42	42	42	42	42
AXLE TO CROWN	495	495	495	495	495
REAR DROPOUT SPACING	135	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Lightweight 27.5" double butted alloy disc specific frame with integrated head tube, snake stays and replaceable derailleur hanger	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext: XS/S=70mm, M/L=90mm, XL=105mm	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	RST Gila 27.5, 100mm travel, mechanical lockout, preload.	<b>CRANKSET</b>	Suntour XCT 42 x 32 x 22T L: XS/S=170, M/L/XL=175mm	<b>BRAKES</b>	Promax Solve ST hydraulic disc brakes with reach adjust, 160mm rotors
<b>REAR SHOCK</b>	N/A	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	27.5" alloy 32 hole A/V double wall disc specific rims, alloy disc hubs and stainless spokes
<b>HEADSET</b>	A-head 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda 27 x 2.1" wire bead
<b>HANDLEBAR</b>	Alloy low riser, W: 640mm, R: 20mm, bore: 31.8mm, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano TY-700	<b>SADDLE</b>	Factor MTB sport saddle
<b>GRIP</b>	Kraton grip	<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SEATPOST/CLAMP</b>	Alloy micro adjust 27.2mm, L:350mm with QR clamp
		<b>SHIFT LEVERS</b>	Shimano Altus 24 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano HG-200 8 speed cassette 12-32T		

# ASPIRE 20



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

- 27.5" MTB specific Alloy Frame
- Kenda 27.5" x 2.1" MTB tyres, with double wall Weinmann rims.
- Oversized 31.8mm alloy A-head stem
- Oversized 31.8mm handlebar.
- 21 speed Shimano EZ-Fire shifting.
- 80mm travel front suspension with lockout.
- Tektro Mechanical Disk brakes front and rear with 160mm rotors
- New double wall alloy rims.
- New reinforced resin pedals
- Selle Royal saddle for maximum riding comfort.

CODES	XS	S	M	L	XL
Gloss Lime / Gloss Black / Gloss Blue	17202	17203	17204	17205	17206
Matte Black / Matte Blue / Matte Lime	17207	17208	17209	17210	17211

GEOMETRY	XS	S	M	L	XL
STACK	593	607	619	630	647
REACH	370	375	396	412	426
STAND OVER HEIGHT	406	438	456	481	512
EFFECTIVE TOP TUBE	540	555	585	605	630
SEAT TUBE (CENTRE TO TOP)	355	410	440	480	530
SEAT ANGLE	74.0°	73.5°	73.0°	73.0°	72.5°
HEAD TUBE LENGTH	110	125	135	145	160
HEAD ANGLE	69.0°	69.0°	69.5°	70.0°	70.5°
WHEEL BASE	1056	1078	1094	1108	1121
CHAIN STAY LENGTH	440	440	440	440	440
BB DROP	45	45	45	45	45
FORK RAKE	42	42	42	42	42
AXLE TO CROWN	495	495	495	495	495
REAR DROPOUT SPACING	135	135	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	Lightweight 27.5" double butted alloy frame, snake stays and replaceable derailleur hanger	<b>HEAD STEM</b>	Alloy A-head 25.4mm Ext: XS/S=70mm, M/L=90mm, XL=105mm	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	27.5" suspension fork, 80mm travel	<b>CRANKSET</b>	Alloy MTB crank 42 x 32 x 22T L=170mm	<b>BRAKES</b>	Tektro MD-M280 mechanical disc brakes with 160mm rotors
<b>REAR SHOCK</b>	N/A	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	27.5" alloy 32 hole A/V double wall disc specific rims, alloy disc hubs and stainless spokes
<b>HEADSET</b>	A-head 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda 27 x 2.1" wire bead
<b>HANDLEBAR</b>	Low riser, W: 640mm, R: 20mm, bore: 31.8mm, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano TY-500	<b>SADDLE</b>	Factor MTB sport saddle
<b>GRIP</b>	Kraton grip	<b>R. DERAILLEUR</b>	Shimano Altus 21 speed	<b>SEATPOST/CLAMP</b>	Alloy micro adjust 27.2mm, L:350mm with QR clamp
		<b>SHIFT LEVERS</b>	Shimano EF-41 EZ FIRE 21 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano HG-20 7 speed cassette 12-28T		



## KEY FEATURES

- 27.5" Women's Specific MTB Alloy Frame
- Kenda 27.5" x 2.1" MTB tyres, with double wall Weinmann rims.
- Oversized 31.8mm alloy A-head stem
- Oversized 31.8mm handlebar.
- 21 speed Shimano EZ-Fire shifting.
- 80mm travel front suspension with lockout
- Tektro Mechanical Disk brakes front and rear with 160mm rotors
- New double wall alloy rims.
- New reinforced resin pedals
- Soft and comfortable women's specific saddle

## CODES

	XS	S	M
Gloss Pink / Gloss Black / Gloss Blue	17212	17213	17214

## GEOMETRY

	XS	S	M
STACK	584	602	616
REACH	373	381	397
STAND OVER HEIGHT	382	412	437
EFFECTIVE TOP TUBE	540	565	585
SEAT TUBE (CENTRE TO TOP)	355	400	440
SEAT ANGLE	74.0°	73.0°	73.0°
HEAD TUBE LENGTH	100	115	130
HEAD ANGLE	69.0°	70.0°	70.0°
WHEEL BASE	1058	1061	1082
CHAIN STAY LENGTH	435	435	435
BB DROP	45	45	45
FORK RAKE	42	42	42
AXLE TO CROWN	495	495	495
REAR DROPOUT SPACING	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	Lightweight female specific 27.5" double butted alloy frame, snake stays and replaceable derailleur hanger	<b>HEAD STEM</b>	Alloy A-head 25.4mm Ext: XS/S=90mm, M=90mm	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	27.5" suspension fork, 80mm travel	<b>CRANKSET</b>	Alloy MTB crank 42 x 32 x 22T L=170mm	<b>BRAKES</b>	Tektro MD-M280 mechanical disc brakes with 160mm rotors
<b>REAR SHOCK</b>	N/A	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	27.5" alloy 32 hole A/V double wall disc specific rims, alloy disc hubs and stainless spokes
<b>HEADSET</b>	A-head 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda 27 x 2.1" wire bead
<b>HANDLEBAR</b>	Low riser, W: 600mm, R: 20mm, bore: 31.8mm, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano TY-500	<b>SADDLE</b>	Factor MTB sport saddle
<b>GRIP</b>	Kraton grip	<b>R. DERAILLEUR</b>	Shimano Altus 21 speed	<b>SEATPOST/CLAMP</b>	Alloy micro adjust 27.2mm, L:350mm with QR clamp
		<b>SHIFT LEVERS</b>	Shimano EF-41 EZ FIRE 21 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano HG-20 7 speed cassette 12-28T		

# ASPIRE 10



MTB

ROAD

LIFESTYLE  
YOUTH

## KEY FEATURES

- 27.5" MTB specific Alloy Frame
- 27.5" x 2.1" MTB tyres, with double wall Weinmann rims.
- Oversized 31.8mm alloy A-head stem
- Oversized 31.8mm handlebar.
- 21 speed Shimano EZ-Fire shifting.
- 80mm travel front suspension.
- Low maintenance Promax V-Brakes.
- New double wall alloy rims.
- New reinforced resin pedals
- Selle Royal saddle for maximum riding comfort.

CODES	XS	S	M	L	XL
Gloss Navy Blue / Gloss Lime	17215	17216	17217	17218	17219
Gloss Black / Gloss Red / Gloss White	17220	17221	17222	17223	17224

GEOMETRY	XS	S	M	L	XL
STACK	570	593	605	616	633
REACH	372	384	410	427	431
STAND OVER HEIGHT	394	426	450	473	505
EFFECTIVE TOP TUBE	535	560	595	615	630
SEAT TUBE (CENTRE TO TOP)	355	400	440	480	530
SEAT ANGLE	74.0°	73.5°	73.0°	73.0°	72.5°
HEAD TUBE LENGTH	100	125	135	145	160
HEAD ANGLE	69.0°	69.0°	69.5°	70.0°	70.5°
WHEEL BASE	1056	1077	1103	1119	1121
CHAIN STAY LENGTH	440	440	440	440	440
BB DROP	45	45	45	45	45
FORK RAKE	42	42	42	42	42
AXLE TO CROWN	480	480	480	480	480
REAR DROPOUT SPACING	135	135	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	Lightweight 27.5" double butted frame, snake stays and replaceable derailleur hanger	<b>GRIP</b>	Kraton grip	<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel
<b>FORK</b>	27.5" suspension fork, 80mm travel	<b>HEAD STEM</b>	Alloy A-head 25.4mm Ext: XS/S=70mm, M/L=90mm, XL=105mm	<b>CHAIN</b>	KMC Z-51
<b>REAR SHOCK</b>	N/A	<b>CRANKSET</b>	Alloy MTB crank 42 x 32 x 22T L=170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	A-head 1-1/8"	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	27.5" alloy 32 hole A/V double wall rims, alloy hubs and stainless spokes
<b>HANDLEBAR</b>	Low riser, W: 640mm, R: 20mm, bore: 31.8mm, sweep: 6°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda 27 x 2.1" wire bead
		<b>F. DERAILLEUR</b>	Shimano TZ-30	<b>SADDLE</b>	Factor MTB sport saddle
		<b>R. DERAILLEUR</b>	Shimano TY-300	<b>SEATPOST/CLAMP</b>	Alloy micro adjust 27.2mm, L:350mm with QR clamp
		<b>SHIFT LEVERS</b>	Shimano EF-41 EZ FIRE 21 speed	<b>EXTRAS</b>	N/A

# ASPIRE 10 WS

27.5" WOMEN'S SPECIFIC MTB - 21 SPEED - V-BRAKE

MTB

ROAD

LIFESTYLE

YOUTH



## KEY FEATURES

- 27.5" Women's specific MTB Alloy Frame
- 27.5" x 2.1" MTB tyres, with double wall Weinmann rims.
- Oversized 31.8mm alloy A-head stem
- Oversized 31.8mm handlebar.
- 21 speed Shimano EZ-Fire shifting.
- 80mm travel front suspension.
- Low maintenance Promax V-Brakes.
- New double wall alloy rims.
- New reinforced resin pedals
- Selle Royal saddle for maximum riding comfort.

## CODES

	XS	S	M
Gloss White / Gloss Purple / Gloss Blue	17225	17226	17227

## GEOMETRY

	XS	S	M
STACK	584	602	616
REACH	373	381	397
STAND OVER HEIGHT	382	412	437
EFFECTIVE TOP TUBE	540	565	585
SEAT TUBE (CENTRE TO TOP)	355	400	440
SEAT ANGLE	74.0°	73.0°	73.0°
HEAD TUBE LENGTH	100	115	130
HEAD ANGLE	69.0°	70.0°	70.0°
WHEEL BASE	1058	1061	1082
CHAIN STAY LENGTH	435	435	435
BB DROP	45	45	45
FORK RAKE	42	42	42
AXLE TO CROWN	495	495	495
REAR DROPOUT SPACING	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	Lightweight female specific 27.5" double butted frame, snake stays and replaceable derailleur hanger	<b>GRIP</b>	Kraton grip	<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel
<b>FORK</b>	27.5" suspension fork, 80mm travel	<b>HEAD STEM</b>	Alloy A-head 25.4mm Ext: XS/S=70mm, M=90mm	<b>CHAIN</b>	KMC Z-51
<b>REAR SHOCK</b>	N/A	<b>CRANKSET</b>	Alloy MTB crank 42 x 32 x 22T L=170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	A-head 1-1/8"	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	27.5" alloy 32 hole A/V double wall rims, alloy hubs and stainless spokes
<b>HANDLEBAR</b>	Low riser, W: 600mm, R: 20mm, bore: 31.8mm, sweep: 6°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Kenda 27 x 2.1" wire bead
		<b>F. DERAILLEUR</b>	Shimano TZ-30	<b>SADDLE</b>	Factor MTB sport saddle
		<b>R. DERAILLEUR</b>	Shimano TY-300	<b>SEATPOST/CLAMP</b>	Alloy micro adjust 27.2mm, L:350mm with QR clamp
		<b>SHIFT LEVERS</b>	Shimano EF-41 EZ FIRE 21 speed	<b>EXTRAS</b>	N/A





MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

Apollo's Carbon Fat Frame tapered head tube, with 12mm thru axle rear.

Apollo's Carbon fat bike fork, with 15mm axle and tapered steer tube.

VeeRubber 26" x 4.5" Snow Shoe Fat tyres.

SRAM X7/X9 2 x 10 speed shifting.

FSA Comet FAT BIKE Crank.

SRAM DB5 hydraulic disc brakes 180mm front and 160mm rear.

CODES	M	L
Matte nude carbon / matte red / matte blue	16285	16286

GEOMETRY	M	L
STACK	593	616
REACH	419	437
STAND OVER HEIGHT		
EFFECTIVE TOP TUBE	600	625
SEAT TUBE (CENTRE TO TOP)	430	483
SEAT ANGLE	73.0°	73.0°
HEAD TUBE LENGTH	110	130
HEAD ANGLE	69.0°	70.0°
WHEEL BASE	1148	1170
CHAIN STAY LENGTH	455	455
BB DROP	60	60
FORK RAKE	51	51
AXLE TO CROWN	483	483
REAR DROPOUT SPACING	190	190

## SPECIFICATIONS

<b>FRAME</b>	Carbon modular monocoque Fat bike frame. Tapered 1-1/8 to 1.5 head tube. 12x142mm dropout, direct mount front derailleur	<b>GRIP</b>	Ultra light hex shaped foam racing grips	<b>CHAIN</b>	KMC X-10
<b>FORK</b>	Carbon modular monocoque Fat bike fork, tapered 1-1/8-1.5 steerer, 15mm THRU AXLE	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext: M=90mm, L=100mm,	<b>BRAKES</b>	SRAM DB5 hydraulic disc brakes with lever adjust, 180mm rotors
<b>REAR SHOCK</b>	N/A	<b>CRANKSET</b>	FSA COMET fat bike specific, 10 speed 36 x 22T L: M/L=175mm	<b>WHEELS</b>	Sunringle Alloy disc specific rims with square holes for reduced weight, 32 hole F/V, precision sealed bearing disc hubs and stainless spokes
<b>HEADSET</b>	A-head semi integrated, for tapered 1.8-1.5 head tube, cartridge bearings with 8mm cone spacer	<b>BOTTOM BRACKET</b>	SRAM GXP 100mm sealed cartridge bottom bracket	<b>TYRES</b>	26 x 4.8" Snowshoe XL Silica Comp 120 TPI folding bead
<b>HANDLEBAR</b>	Factor butted alloy flat bar bore: 31.8mm W: 700mm, sweep: 9°	<b>PEDALS</b>	Low profile high impact resin	<b>SADDLE</b>	Factor MTB sport saddle
		<b>F. DERAILLEUR</b>	SRAM X-5 2 x 10 high direct mount	<b>SEATPOST/CLAMP</b>	Factor 31.6mm alloy, micro adjust with twin bolt head, L:400mm
		<b>R. DERAILLEUR</b>	SRAM X-9 type 2 x 10 speed mid cage	<b>EXTRAS</b>	N/A
		<b>SHIFT LEVERS</b>	SRAM X-7 20 speed		
		<b>CASSETTE</b>	SRAM 10 speed cassette 11 - 36T		

MTB

ROAD

LIFESTYLE

YOUTH



## KEY FEATURES

Apollo's Alloy Fat Frame tapered head tube, with 12mm thru axle rear.

Apollo's formed alloy fat bike fork, with 15mm axle and tapered steer tube.

Veetire 26" x 4.8" Snow Shoe Fat tyres.

SRAM NX 1 x 11 speed shifting with FSA COMET 30T crank.

SRAM Level Hydraulic disc brakes 180mm front and 160mm rear.

## CODES

	S	M	L
Matte black / matte orange / matte blue	17150	17151	17152

## GEOMETRY

	S	M	L
STACK	589	593	616
REACH	394	419	437
STAND OVER HEIGHT	400	427	463
EFFECTIVE TOP TUBE	566	600	625
SEAT TUBE (CENTRE TO TOP)	380	430	483
SEAT ANGLE	73.0°	73.0°	73.0°
HEAD TUBE LENGTH	100	110	130
HEAD ANGLE	69.0°	69.0°	70.0°
WHEEL BASE	1103	1140	1153
CHAIN STAY LENGTH	455	455	455
BB DROP	60	60	60
FORK RAKE	51	51	51
AXLE TO CROWN	483	483	483
REAR DROPOUT SPACING	197	197	197

## SPECIFICATIONS

<b>FRAME</b>	Triple butted 6061 alloy Fat bike frame. Tapered 1-1/8 to 1.5 head tube. 12 x 142mm dropout, direct mount front derailleur	<b>GRIP</b>	Ultra light hex shaped foam racing grips	<b>CASSETTE</b>	SRAM 11 speed cassette 11 - 42T
<b>FORK</b>	Apollo 26" Fatty fork, full alloy with tapered 1-1/8-1.5 steerer	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext: S/M=75mm, L=90mm,	<b>CHAIN</b>	KMC-X11
<b>REAR SHOCK</b>	N/A	<b>CRANKSET</b>	FSA COMET fat bike specific, 11 speed 30T L: M/L=175mm	<b>BRAKES</b>	Sram Level hydraulic disc brakes, 180mm rotors
<b>HEADSET</b>	A-head semi integrated, for tapered 1.8-1.5 head tube, cartridge bearings with 8mm cone spacer	<b>BOTTOM BRACKET</b>	FSA 100mm sealed cartridge bottom bracket	<b>WHEELS</b>	26" Alloy disc specific rims with square holes for reduced weight, 32 hole F/V, anodised disc hubs and stainless spokes
<b>HANDLEBAR</b>	Factor butted alloy flat bar bore: 31.8mm W: 700mm, sweep: 9°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	26 x 4.8" Snowshoe XL 72 TPI
		<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Factor MTB sport saddle
		<b>R. DERAILLEUR</b>	SRAM NX 11 speed	<b>SEATPOST/ CLAMP</b>	Factor 27.2mm alloy, micro adjust with twin bolt head, L:400mm
		<b>SHIFT LEVERS</b>	SRAM NX 11 speed	<b>EXTRAS</b>	N/A



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

- Apollo's Alloy Fat Frame, standard QR Rear Dropout
- Custom Hi-Ten extra strong fork for fat bikes, QR style
- Kenda 26" x 4.5" Fat tyres.
- SRAM X5 2 x 9 speed shifting.
- Promax ST Hydraulic disc brakes front and rear.

CODES	S	M	L
Gloss green / gloss black / gloss blue	17153	17154	17155

GEOMETRY	S	M	L
STACK	589	593	616
REACH	394	419	437
STAND OVER HEIGHT	400	427	463
EFFECTIVE TOP TUBE	566	600	625
SEAT TUBE (CENTRE TO TOP)	380	430	483
SEAT ANGLE	73.0°	73.0°	73.0°
HEAD TUBE LENGTH	100	110	130
HEAD ANGLE	69.0°	69.0°	70.0°
WHEEL BASE	1103	1140	1153
CHAIN STAY LENGTH	455	455	455
BB DROP	60	60	60
FORK RAKE	51	51	51
AXLE TO CROWN	483	483	483
REAR DROPOUT SPACING	190	190	190

## SPECIFICATIONS

<b>FRAME</b>	Triple butted 6061 alloy Fat bike frame. 1-1/8 head tube. Replaceable dropout, direct mount front derailleur	<b>HEAD STEM</b>	Factor 31.8mm 4 bolt stem, Ext: S/ M=75mm, L=90mm,	<b>CHAIN</b>	KMC Z-99
<b>FORK</b>	Apollo 26" Fatty fork, full cr-mo steel 1-1/8 steerer	<b>CRANKSET</b>	Alloy 2-pc MTB crank 38 x 24T S=170mm, M/L=175mm	<b>BRAKES</b>	Promax Solve ST hydraulic disc brakes with reach adjust, 160mm rotors
<b>REAR SHOCK</b>	N/A	<b>BOTTOM BRACKET</b>	100mm sealed cartridge bottom bracket	<b>WHEELS</b>	26" Alloy disc specific rims with square holes for reduced weight, 32 hole F/V, anodised disc hubs and stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	26 x 4.5" Kenda Juggernaut 60 TPI
<b>HANDLEBAR</b>	Factor butted alloy flat bar bore: 31.8mm W: 700mm, sweep: 9°	<b>F. DERAILLEUR</b>	SRAM X-5 high direct mount	<b>SADDLE</b>	Factor MTB sport saddle
<b>GRIP</b>	Ultra light hex shaped foam racing grips	<b>R. DERAILLEUR</b>	SRAM X-5 x 9 speed long cage	<b>SEATPOST/ CLAMP</b>	Factor 27.2mm alloy, micro adjust with twin bolt head, L:400mm
		<b>SHIFT LEVERS</b>	SRAM X-5	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	SRAM cassette 11 - 34T		

MTB

ROAD

LIFESTYLE

YOUTH



## KEY FEATURES

26" Women's specific geometry with low step through style frame.

Front Suspension with lockout for maximum ride ability and comfort.

Strong 26" Wheels with double wall rims and easy rolling semi slick tyres.

Promax mechanical disc brakes with alloy hubs.

Alloy A-head Stem, with threadless steer tube.

Soft and comfortable women's specific saddle.

21 Speed, Shimano EZ-fire shifting with cassette.

## CODES

	XS	S	M
Gloss White / Gloss Black / Gloss Purple	16387	16388	16389

## GEOMETRY

	XS	S	M
STACK	533	551	570
REACH	387	396	411
STAND OVER HEIGHT	325	334	344
EFFECTIVE TOP TUBE	540	565	585
SEAT TUBE (CENTRE TO TOP)	350	400	450
SEAT ANGLE	74.0°	73.0°	73.0°
HEAD TUBE LENGTH	110	130	150
HEAD ANGLE	70.0°	70.0°	70.0°
WHEEL BASE	1035	1051	1072
CHAIN STAY LENGTH	430	430	430
BB DROP	35	35	35
FORK RAKE	38	38	38
AXLE TO CROWN	435	435	435
REAR DROPOUT SPACING	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	Butted 6061 disc aluminium low step through women's specific frame with snake stays and replaceable derailleur hanger	<b>GRIP</b>	Kraton comfort grip	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	Suspension fork with lockout, 60mm travel with preload, alloy crown and brace, Hi-Ten lowers, coil spring	<b>HEAD STEM</b>	Alloy A-head 25.4mm Ext: XS/S=70mm, M=90mm	<b>BRAKES</b>	Promax DSK 300 mechanical disc brakes with 160mm rotors
<b>REAR SHOCK</b>	N/A	<b>CRANKSET</b>	Alloy MTB crank 42 x 34 x 24T L=170mm	<b>WHEELS</b>	Double wall 32 hole A/V rims, alloy disc hubs with QR, cassette rear, stainless spokes
<b>HEADSET</b>	A-head 1-1/8"	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>TYRES</b>	26 x 2.0" wire bead
<b>HANDLEBAR</b>	Low riser, W: 580mm, R: 20mm, bore: 25.4mm, sweep: 6°	<b>PEDALS</b>	Non-slip with inlaid TPE tread	<b>SADDLE</b>	Factor Comfortech women's specific
		<b>F. DERAILLEUR</b>	Shimano TX-50 for 31.8	<b>SEATPOST/CLAMP</b>	Alloy micro adjust 27.2mm, L:300mm with QR clamp
		<b>R. DERAILLEUR</b>	Shimano TX-55	<b>EXTRAS</b>	N/A
		<b>SHIFT LEVERS</b>	Shimano EF-41 EZ FIRE 21 speed		
		<b>CASSETTE</b>	Shimano HG-20 7 speed cassette 12-28T		

# ALPINA WS



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

26" Women's specific geometry with low step through style frame.

Front Suspension for maximum riding comfort.

Strong 26" Wheels with double wall rims and easy rolling semi slick tyres.

Alloy hubs

Alloy A-head Stem, with threadless steer tube.

Soft and comfortable women's specific saddle.

21 Speed, Shimano EZ-fire shifting.

CODES	XS	S	M
Gloss Light Pink / Gloss White	16390	16391	16392
Gloss Blue / Gloss Purple / Gloss White		16394	16395

GEOMETRY	XS	S	M
STACK	533	551	570
REACH	387	396	411
STAND OVER HEIGHT	325	334	344
EFFECTIVE TOP TUBE	540	565	585
SEAT TUBE (CENTRE TO TOP)	350	400	450
SEAT ANGLE	74.0°	73.0°	73.0°
HEAD TUBE LENGTH	110	130	150
HEAD ANGLE	70.0°	70.0°	70.0°
WHEEL BASE	1035	1051	1072
CHAIN STAY LENGTH	430	430	430
BB DROP	35	35	35
FORK RAKE	38	38	38
AXLE TO CROWN	435	435	435
REAR DROPOUT SPACING	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	Butted 6061 aluminium low step through women's specific frame with snake stays and replaceable derailleur hanger	<b>GRIP</b>	Kraton comfort grip	<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel
<b>FORK</b>	Suspension fork with 50mm travel, alloy crown and brace, Hi-Ten lowers, coil spring	<b>HEAD STEM</b>	Alloy A-head 25.4mm Ext: XS/S=70mm, M=90mm	<b>CHAIN</b>	KMC Z-51
<b>REAR SHOCK</b>	N/A	<b>CRANKSET</b>	Alloy MTB crank 42 x 34 x 24T L=170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	A-head 1-1/8"	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Alloy double wall 32 hole A/V rims, alloy QR hubs, Stainless spokes
<b>HANDLEBAR</b>	Low riser, W: 580mm, R: 20mm, bore: 25.4mm, sweep: 6°	<b>PEDALS</b>	Non-slip with inlaid TPE tread	<b>TYRES</b>	26 x 2.0" wire bead
		<b>F. DERAILLEUR</b>	Shimano TX-50 for 31.8	<b>SADDLE</b>	Factor Comfortech women's specific
		<b>R. DERAILLEUR</b>	Shimano TX-55	<b>SEATPOST/CLAMP</b>	Alloy micro adjust 27.2mm, L:300mm with QR clamp
		<b>SHIFT LEVERS</b>	Shimano EF-41 EZ FIRE 21 speed	<b>EXTRAS</b>	Kickstand

MTB

ROAD

LIFESTYLE

YOUTH



## KEY FEATURES

26" Women's specific geometry with low step through style frame.

Front Suspension for maximum riding comfort.

Strong 26" Wheels, with easy rolling semi slick tyres.

Quilled stem for maximum adjustability.

Soft and comfortable women's specific saddle.

21 Speed, Shimano EZ-fire shifting.

## CODES

	XS	S	M
Gloss White / Gloss Chrome / Gloss Lime	16396	16397	16398
Gloss Pink / Gloss White / Gloss Blue	16399	16400	16401

## GEOMETRY

	XS	S	M
STACK	533	551	570
REACH	387	396	411
STAND OVER HEIGHT	325	334	344
EFFECTIVE TOP TUBE	540	565	585
SEAT TUBE (CENTRE TO TOP)	350	400	450
SEAT ANGLE	74.0°	73.0°	73.0°
HEAD TUBE LENGTH	110	130	150
HEAD ANGLE	70.0°	70.0°	70.0°
WHEEL BASE	1035	1051	1072
CHAIN STAY LENGTH	430	430	430
BB DROP	35	35	35
FORK RAKE	38	38	38
AXLE TO CROWN	435	435	435
REAR DROPOUT SPACING	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	Butted 6061 aluminium low step through women's specific frame with snake stays and replaceable derailleur hanger	<b>GRIP</b>	Kraton comfort grip	<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel
<b>FORK</b>	26", 50mm travel coil spring, pressed crown with Hi-Ten lowers	<b>HEAD STEM</b>	Alloy quill stem 1-1/8", L: 80mm, bore: 25.4mm	<b>CHAIN</b>	KMC Z-51
<b>REAR SHOCK</b>	N/A	<b>CRANKSET</b>	Alloy MTB crank 42 x 32 x 22T L: 170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	Threaded semi-sealed 1-1/8"	<b>BOTTOM BRACKET</b>	Nutted type	<b>WHEELS</b>	Alloy 36 hole A/V rims, quick release front wheel. Stainless spokes
<b>HANDLEBAR</b>	Low riser, W: 580mm, R: 20mm, bore: 25.4mm, sweep: 6°	<b>PEDALS</b>	Non-slip resin	<b>TYRES</b>	26 x 2.0" wire bead
		<b>F. DERAILLEUR</b>	Shimano TZ-30 for 31.8	<b>SADDLE</b>	Factor Comfortech women's specific
		<b>R. DERAILLEUR</b>	Shimano TX-35	<b>SEATPOST/CLAMP</b>	27.2mm L:300mm with QR clamp
		<b>SHIFT LEVERS</b>	Shimano EF-41 EZ FIRE 21 speed	<b>EXTRAS</b>	Kickstand



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

Apollo super lightweight advanced technology racing specific road frame and fork, with road racing geometry.

BB86 BB Interface.

Shimano Dura-Ace shifting.

Shimano Dura-Ace brake calipers.

ITM Triango carbon wrap handlebar with ITM Alutech stem.

Prologo ZERO 2 road racing saddle.

DT Swiss R24 Spline Clincher road wheels.

## CODES

	XS	S	M	L	XL
Matte Nude Carbon / Gloss White / Gloss Silver	16000	16001	16002	16003	16004

## GEOMETRY

	XS	S	M	L	XL
STACK	522	541	557	578	599
REACH	378	379	384	393	407
EFFECTIVE TOP TUBE	523	534	549	570	590
SEAT TUBE (CENTRE TO TOP)	500	530	550	580	610
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	180	200
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	972	979	985	996	1010
CHAIN STAY LENGTH	406	406	406	406	406
BB DROP	70	70	70	70	70
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	368	368	368	368	368
REAR DROPOUT SPACING	130	130	130	130	130

## SPECIFICATIONS

<b>FRAME</b>	Modular monoque carbon frame incorporating multi weave carbon lay up with EPS technology. Box technology down tube, BB30 bottom bracket, slim seatstays, tapered head tube 1-1/8 to 1-1/4, internal cable routing Di2 and mechanical compatible	<b>GRIP</b>	PU performance tape	<b>CASSETTE</b>	Shimano 11 speed cassette 11-25T
<b>FORK</b>	Full monoque carbon fork with carbon blades, steerer, crown and dropouts. Tapered 1-1/4 to 1-1/8 steerer.	<b>HEADSTEM</b>	ITM Alutech 7075 3D forged 31.8mm alloy, L: XS=100mm, S/M=110mm, L=120mm, XL=130mm	<b>CHAIN</b>	KMC X11-L 11 speed
<b>HEADSET</b>	A-head integrated 1-1/4 to 1-1/8 sealed angular cartridge bearings with 5mm cone spacer	<b>CRANKSET</b>	FSA Energy BB30 cold forged crank, 52/36T alloy Rings L: XS/S=170mm, M=172.5mm, L/XL=175mm	<b>BRAKES</b>	Shimano BR-9000 Dura Ace
<b>HANDLEBAR</b>	ITM Triango 31.8mm carbon wrapped bar W: 40cm	<b>BOTTOM BRACKET</b>	SRAM BB30	<b>WHEELS</b>	DT Swiss R24 Spline clincher wheelset. 20 hole front; 24 hole rear laced with DT Swiss hubs, DT aero spokes, alloy nipples
		<b>PEDALS</b>	Nil	<b>TYRES</b>	Hutchinson Fusion 3 700 x 25 with Kevlar pro tech triple compound, 127tpi
		<b>F. DERAILLEUR</b>	Shimano Dura Ace mechanical braze on	<b>SADDLE</b>	Prologo Zero 2 custom
		<b>R. DERAILLEUR</b>	Shimano Dura Ace mechanical	<b>SEATPOST / CLAMP</b>	Factor Carbon 27.2mm, 300mm post, twin bolt, forged head, alloy seat clamp
		<b>SHIFT LEVERS</b>	Shimano Dura Ace mechanical 22 speed STI shifters		

## ROAD SERIES

# ELITE



## BICYCLING

Australia

Reviewed by Luke Meers | 10 March 2016

When testing a racing bike, the ideal test is to race. That is just the treatment this Apollo Elite got during the 2015 Tour of Bright in the Victorian Alps. I received the Apollo about three days prior to when I was due to depart on the drive down to Bright. Usually test bikes take a few rides to bed them in and adjust bits and pieces, get the fit just right. On the Elite, however, I felt at home immediately and decided to do what is generally recommended against: ride a new, untested bike during a race. An ideal test ground for the Apollo to prove its worth.

First impressions often go a long way to determining one's thoughts about a test bike. Visually and on the road, the first ride provides the most ideas, sensations and observations about how a bike differs from others and what type of ride it delivers. The Apollo impressed immediately, the very generously proportioned downtube draws the attention, down towards the BB86 pressfit bottom bracket, surrounded by a mass of carbon. The tube profiles are overly square in shape. This is in contrast to many of the aerodynamically focussed designs currently on the market and highlights the fact Apollo have focussed on stiffness and dynamics above creating a slippery frame. The oversized downtube and bottom bracket area contrast the spidery thin seat stays. A raw carbon finish and minimalist decals provide a reasonably stealthy appearance. Whether it was these positive initial visual impressions that made the first ride feel good or the ride itself, I'll never know. Either way, after the first short ride of 15km or so, the Elite gave me the confidence that it was a bike built to be raced.

A couple of days later it was packed up and heading down to Bright for three days of tough racing. The Tour of Bright saw the bike perform three quite different stages. In the first stage the road bike did its best impression of a time trial machine. The handlebars were dumped and some aero bars attached, deep dish Zipp wheels fitted and bottle cages removed. Admittedly, the geometry of the Elite is not well suited to time trial adaptation. The headtube is relatively tall (160mm in the medium size).

As such, the time trial position was a little higher than ideal. The square and wide down tube cannot be highly aerodynamic either. Regardless, the handling was predictable, even when down in the aero tuck.

Day two presented a mixed 90km road stage, requiring plenty of navigating within a peloton of 100 riders and finishing up with a 6km climb up Tawonga gap. The handling was predictable within tight bunch riding situations and the fairly standard tube angles and wheelbase provided a confident ride whilst descending. Additionally, much praise needs to be given to the Dura Ace brakes. The latest offering from Shimano are certainly their best yet, with ample power and the right level of mechanical advantage to provide meaningful control.

The final, brutal stage, just 60 km, but the last 30 of which are ascending Mt Hotham; a climb taking the best part of 90 minutes. This undulating ascent is a genuine test of the climbing prowess of a bike. Whilst this rider's legs weren't quite at the level required to hang with the best on the climb, the Apollo Elite certainly did its part. The frame feels very light and lively. A flick of the finger on any of the main tubes of the bike delivers a noise identifying very thin wall sections. Apollo use polyurethane inserts during manufacture of the frame to control the internal surface. Achieving consistent wall thickness gives greater confidence of the frame strength allowing the manufacturer to push the boundaries and reduce weight. Despite the wafer thin tubes, the Elite is superbly stiff out of the saddle, the generous dimensions around the bottom bracket providing the rigid base through which any power delivered by my legs was more than adequately transferred. Most of the Hotham climb was spent in the small Dura Ace chainring and either the 25 or 28 tooth cogs on the rear cassette. I had cited the tall head tube earlier. For the majority of riding, the 160mm length borders on too tall, but during the long Hotham ascent, the bit of extra stack was appreciated.





During all three stages the shifting of the Dura Ace gears was flawless as you would hope for in the top offering from any manufacturer. The level of crisp and clear mechanical shifting achieved by Shimano in the 11 speed range provides a legitimate alternative to the more expensive electronic option. Apart from the need to replace cables once or twice a year, the mechanical Dura Ace would not leave you wishing for Di2.

At this stage of a review, I usually have some form of criticism to make. Usually a poor wheel choice or badly specified componentry. However, I could find little on the Elite which was not done well. The quality frame was well adorned in Dura Ace gear set, ITM stem and bars, Prologo Zero 2 saddle and Factor carbon seat mast. The DT Swiss R20 Dicut clincher wheelset was also a good match. Perhaps it could be argued that for a bike as well specified as this one, a carbon wheel set would be appropriate. The DT Swiss wheels, however, performed solidly, feeling stiff and fast. The all round performance and training suitability of a good set of alloy clinchers is hard to argue against. At 1550g for the set, the weight of the R20s is respectable too.

The Apollo Elite first impressions were good. Good enough to give the confidence to race on this bike immediately. During racing it then delivered convincingly on what was first promised. Leaving no doubt that any lack of results was due to the form of the rider, not the function of the bike. It is a good all round race machine, stiff, fast and lively. Spindly seat stays give enough compliance to keep you comfortable over longer or rougher terrain. The oversized and somewhat boxy tube design is admittedly not to everyone's taste, but it appealed to me. The Elite perhaps does not offer the "wow factor" or any attention grabbing design features that often adorn new bikes these days, but I appreciated the Aussie-style understated nature of the bike. This is a quality build, well spec'd, from groupset to wheels and at a retail of around \$5,500, it provides good value for money. Especially for those wanting to support an Australian company. It is a sad thing writing this review, because it means I now have to give the bike back.

## Summing Up

**Quality:** the quality carbon frame is finished nicely. With a good set of components throughout.

**Performance:** This is a bike built to race, the frame is light and lively. The BB area is bulky and very stiff. All parts of the machine gel together well and perform as a seamless unit.

**Value:** \$5.5k for a quality frame, Full Dura Ace, DT Swiss R20 wheels and carbon components. The Elite offers good value for money.

**Overall:** There was very little to fault with this bike. A great frame, and Shimano's trusty Dura Ace combine to create a bike which raced well on the flats, was a lively climber and confidence inspiring on the descents. Apollo have created a very good all round race machine.



## KEY FEATURES

Apollo lightweight racing specific road frame, with road racing geometry.

BB86 BB Interface.

Shimano Dura-Ace shifting with Dura Ace Crank.

Shimano Dura-Ace brake calipers.

ITM ALUTECH stem and R TRIANGO handlebar.

Prologo road racing saddle.

DT Swiss R20 DIECUT road wheels.

## CODES

	XS	S	M	L	XL
Matte Nude Carbon / Gloss White / Gloss Silver	16010	16011	16012	16013	16014

## GEOMETRY

	XS	S	M	L	XL
STACK	522	541	557	578	599
REACH	378	379	384	393	407
EFFECTIVE TOP TUBE	523	534	549	570	590
SEAT TUBE (CENTRE TO TOP)	500	530	550	580	610
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	180	200
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	972	979	985	996	1010
CHAIN STAY LENGTH	406	406	406	406	406
BB DROP	70	70	70	70	70
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	368	368	368	368	368
REAR DROPOUT SPACING	130	130	130	130	130

## SPECIFICATIONS

<b>FRAME</b>	Modular monocoque carbon frame incorporating dual weave carbon lay up with EPS technology. Box technology down tube, BB86 bottom bracket, slim seatstays, tapered head tube 1-1/8 to 1-1/4, internal cable routing Di2 and mechanical compatible
<b>FORK</b>	Full monocoque carbon fork with carbon blades, steerer, crown and dropouts. Tapered 1-1/4 to 1-1/8 steerer.
<b>HEADSET</b>	A-head integrated 1-1/4 to 1-1/8 sealed angular cartridge bearings with 15mm cone spacer
<b>HANDLEBAR</b>	ITM Triango 31.8mm carbon wrapped bar W: XS=40cm, S/M=42cm, L/XL= 44cm
<b>GRIP</b>	PU performance tape

<b>HEADSTEM</b>	ITM Alutech 7075 3D forged 31.8mm alloy, L: XS=100mm, S/M=110mm, L=120mm, XL=130mm
<b>CRANKSET</b>	Shimano Dura Ace, 4 arm crank, 53 x 39T L: XS/S=170mm, M=172.5mm, L/XL=175mm
<b>BOTTOM BRACKET</b>	Press fit BB86
<b>PEDALS</b>	Nil
<b>F. DERAILLEUR</b>	Shimano Dura Ace mechanical braze on
<b>R. DERAILLEUR</b>	Shimano Dura Ace mechanical
<b>SHIFT LEVERS</b>	Shimano Dura Ace mechanical 22 speed STI shifters
<b>CASSETTE</b>	Shimano 6800 11 speed 11-25T

<b>CHAIN</b>	KMC X11-L11 speed
<b>BRAKES</b>	Shimano BR-9000 Dura Ace
<b>WHEELS</b>	DT Swiss R20 Dicut® clincher wheelset. Welded alloy rim, 16 hole front; 20 hole rear laced with DT Swiss hubs, DT aero nail head spokes, alloy nipples, RWS skewers, 1550g
<b>TYRES</b>	Hutchinson Fusion 3 700 x 25 with Kevlar pro tech triple compound, 127tpi
<b>SADDLE</b>	Prologo Zero 2 custom
<b>SEATPOST / CLAMP</b>	Factor Carbon 27.2mm, 300mm post, twin bolt, forged head, alloy seat clamp



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

Apollo custom lightweight Carbon frame and fork, with comfort road geometry.

BB86 / BB386 BB Interface for ultra rigidity.

Shimano 22 speed Dura Ace shifting

FSA BB386 36/52T 2-pc crank

In-line cable adjuster for shifter cables for easy shifter adjustments

DT Swiss R24 SPLINE road wheels.

ARC cold forged dual pivot brake calipers with cartridge pads

## CODES

	XS	S	M	L	XL
Matte Nude Carbon / Gloss Black	16015	16016	16017	16018	16019

## GEOMETRY

	XS	S	M	L	XL
STACK	530	549	565	591	636
REACH	368	373	383	389	396
STAND OVER HEIGHT	396	415	430	458	495
EFFECTIVE TOP TUBE	515	530	550	570	590
SEAT TUBE (CENTRE TO TOP)	460	480	500	530	560
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	185	230
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	968	978	990	999	1014
CHAIN STAY LENGTH	410	410	410	410	410
BB DROP	72	72	72	72	72
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	374	374	374	374	374
REAR DROPOUT SPACING	130	130	130	130	130

## SPECIFICATIONS

<b>FRAME</b>	Hi-modulus Mitsubishi carbon modular monocoque frame. Box technology down tube with BB386 press fit system, slim seatstays, Tapered head tube 1-1/8 to 1-1/2,	<b>HEADSTEM</b>	Factor 1-1/8" 3D forged alloy 4 bolt stem. XS=90mm, S=100mm, M=110mm, L/XL=120mm	<b>CHAIN</b>	KMC 11 speed
<b>FORK</b>	Full carbon straight blade fork with tapered 1-1/8 to 1-1/2 carbon steerer, fully integrated	<b>CRANKSET</b>	FSA Energy BB386 cold forged crank, 52/36T alloy Rings L: XS/S=170mm, M=172.5mm, L/XL=175mm	<b>BRAKES</b>	ARC Cold forged dual pivot brake with Swiss stop cartridge pads
<b>HEADSET</b>	A-head integrated 1-1/2 to 1-1/8 sealed angular cartridge bearings with 15mm cone spacer	<b>BOTTOM BRACKET</b>	Press fit BB386	<b>WHEELS</b>	DT Swiss R24 Spline clincher wheelset. 20 hole front; 24 hole rear laced with DT Swiss hubs, DT aero spokes, alloy nipples
<b>HANDLEBAR</b>	ITM Alcor 80 butted alloy 31.8mm road bar W: XS=40cm, S/M=42cm, L/XL=44cm	<b>PEDALS</b>	Nil	<b>TYRES</b>	Hutchinson Equinox 2 700 x 25c 66tpi folding bead
<b>GRIP</b>	PU performance tape	<b>F. DERAILLEUR</b>	Shimano 6800 mechanical braze on	<b>SADDLE</b>	Factor road saddle with cro-mo rail
		<b>R. DERAILLEUR</b>	Shimano Dura Ace mechanical	<b>SEATPOST / CLAMP</b>	Factor Carbon 27.2mm 350mm long post, twin bolt, forged head, alloy seat clamp
		<b>SHIFT LEVERS</b>	Shimano Dura Ace mechanical 22 speed STI shifters		
		<b>CASSETTE</b>	Shimano 11 speed cassette 12-25T		



### KEY FEATURES

Apollo custom lightweight Carbon frame and fork, with comfort road geometry.

BB86 / BB386 BB Interface.

Shimano 22 speed Ultegra Di2 electric shifting

FSA Energy BB386 36/52T 2-pc Crank

Addition of an in-line cable adjuster for shifter cables.

Upgraded DT SWISS 444D rims.

ARC Cold Forged Dual Pivot Brake calipers with Cartridge pads

### CODES

	XS	S	M	L	XL
Matte Nude Carbon / Gloss Lime	16020	16021	16022	16023	16024

### GEOMETRY

	XS	S	M	L	XL
STACK	530	549	565	591	636
REACH	368	373	383	389	396
STAND OVER HEIGHT	396	415	430	458	495
EFFECTIVE TOP TUBE	515	530	550	570	590
SEAT TUBE (CENTRE TO TOP)	460	480	500	530	560
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	185	230
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	968	978	990	999	1014
CHAIN STAY LENGTH	410	410	410	410	410
BB DROP	72	72	72	72	72
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	374	374	374	374	374
REAR DROPOUT SPACING	130	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Hi-modulus Mitsubishi carbon modular monocoque frame. Box technology down tube with BB386 press fit system, slim seatstays, Tapered head tube 1-1/8 to 1-1/2,	<b>HEADSTEM</b>	ITM Alcor 80 forged 31.8mm alloy, L: XS=90mm, S=100mm, M=110mm, L/XL=120mm	<b>CHAIN</b>	KMC 11 speed
<b>FORK</b>	Full carbon straight blade fork with tapered 1-1/8 to 1-1/2 carbon steerer, fully integrated	<b>CRANKSET</b>	FSA Energy BB386 cold forged crank, 52/36T alloy Rings L: XS/S=170mm, M=172.5mm, L/XL=175mm	<b>BRAKES</b>	ARC Cold forged dual pivot brake with Swiss stop cartridge pads
<b>HEADSET</b>	A-head integrated 1-1/2 to 1-1/8 sealed angular cartridge bearings with 15mm cone spacer	<b>BOTTOM BRACKET</b>	Press fit BB386	<b>WHEELS</b>	DT Swiss R-460 box section rim, 28 hole paired with 11 speed sealed bearing alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	ITM Alcor 80 butted alloy 31.8mm road bar W: XS=40cm, S/M=42cm, L/XL=44cm	<b>PEDALS</b>	Nil	<b>TYRES</b>	Hutchinson Equinox 2 700 x 25c 66tpi folding bead
<b>GRIP</b>	PU performance tape	<b>F. DERAILLEUR</b>	Shimano Ultegra 6870-F Di2	<b>SADDLE</b>	Factor road saddle with cro-mo rail
		<b>R. DERAILLEUR</b>	Shimano Ultegra 6870 Di2 11 speed	<b>SEATPOST / CLAMP</b>	Factor Carbon 27.2mm 350mm long post, twin bolt, forged head, alloy seat clamp
		<b>SHIFT LEVERS</b>	Shimano Ultegra 6870 Di2 22 speed STI shifters		
		<b>CASSETTE</b>	Shimano 5800 11 speed cassette 11-25T		



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

Apollo custom lightweight Carbon frame and fork, with comfort road geometry.

BB86 / BB386 BB Interface.

Shimano 22 speed Ultegra shifting

FSA Energy BB386 36/52T 2-pc Crank

Addition of an in-line cable adjuster for shifter cables.

Upgraded DT SWISS 444D rims.

ARC Cold Forged Dual Pivot Brake calipers with Cartridge pads

## CODES

	XS	S	M	L	XL
Matte Nude Carbon / Gloss Red	16025	16026	16027	16028	16029

## GEOMETRY

	XS	S	M	L	XL
STACK	530	549	565	591	636
REACH	368	373	383	389	396
STAND OVER HEIGHT	396	415	430	458	495
EFFECTIVE TOP TUBE	515	530	550	570	590
SEAT TUBE (CENTRE TO TOP)	460	480	500	530	560
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	185	230
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	968	978	990	999	1014
CHAIN STAY LENGTH	410	410	410	410	410
BB DROP	72	72	72	72	72
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	374	374	374	374	374
REAR DROPOUT SPACING	130	130	130	130	130

## SPECIFICATIONS

<b>FRAME</b>	Hi-modulus Mitsubishi carbon modular monocoque frame. Box technology down tube with BB386 press fit system, slim seatstays, Tapered head tube 1-1/8 to 1-1/2,	<b>HEADSTEM</b>	Factor 1-1/8" 3D forged alloy 4 bolt stem. XS=90mm, S=100mm, M=110mm, L/XL=120mm	<b>CHAIN</b>	KMC 11 speed
<b>FORK</b>	Full carbon straight blade fork with tapered 1-1/8 to 1-1/2 carbon steerer, fully integrated	<b>CRANKSET</b>	FSA Energy BB386 cold forged crank, 52/36T alloy Rings L: XS/S=170mm, M=172.5mm, L/XL=175mm	<b>BRAKES</b>	ARC Cold forged dual pivot brake with Swiss stop cartridge pads
<b>HEADSET</b>	A-head integrated 1-1/2 to 1-1/8 sealed angular cartridge bearings with 15mm cone spacer	<b>BOTTOM BRACKET</b>	Press fit BB386	<b>WHEELS</b>	DT Swiss R-460 box section rim, 28 hole paired with 11 speed sealed bearing alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Factor butted alloy Anatomic shallow drop 31.8mm alloy W: XS=40cm, S/M=42cm, L/XL=44cm	<b>PEDALS</b>	Nil	<b>TYRES</b>	Hutchinson Equinox 2 700 x 25c 66tpi folding bead
<b>GRIP</b>	PU performance tape	<b>F. DERAILLEUR</b>	Shimano Ultegra 6800 braze on	<b>SADDLE</b>	Factor road
		<b>R. DERAILLEUR</b>	Shimano Ultegra 6800 11 speed	<b>SEATPOST / CLAMP</b>	Factor 27.2mm 350mm long post, twin bolt, forged head, alloy seat clamp
		<b>SHIFT LEVERS</b>	Shimano Ultegra 6800 22 speed STI shifters		
		<b>CASSETTE</b>	Shimano 11 speed cassette 12-25T		



## KEY FEATURES

New upgraded Apollo custom lightweight Carbon frame and fork, with comfort road geometry.

BB86 / BB386 BB Interface.

Sun Ringle Venus Rims with Alloy hubs.

Shimano 22 speed 105 shifting

FSA Gossamer BB386 36/52T 2-pc Crank

Addition of an in-line cable adjuster for shifter cables.

## CODES

	XS	S	M	L	XL
Matte Nude Carbon / Gloss White	16030	16031	16032	16033	16034

## GEOMETRY

	XS	S	M	L	XL
STACK	530	549	565	591	636
REACH	368	373	383	389	396
STAND OVER HEIGHT	396	415	430	458	495
EFFECTIVE TOP TUBE	515	530	550	570	590
SEAT TUBE (CENTRE TO TOP)	460	480	500	530	560
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	185	230
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	968	978	990	999	1014
CHAIN STAY LENGTH	410	410	410	410	410
BB DROP	72	72	72	72	72
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	374	374	374	374	374
REAR DROPOUT SPACING	130	130	130	130	130

## SPECIFICATIONS

<b>FRAME</b>	Hi-modulus Mitsubishi carbon modular monocoque frame. Box technology down tube with BB386 press fit system, slim seatstays, Tapered head tube 1-1/8 to 1-1/2,	<b>GRIP</b>	PU performance tape	<b>CASSETTE</b>	Shimano 11 speed cassette 11-28T
<b>FORK</b>	Full carbon straight blade fork with tapered 1-1/8 to 1-1/2 carbon steerer, fully integrated	<b>HEADSTEM</b>	Factor 1-1/8" 3D forged alloy 4 bolt stem. XS=90mm, S=100mm, M=110mm, L/XL=120mm	<b>CHAIN</b>	KMC 11 speed
<b>HEADSET</b>	A-head integrated 1-1/2 to 1-1/8 sealed angular cartridge bearings with 15mm cone spacer	<b>CRANKSET</b>	FSA Gossamer Pro cold forged crank, 52/36T alloy Rings L: XS/S=170mm, M=172.5mm, L/XL=175mm	<b>BRAKES</b>	Dual pivot brake with cartridge pads
<b>HANDLEBAR</b>	Factor butted alloy Anatomic shallow drop 31.8mm alloy W: XS=40cm, S/M=42cm, L/XL=44cm	<b>BOTTOM BRACKET</b>	Press fit BB386	<b>WHEELS</b>	Sun Ringle Venus welded rim, 28 hole, 25mm deep rims paired with 11 speed alloy hubs and stainless spokes.
		<b>PEDALS</b>	Nil	<b>TYRES</b>	Hutchinson Nitro 2 700c x 25c 33tpi
		<b>F. DERAILLEUR</b>	Shimano 105 braze on	<b>SADDLE</b>	Factor road
		<b>R. DERAILLEUR</b>	Shimano 105 11 speed	<b>SEATPOST / CLAMP</b>	Factor 27.2mm 350mm long post, twin bolt, forged head, alloy seat clamp
		<b>SHIFT LEVERS</b>	Shimano 105 STI 22 speed shifters		



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

700c light weight butted alloy frame with road specific geometry

Upgraded oversized carbon fork with alloy steer tube.

Shimano 22 speed 105 shifting

Shimano Compact 34/50T 2-pc Crank

Alloy Hubs with Sun Ringle Venus rims.

Addition of an in-line cable adjuster for shifter cables.

## CODES

	XS	S	M	L	XL
Matte Black / Gloss Black	16035	16036	16037	16038	16039

## GEOMETRY

	XS	S	M	L	XL
STACK	523	542	558	584	629
REACH	370	374	385	391	398
EFFECTIVE TOP TUBE	515	530	550	570	590
SEAT TUBE (CENTRE TO TOP)	500	520	550	580	610
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	185	230
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	975	984	994	1004	1013
CHAIN STAY LENGTH	415	415	415	415	415
BB DROP	72	72	72	72	72
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	367	367	367	367	367
REAR DROPOUT SPACING	130	130	130	130	130

## SPECIFICATIONS

<b>FRAME</b>	Superlite triple butted 6061 alloy, smooth welded, integrated head tube and replaceable derailleur hanger	<b>HEADSTEM</b>	Factor 1-1/8" 3D forged alloy 4 bolt stem. XS=90mm, S=100mm, M/L=110mm, XL=120mm	<b>CASSETTE</b>	Shimano 11 speed cassette 11-28T
<b>FORK</b>	Carbon oversized 1-1/8 straight blades with alloy steerer, fully integrated	<b>CRANKSET</b>	Shimano FC-R500 compact 50 x 34T 2 piece crank, XS=170mm, S/M=172.5mm, L/XL=175mm	<b>CHAIN</b>	KMC 11 speed
<b>HEADSET</b>	A-head integrated 1-1/8 cartridge bearings with 15mm cone spacer	<b>BOTTOM BRACKET</b>	Shimano integrated sealed	<b>BRAKES</b>	Dual pivot brake with cartridge pads
<b>HANDLEBAR</b>	Factor butted alloy Anatomic shallow drop 31.8mm alloy W: XS/S/M=42cm, L/XL=44cm	<b>PEDALS</b>	Nil	<b>WHEELS</b>	Sun Ringle Venus welded rim, 28 hole, 25mm deep rims paired with 11 speed alloy hubs and stainless spokes.
<b>GRIP</b>	PU performance tape	<b>F. DERAILLEUR</b>	Shimano 105 band clamp	<b>TYRES</b>	Hutchinson Nitro 2 700c x 25c 33tpi
		<b>R. DERAILLEUR</b>	Shimano 105 11 speed	<b>SADDLE</b>	Factor road
		<b>SHIFT LEVERS</b>	Shimano 105 STI 22 speed shifters	<b>SEATPOST / CLAMP</b>	Factor alloy 27.2mm post, twin bolt with alloy seat clamp



### KEY FEATURES

700c light weight butted alloy frame with women specific geometry

Upgraded oversized carbon fork with alloy steer tube.

Shimano 22 speed 105 shifting

Shimano Compact 34/50T 2-pc Crank

Alloy Hubs with Sun Ringle Venus rims.

Addition of an in-line cable adjuster for shifter cables.

### CODES

	XS	S	M
Gloss White / Gloss Green	16045	16046	16047

### GEOMETRY

	XS	S	M
STACK	504	524	545
REACH	375	374	376
EFFECTIVE TOP TUBE	510	519	532
SEAT TUBE (CENTRE TO TOP)	460	480	520
SEAT ANGLE	75.0°	74.5°	74.0°
HEAD TUBE LENGTH	110	130	150
HEAD ANGLE	71.0°	71.5°	72.0°
WHEEL BASE	981	982	995
CHAIN STAY LENGTH	415	415	415
BB DROP	70	70	70
FORK RAKE	45	45	45
AXLE TO CROWN	367	367	367
REAR DROPOUT SPACING	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Women's specific Superlite triple butted 6061 alloy, smooth welded, integrated head tube and replaceable derailleur hanger	<b>HEADSTEM</b>	Factor 1-1/8" 3D forged alloy 4 bolt stem. XS/S=90mm, M=100mm	<b>CHAIN</b>	KMC 11 speed
<b>FORK</b>	Carbon oversized 1-1/8" straight blades with alloy steerer, fully integrated	<b>CRANKSET</b>	Shimano FC-R565 compact 50 x 34T 2 piece crank, XS/S/M=170mm	<b>BRAKES</b>	Dual pivot brake with cartridge pads
<b>HEADSET</b>	A-head integrated 1-1/8" cartridge bearings with 15mm cone spacer	<b>BOTTOM BRACKET</b>	Shimano integrated sealed	<b>WHEELS</b>	Sun Ringle Venus welded rim, 28 hole, 25mm deep rims paired with 11 speed alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Factor butted alloy female specific alloy road bar with short reach and shallow drop 31.8. XS=38cm, S/M=40cm	<b>PEDALS</b>	Resin with toe straps	<b>TYRES</b>	Hutchinson Nitro 2 700c x 25c 33tpi
<b>GRIP</b>	PU performance tape	<b>F. DERAILLEUR</b>	Shimano 105 band clamp	<b>SADDLE</b>	Factor female specific road with cutout
		<b>R. DERAILLEUR</b>	Shimano 105 11 speed	<b>SEATPOST / CLAMP</b>	Factor 27.2mm alloy post, twin bolt with alloy seat clamp
		<b>SHIFT LEVERS</b>	Shimano 105 STI 22 speed shifters		
		<b>CASSETTE</b>	Shimano 11 speed cassette 11-28T		





MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c light weight butted alloy frame with road specific geometry

Upgraded oversized carbon fork with alloy steer tube.

Shimano SORA 18 speed shifting

FSA Vero Compact 34/50T Crank.

Alloy hubs with Weinmann Double Wall rims.

Addition of an in-line cable adjuster for shifter cables.

### CODES

	XS	S	M	L	XL
Gloss Black / Gloss Green	16048	16049	16050	16051	16052

### GEOMETRY

	XS	S	M	L	XL
STACK	523	542	558	584	629
REACH	370	374	385	391	398
EFFECTIVE TOP TUBE	515	530	550	570	590
SEAT TUBE (CENTRE TO TOP)	500	520	550	580	610
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	185	230
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	975	984	994	1004	1013
CHAIN STAY LENGTH	415	415	415	415	415
BB DROP	72	72	72	72	72
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	367	367	367	367	367
REAR DROPOUT SPACING	130	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Superlite triple butted 6061 alloy, smooth welded, integrated head tube and replaceable derailleur hanger	<b>HEADSTEM</b>	Factor 1-1/8" 3D forged alloy 4 bolt stem. XS=90mm, S=100mm, M/L=110mm, XL=120mm	<b>CHAIN</b>	KMC X-9
<b>FORK</b>	Carbon oversized 1-1/8 straight blades with alloy steerer, fully integrated	<b>CRANKSET</b>	FSA Vero compact, 50 x 34T XS=170mm, S/M=172.5mm, L/XL=175mm	<b>BRAKES</b>	Tektro R-312 dual pivot
<b>HEADSET</b>	A-head integrated 1-1/8 cartridge bearings with 15mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge sealed	<b>WHEELS</b>	Weinmann DNZ18 sleeved double wall 24mm deep rim, CNC machined side walls, 32 hole F/V, alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Factor butted alloy Anatomic shallow drop 31.8mm alloy W: XS/S/M=42cm, L/XL=44cm	<b>PEDALS</b>	Nil	<b>TYRES</b>	Hutchinson Nitro 2 700c x 25c 33tpi
<b>GRIP</b>	PU performance tape	<b>F. DERAILEUR</b>	Shimano Sora band clamp	<b>SADDLE</b>	Factor Road
		<b>R. DERAILEUR</b>	Shimano Sora 9 speed	<b>SEATPOST / CLAMP</b>	Factor 27.2mm alloy post, twin bolt with alloy seat clamp
		<b>SHIFT LEVERS</b>	Shimano Sora 18 speed STI shifters		
		<b>CASSETTE</b>	Shimano HG-50 9 speed cassette 11-30T		



### KEY FEATURES

700c light weight butted alloy frame with women specific geometry

Upgraded oversized carbon fork with alloy steer tube.

Shimano SORA 18 speed shifting

FSA Vero Compact 34/50T Crank.

Alloy hubs with Weinmann Double Wall rims.

Addition of an in-line cable adjuster for shifter cables.

### CODES

	XS	S	M
Gloss White / Gloss Navy Blue	16053	16054	16055

### GEOMETRY

	XS	S	M
STACK	504	524	545
REACH	375	374	376
EFFECTIVE TOP TUBE	510	519	532
SEAT TUBE (CENTRE TO TOP)	460	480	520
SEAT ANGLE	75.0°	74.5°	74.0°
HEAD TUBE LENGTH	110	130	150
HEAD ANGLE	71.0°	71.5°	72.0°
WHEEL BASE	981	982	995
CHAIN STAY LENGTH	415	415	415
BB DROP	70	70	70
FORK RAKE	45	45	45
AXLE TO CROWN	367	367	367
REAR DROPOUT SPACING	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Women's specific Superlite triple butted 6061 alloy, smooth welded, integrated head tube and replaceable derailleur hanger
<b>FORK</b>	Carbon oversized 1-1/8" straight blades with alloy steerer, fully integrated
<b>HEADSET</b>	A-head integrated 1-1/8" cartridge bearings with 15mm cone spacer
<b>HANDLEBAR</b>	Factor butted alloy female specific alloy road bar with short reach and shallow drop 31.8. XS=38cm, S/M=40cm
<b>GRIP</b>	PU performance tape

<b>HEADSTEM</b>	Factor 1-1/8" 3D forged alloy 4 bolt stem. XS/S=90mm, M=100mm
<b>CRANKSET</b>	FSA Vero compact 50 x 34T, XS/S/M=170mm
<b>BOTTOM BRACKET</b>	Cartridge sealed
<b>PEDALS</b>	Resin with toe straps
<b>F. DERAILLEUR</b>	Shimano Sora band clamp
<b>R. DERAILLEUR</b>	Shimano Sora 9 speed
<b>SHIFT LEVERS</b>	Shimano Sora 18 speed STI shifters
<b>CASSETTE</b>	Shimano HG-50 9 speed cassette 11-30T

<b>CHAIN</b>	KMC X-9
<b>BRAKES</b>	Tektro R-312 dual pivot
<b>WHEELS</b>	Weinmann DNZ18 sleeved double wall 24mm deep rim, CNC machined side walls, 32 hole F/V, alloy hubs and stainless spokes.
<b>TYRES</b>	Hutchinson Nitro 2 700c x 25c 33tpi
<b>SADDLE</b>	Factor female specific road with cutout
<b>SEATPOST / CLAMP</b>	Factor 27.2mm alloy post, twin bolt with alloy seat clamp



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c light weight butted alloy frame with road specific geometry

Lightweight alloy fork with alloy steer tube.

Lightweight wheels with alloy hubs with Weinmann double wall rims

Shimano Claris 16 speed shifting.

Powerful Tektro Caliper brakes.

Addition of an in-line cable adjuster for shifter cables.

### CODES

	XS	S	M	L	XL
Gloss Black / Gloss White	17005	17006	17007	17008	17009

### GEOMETRY

	XS	S	M	L	XL
STACK	530	549	565	591	636
REACH	368	373	383	389	396
STAND OVER HEIGHT	396	415	430	458	495
EFFECTIVE TOP TUBE	515	530	550	570	590
SEAT TUBE (CENTRE TO TOP)	460	480	500	530	560
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	185	230
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	975	984	994	1004	1013
CHAIN STAY LENGTH	410	410	410	410	410
BB DROP	72	72	72	72	72
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	374	374	374	374	374
REAR DROPOUT SPACING	130	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy, integrated head tube and replaceable derailleur hanger	<b>HEADSTEM</b>	Factor 3D forged 2 bolt Road 1-1/8" alloy XS/S=90mm, M/L=110mm, XL=120mm	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	1-1/8 alloy straight blades fully integrated	<b>CRANKSET</b>	FSA Tempo compact, 50 x 34T XS=170mm, S/M=172.5mm, L/XL=175mm	<b>BRAKES</b>	Tektro R-312 dual pivot
<b>HEADSET</b>	A-head integrated 1-1/8"	<b>BOTTOM BRACKET</b>	Cartridge sealed	<b>WHEELS</b>	700c Weinmann X-MI 32 hole box section rims paired with alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Factor butted alloy Anatomic shallow drop 31.8mm alloy W: XS/S/M=42cm, L/XL=44cm	<b>PEDALS</b>	Nil	<b>TYRES</b>	Kenda K-196 700 x 26c 30tpi
<b>GRIP</b>	Soft compound EVA wrap	<b>F. DERAILLEUR</b>	Shimano Claris band clamp	<b>SADDLE</b>	Factor Road
		<b>R. DERAILLEUR</b>	Shimano Claris 8 speed	<b>SEATPOST / CLAMP</b>	Factor 27.2mm alloy post, twin bolt with alloy seat clamp
		<b>SHIFT LEVERS</b>	Shimano Claris 16 speed STI shifters		
		<b>CASSETTE</b>	Shimano 8 speed cassette 13-26T		



### KEY FEATURES

Apollo Carbon time trail frame with, integrated fork, stem, handle bar and seat post.

DT Swiss RC55 Carbon wheels

TRP arrow mini V-brakes.

Shimano Dura Ace Di2 shifting

Time trail specific saddle

### CODES

	XS	S	M	L	XL
Matte Nude Carbon / Matte Chrome	16081	16082	16083	16084	16085

### GEOMETRY

	XS	S	M	L	XL
STACK	494	509	518	536	553
REACH	358	375	393	406	448
EFFECTIVE TOP TUBE	490	511	532	550	596
SEAT TUBE (CENTRE TO TOP)	450	515	525	540	561
SEAT ANGLE	75.0°	75.0°	75.0°	75.0°	75.0°
HEAD TUBE LENGTH	91	102	111	130	148
HEAD ANGLE	71.0°	72.5°	72.5°	72.5°	72.5°
WHEEL BASE	946	946	967	987	1006
CHAIN STAY LENGTH	395	395	395	395	395
BB DROP	75	75	75	75	75
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	370	370	370	370	370
REAR DROPOUT SPACING	130	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Arctec aero monocoque frame with integrated handlebar and stem system. BSA threaded bottom bracket, hidden seat post clamp, tapered head tube and hidden aero front and rear brakes.
<b>FORK</b>	Fully integrated bayonet style monocoque carbon aero fork and stem system with carbon steerer and aerodynamic concealed front brake
<b>HEADSET</b>	A-head integrated 1-1/8" cartridge bearings
<b>HANDLEBAR</b>	Carbon airwing base bar with internal cable routing 400mm wide
<b>GRIP</b>	PU performance tape

<b>HEADSTEM</b>	Integrated aero stem and faceplate
<b>CRANKSET</b>	Shimano 6800 Ultegra crank, 53/39T, L: XS/S=170mm, M/L=172.5mm, XL=175mm
<b>BOTTOM BRACKET</b>	SRAM GXP threaded
<b>PEDALS</b>	N/A
<b>F. DERAILLEUR</b>	Shimano Ultegra 6870-F Di2
<b>R. DERAILLEUR</b>	Shimano Ultegra 6870 Di2 11 speed
<b>SHIFT LEVERS</b>	Shimano Ultegra 6870 Di2 22 speed STI shifters
<b>CASSETTE</b>	Shimano 5800 11 speed cassette 11-25T
<b>CHAIN</b>	KMC 11 speed

<b>BRAKES</b>	Tektro aero brake caliper with SRAM alloy brake levers
<b>WHEELS</b>	DT Swiss RC55 Spline hand built carbon clincher wheelset. 55mm deep rim, 20 hole front; 24 hole rear laced with DT Swiss hubs, DT aerolite spokes, alloy nipples, RWS skewers
<b>TYRES</b>	Hutchinson Atom Comp 700 x 23 with Kevlar pro tech triple compound, 160g, 127tpi
<b>SADDLE</b>	Factor TT specific saddle
<b>SEATPOST / CLAMP</b>	Aero carbon post with 80mm of fore and aft adjustment



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

Apollo Carbon time trail frame with, integrated fork, stem, handle bar and seat post.

Alloy hubs with Sun Ringle Venus rims

TRP arrow mini V-brakes.

SRAM 22 speed shifting.

Time trail specific saddle

### CODES

	XS	S	M	L	XL
Matte Nude Carbon / Matte Red	16086	16087	16088	16089	16090

### GEOMETRY

	XS	S	M	L	XL
STACK	494	509	518	536	553
REACH	358	375	393	406	448
EFFECTIVE TOP TUBE	490	511	532	550	596
SEAT TUBE (CENTRE TO TOP)	450	515	525	540	561
SEAT ANGLE	75.0°	75.0°	75.0°	75.0°	75.0°
HEAD TUBE LENGTH	91	102	111	130	148
HEAD ANGLE	71.0°	72.5°	72.5°	72.5°	72.5°
WHEEL BASE	946	946	967	987	1006
CHAIN STAY LENGTH	395	395	395	395	395
BB DROP	75	75	75	75	75
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	370	370	370	370	370
REAR DROPOUT SPACING	130	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Arctec aero monocoque frame with integrated handlebar and stem system. BSA threaded bottom bracket, hidden seat post clamp, tapered head tube and hidden aero front and rear brakes.	<b>GRIP</b>	PU performance tape	<b>CASSETTE</b>	SRAM 11 speed cassette 11-25T
<b>FORK</b>	Fully integrated bayonet style monocoque carbon aero fork and stem system with carbon steerer and aerodynamic concealed front brake	<b>HEADSTEM</b>	Integrated aero stem and faceplate	<b>CHAIN</b>	KMC X-11
<b>HEADSET</b>	A-head integrated 1-1/8" cartridge bearings	<b>CRANKSET</b>	FSA Mega EXO 53/39 L: XS/S=170mm, M/L=172.5mm, XL=175mm	<b>BRAKES</b>	Tektro aero brake caliper with SRAM alloy brake levers
<b>HANDLEBAR</b>	Carbon airwing base bar with internal cable routing 400mm wide	<b>BOTTOM BRACKET</b>	FSA with external cups	<b>WHEELS</b>	Sun Ringle Venus welded rim, 28 hole, 25mm deep rims paired with 11 speed sealed bearing alloy hubs and DT Champion stainless spokes.
		<b>PEDALS</b>	N/A	<b>TYRES</b>	Hutchinson Nitro 700 x 25c 33tpi
		<b>F. DERAILLEUR</b>	SRAM Rival 22	<b>SADDLE</b>	Factor TT specific saddle
		<b>R. DERAILLEUR</b>	SRAM Rival 22 speed	<b>SEATPOST / CLAMP</b>	Aero carbon post with 80mm of fore and aft adjustment
		<b>SHIFT LEVERS</b>	SRAM TT-500 22 speed		



## KEY FEATURES

Apollo custom lightweight disc specific Carbon frame and fork, with comfort road geometry.

BB86 / BB386 BB Interface.

15mm thru axles on the front, 12mm thru axle on the rear.

Shimano Ultegra road hydraulic disc brakes with 160mm rotors front and rear.

Shimano 22 speed Ultegra shifting

FSA Energy BB386 36/52T 2-pc Crank

Addition of an in-line cable adjuster for shifter cables.

Upgraded DT SWISS 444D rims.

## CODES

	XS	S	M	L	XL
Matte Nude Carbon / Gloss Black	16066	16067	16068	16069	16070

## GEOMETRY

	XS	S	M	L	XL
STACK	530	549	565	591	636
REACH	368	373	383	389	396
STAND OVER HEIGHT	396	415	430	458	495
EFFECTIVE TOP TUBE	515	530	550	570	590
SEAT TUBE (CENTRE TO TOP)	460	480	500	530	560
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	185	230
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	968	978	990	999	1014
CHAIN STAY LENGTH	410	410	410	410	410
BB DROP	72	72	72	72	72
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	374	374	374	374	374
REAR DROPOUT SPACING	142	142	142	142	142

## SPECIFICATIONS

<b>FRAME</b>	Hi-modulus Mitsubishi carbon modular monocoque disc specific road frame. Box technology down tube with BB386 press fit system, slim seatstays, Tapered head tube 1-1/8 to 1-1/2,	<b>HEADSTEM</b>	Factor 1-1/8" 3D forged alloy 4 bolt stem. XS=90mm, S=100mm, M=110mm, L/XL=120mm	<b>CASSETTE</b>	Shimano 11 speed cassette 12-25T
<b>FORK</b>	Full carbon straight blade disc specific fork with tapered 1-1/8 to 1-1/2 carbon steerer, fully integrated	<b>CRANKSET</b>	FSA Energy BB386 cold forged crank, 52/36T alloy Rings L: XS/S=170mm, M=172.5mm, L/XL=175mm	<b>CHAIN</b>	KMC 11 speed
<b>HEADSET</b>	A-head integrated 1-1/2 to 1-1/8 sealed angular cartridge bearings with 15mm cone spacer	<b>BOTTOM BRACKET</b>	Press fit BB386	<b>BRAKES</b>	Shimano BR-505 hydraulic road disc brakes with 140mm rotors
<b>HANDLEBAR</b>	Factor butted alloy Anatomic shallow drop 31.8mm alloy W: XS=40cm, S/M=42cm, L/XL=44cm	<b>PEDALS</b>	Nil	<b>WHEELS</b>	DT Swiss R-444d disc specific road rim, 32 hole paired with 11 speed sealed bearing disc alloy hubs and stainless spokes.
<b>GRIP</b>	PU performance tape	<b>F. DERAILLEUR</b>	Shimano Ultegra 6800 braze on	<b>TYRES</b>	Hutchinson Equinox 2 700 x 25c 66tpi folding bead
		<b>R. DERAILLEUR</b>	Shimano Ultegra 6800 11 speed	<b>SADDLE</b>	Factor road
		<b>SHIFT LEVERS</b>	Shimano Ultegra RS-505 22 speed STI hydraulic road shifters	<b>SEATPOST / CLAMP</b>	Factor 27.2mm 350mm long post, twin bolt, forged head, alloy seat clamp



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c light weight butted alloy frame with road specific geometry

New lightweight full carbon fork with carbon steer tube.

Lightweight wheels with alloy hubs with DT SWISS 545D rims

Fast rolling Veetire Roadrunner 700c x 28c tyres

Shimano 22 speed 105 shifting

Shimano Compact 34/50T 2-pc crank

Powerful road specific Tektro flat mount Disc brakes with 160mm rotors.

In-line cable adjuster for shifter cables for easy shifter adjustments.

### CODES

	XS	S	M	L	XL
Matte Charcoal / Gloss Black	17010	17011	17012	17013	17014

### GEOMETRY

	XS	S	M	L	XL
STACK	523	542	558	584	629
REACH	370	375	385	392	398
STAND OVER HEIGHT	396	415	430	458	495
EFFECTIVE TOP TUBE	515	530	550	570	590
SEAT TUBE (CENTRE TO TOP)	460	480	500	530	560
SEAT ANGLE	74.5°	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	125	145	160	185	230
HEAD ANGLE	72.0°	72.0°	72.5°	73.0°	73.5°
WHEEL BASE	976	987	998	1007	1027
CHAIN STAY LENGTH	415	415	415	415	415
BB DROP	65	65	65	65	65
FORK RAKE	45	45	45	45	45
AXLE TO CROWN	374	374	374	374	374
REAR DROPOUT SPACING	135	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Superlite butted 6061 alloy, integrated head tube and replaceable derailleur hanger	<b>HEADSTEM</b>	Factor 1-1/8" 3D forged alloy 4 bolt stem. XS=90mm, S=100mm, M/L=110mm, XL=120mm	<b>CASSETTE</b>	Shimano 11 speed cassette 11-28T
<b>FORK</b>	Alloy 1-1/8 straight blades with alloy steerer, fully integrated. HI VIZ reflective decals	<b>CRANKSET</b>	Shimano FC-R500 compact 50 x 34T 2 piece crank, XS=170mm, S/M=172.5mm, L/XL=175mm	<b>CHAIN</b>	KMC 11 speed
<b>HEADSET</b>	A-head integrated 1-1/8 cartridge bearings with 15mm cone spacer	<b>BOTTOM BRACKET</b>	Shimano integrated sealed	<b>BRAKES</b>	Hayes CX Comp mechanical disc brakes with 160mm rotors
<b>HANDLEBAR</b>	Factor butted alloy Anatomic shallow drop 31.8mm alloy W: XS/S/M=42cm, L/XL=44cm	<b>PEDALS</b>	Nil	<b>WHEELS</b>	700c DT Swiss R-545D double wall disc specific rims, 32 hole 11 speed disc hubs with stainless spokes
<b>GRIP</b>	PU performance tape	<b>F. DERAILLEUR</b>	Shimano 105 band clamp	<b>TYRES</b>	Veetire Roadrunner 700 x 28c, 27TPI
		<b>R. DERAILLEUR</b>	Shimano 105 11 speed	<b>SADDLE</b>	Factor road
		<b>SHIFT LEVERS</b>	Shimano 105 STI 22 speed shifters	<b>SEATPOST / CLAMP</b>	Factor alloy 27.2mm post, twin bolt with alloy seat clamp





# TRANSFER

## URBAN TOUGH

Weekday commuter designed with similar agility and comfort as our Trace series, the Transfer offers a suspension fork and knobby tyres; ideal for going from street to gravel with confidence.

### SUSPENSION FORK

Confidence and control on rough surfaces.

### WIDE TYRES

Multi-terrain 700 x 38, for better grip and control.

### DOUBLE WALL RIMS

Greater strength for urban environments.

### CARRIER & FENDER MOUNTS

Easily customisable to suit your riding needs.

### LIGHT WEIGHT

Light and strong - double or triple butted frames for easy riding.

MTB

ROAD

LIFESTYLE

YOUTH



### KEY FEATURES

700c alloy frame, with Apollo's performance geometry.

RST Neon Suspension fork with 60mm of travel and Mechanical lockout.

Alloy hubs, with Weinmann double wall rims.

700c x 38c urban multi-terrain tyres.

24 speed Shimano rapid-fire shifting with cassette.

Oversized 31.8mm handlebar and stem

Powerful Promax Hydraulic disc brakes, with 160mm rotors.

Apollo Custom comfort Grip.

### CODES

	S	M	L	XL
Gloss Bronze / Gloss Charcoal	17061	17062	17063	17064

### GEOMETRY

	S	M	L	XL
STACK	573	584	600	615
REACH	380	402	416	426
STAND OVER HEIGHT	409	441	473	504
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	100	110	125	140
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1043	1062	1077	1091
CHAIN STAY LENGTH	440	440	440	440
BB DROP	50	50	50	50
FORK RAKE	44	44	44	44
AXLE TO CROWN	470	470	470	470
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Triple butted 6061 frame with smooth welding. Integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>HEADSTEM</b>	4 bolt alloy stem, 31.8mm, S/M=90mm, L/XL=105mm	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	RST Neon suspension fork, 60mm travel with lockout and preload. Alloy crown with magnesium lowers	<b>CRANKSET</b>	Suntour XCE 48 x 38 x 28T L: S/M=170mm, L/XL=175mm	<b>BRAKES</b>	Promax Decipher hydraulic disc brakes with reach adjust, 160mm rotors
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Weinmann U-26 double wall disc specific rims, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 600mm, sweep: 6°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Multi terrain utility tread, 700 x 38c wire bead
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano M191 8 speed for 31.8	<b>SADDLE</b>	Factor Ergotech dual density saddle
		<b>R. DERAILLEUR</b>	Shimano Alivio 8 speed	<b>SEATPOST / CLAMP</b>	Alloy twin bolt micro adjust 27.2mm
		<b>SHIFT LEVERS</b>	Shimano Altus 24 speed Rapid Fire	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c alloy frame, with Apollo's performance geometry.

RST Neon Suspension fork with 60mm of travel and Mechanical lockout.

Alloy hubs, with Weinmann double wall rims.

700c x 38c urban multi-terrain tyres.

24 speed Shimano EZ-fire shifting.

Oversized 31.8mm handlebar and stem

Powerful mechanical disc brakes, with 160mm rotors.

Apollo custom comfort grip.

### CODES

	S	M	L	XL
Matte Black / Matte White / Matte Blue	17065	17066	17067	17068

### GEOMETRY

	S	M	L	XL
STACK	573	584	600	615
REACH	380	402	416	426
STAND OVER HEIGHT	409	441	473	504
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	100	110	125	140
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1043	1062	1077	1091
CHAIN STAY LENGTH	440	440	440	440
BB DROP	50	50	50	50
FORK RAKE	44	44	44	44
AXLE TO CROWN	470	470	470	470
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy frame with integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>CRANKSET</b>	Suntour XCE 48 x 38 x 28T L: S/M=170mm, L/XL=175mm	<b>BRAKES</b>	TEKTRO MD-280 mechanical disc brakes with 160mm rotors
<b>FORK</b>	RST Neon suspension fork, 60mm travel with lockout and preload. Alloy crown with alloy lowers	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Weinmann X-M1 double wall rims, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Urban multi terrain, 700 x 38c wire bead
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 600mm wide, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano M191 8 speed for 31.8	<b>SADDLE</b>	Factor Ergotech dual density saddle
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>HEADSTEM</b>	Alloy, 31.8mm, S=70mm, M/L=90mm, XL=105mm	<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed	<b>SEATPOST / CLAMP</b>	Factor 31.6mm alloy, micro adjust with twin bolt head, L:400mm
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T	<b>EXTRAS</b>	N/A
		<b>CHAIN</b>	KMC Z-7		

MTB

ROAD



### KEY FEATURES

700c alloy frame, with Apollo's performance Women's specific geometry

RST Neon Suspension fork with 60mm of travel and Mechanical lockout.

Alloy hubs, with Weinmann double wall rims.

700c x 38c urban multi-terrain tyres.

24 speed Shimano EZ-fire shifting.

Oversized 31.8mm handlebar and stem

Women's specific saddle for maximum riding comfort.

Powerful mechanical disc brakes, with 160mm rotors.

Apollo custom comfort grip.

### CODES

	XS	S	M
Gloss Navy Blue / Gloss Silver / Gloss Turquoise	17069	17070	17071

### GEOMETRY

	XS	S	M
STACK	583	600	615
REACH	367	377	388
EFFECTIVE TOP TUBE	396	418	440
SEAT TUBE (CENTRE TO TOP)	540	555	570
SEAT ANGLE	400	430	460
HEAD TUBE LENGTH	73.5"	73.5"	73.5"
HEAD ANGLE	110	125	140
WHEEL BASE	70.0"	70.5"	71.0"
CHAIN STAY LENGTH	1041	1053	1062
BB DROP	440	440	440
FORK RAKE	55	55	55
AXLE TO CROWN	43	43	45
REAR DROPOUT SPACING	470	470	470
	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy women's specific frame with integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>HEADSTEM</b>	Alloy, 31.8mm, XS/S= 70mm, M=90mm	<b>BRAKES</b>	TEKTRO MD-280 mechanical disc brakes with 160mm rotors
<b>FORK</b>	RST Neon suspension fork, 60mm travel with lockout and preload. Alloy crown with alloy lowers	<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L=170mm	<b>WHEELS</b>	700c Weinmann X-M1 double wall rims, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>TYRES</b>	Urban multi terrain, 700 x 38c wire bead
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 580mm, sweep: 6°	<b>PEDALS</b>	Low profile high impact resin	<b>SADDLE</b>	Factor women's specific Ergotech dual density saddle
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano M191 8 speed for 31.8	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>EXTRAS</b>	N/A
		<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed		
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		
		<b>CHAIN</b>	KMC Z-7		

LIFESTYLE

YOUTH

## TRANSFER 10

700C TRAIL - 21 SPEED



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

700c alloy frame, with Apollo's performance geometry.

Suntour M-3010 Suspension fork with 50mm of travel.

Alloy hubs, with Weinmann double wall rims.

700c x 38c urban multi-terrain tyres.

21 speed Shimano EZ-fire shifting.

Oversized 31.8mm handlebar and stem.

Selle Royal saddle for maximum riding comfort.

Powerful Promax V-Brakes.

Apollo custom comfort grip.

## CODES

	S	M	L	XL
Gloss Red / Gloss Black / Gloss Charcoal	17072	17073	17074	17075
Gloss Charcoal / Gloss Black / Gloss Green	17076	17077	17078	17079

## GEOMETRY

	S	M	L	XL
STACK	573	584	600	615
REACH	380	402	416	426
STAND OVER HEIGHT	409	441	473	504
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	100	110	125	140
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1043	1062	1077	1091
CHAIN STAY LENGTH	440	440	440	440
BB DROP	50	50	50	50
FORK RAKE	44	44	44	44
AXLE TO CROWN	470	470	470	470
REAR DROPOUT SPACING	135	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy frame, pannier mounts and replaceable derailleur hanger.	<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L=170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>FORK</b>	Suntour M3010 suspension fork, 700c, 50mm travel, alloy crown and lowers	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Weinmann X-M1 double wall alloy rims. 32 hole A/V, alloy quick release hubs with double seal system. Stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	High impact nylon	<b>TYRES</b>	Urban multi terrain, 700 x 38c wire bead
<b>HANDLEBAR</b>	Low riser, bore: 31.8mm, W:600mm, sweep: 6°	<b>F. DERAILEUR</b>	Shimano TX-800 top pull for 31.8mm	<b>SADDLE</b>	Factor Ergotech saddle
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILEUR</b>	Shimano TY-300 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>HEADSTEM</b>	Alloy, 31.8mm, S=70mm, M/L=90mm, XL=105mm	<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed	<b>SEATPOST / CLAMP</b>	N/A
		<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel	<b>EXTRAS</b>	N/A
		<b>CHAIN</b>	KMC Z-51		



MTB

ROAD

LIFESTYLE

### KEY FEATURES

700c alloy frame, with Apollo's performance Women's specific geometry

Suntour M-3010 Suspension fork with 50mm of travel.

Alloy hubs, with Weinmann double wall rims.

700c x 38c semi-slick tyres.

21 speed Shimano EZ-fire shifting.

Oversized 31.8mm handlebar and stem.

Women's specific saddle for maximum riding comfort.

Powerful Promax V-Brakes.

Apollo custom comfort grip.

### CODES

	XS	S	M
Gloss White / Gloss Charcoal / Gloss Pink	17080	17081	17082
Gloss Charcoal / Gloss Silver / Gloss Lavender	17083	17084	17085

### GEOMETRY

	XS	S	M
STACK	583	600	615
REACH	367	377	388
EFFECTIVE TOP TUBE	396	418	440
SEAT TUBE (CENTRE TO TOP)	540	555	570
SEAT ANGLE	400	430	460
HEAD TUBE LENGTH	73.5"	73.5"	73.5"
HEAD ANGLE	110	125	140
WHEEL BASE	70.0"	70.5"	71.0"
CHAIN STAY LENGTH	1041	1053	1062
BB DROP	440	440	440
FORK RAKE	55	55	55
AXLE TO CROWN	43	43	45
REAR DROPOUT SPACING	470	470	470
	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy women's specific frame, pannier mounts and replaceable derailleur hanger.
<b>FORK</b>	Suntour M3010 suspension fork, 700c, 50mm travel, alloy crown and lowers
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer
<b>HANDLEBAR</b>	Low riser, bore: 31.8mm, W: 580mm, sweep: 6°
<b>GRIP</b>	Kraton ERGO comfort grip

<b>HEADSTEM</b>	Alloy, 31.8mm, XS/S= 70mm, M=90mm
<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L=170mm
<b>BOTTOM BRACKET</b>	Cartridge bottom bracket
<b>PEDALS</b>	High impact nylon
<b>F. DERAILLEUR</b>	Shimano TX-800 top pull for 31.8mm
<b>R. DERAILLEUR</b>	Shimano TY-300 7 speed
<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed
<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel

<b>CHAIN</b>	KMC Z-51
<b>BRAKES</b>	Alloy linear pull brakes
<b>WHEELS</b>	700c Weinmann X-M1 double wall alloy rims. 32 hole A/V, alloy quick release hubs with double seal system. Stainless spokes
<b>TYRES</b>	Urban multi terrain, 700 x 38c wire bead
<b>SADDLE</b>	Factor women's specific Ergotech saddle
<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>EXTRAS</b>	N/A

YOUTH

# TRACE

## URBAN COOL

A weekday commuter that is more relaxed and comfortable than a flat bar road bike, with increased stopping power, and a rigid fork with slick, wider tyres. Exceptional versatility to tackle any weekend getaway.

### **RIGID FORK**

Light and responsive handling.

### **WIDE TYRES**

700 x 38, up to  
700 x 40 for smooth  
rolling comfort.

### **DOUBLE WALL RIMS**

Greater strength for  
urban environments.

### **CARRIER & FENDER MOUNTS**

Easily customisable to  
suit your riding needs.

### **LIGHT WEIGHT**

Light and strong - double  
or triple butted frames  
for easy riding.



### KEY FEATURES

700c light weight butted Alloy Frame, with Apollo's performance geometry, and eccentric BB, perfect for commuting.

Alloy integrated fork with alloy steer tube.

Alloy hubs, with Weinmann double wall rims.

700c x 40c slick tyres with reflective sidewall.

Shimano Alfine Inner-11 geared hub.

Gates CentreTrack Belt Drive system.

Powerful Shimano Hydraulic disc brakes, with 160mm rotors.

Apollo custom comfort grip and oversized handlebar and stem.

### CODES

	S	M	L	XL
Matte Black / Gloss Black	16128	16129	16130	16131

### GEOMETRY

	S	M	L	XL
STACK	530	555	576	595
REACH	393	411	424	432
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	130	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1039	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	60	60	60	60
FORK RAKE	45	45	45	45
AXLE TO CROWN	385	385	385	385
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Triple butted superlite 6061 frame with smooth welding. Belt drive compatible, integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>CRANKSET</b>	Shimano Alfine 2 piece crank with 46T Gates Centretrack belt drive chainring and chain guard L: M/L/XL=170mm	<b>CASSETTE</b>	Gates Centretrack 24T sprocket for belt drive
<b>FORK</b>	Ultralite full alloy 700c disc specific post mount fork with alloy steerer and rack and fender mounts,	<b>BOTTOM BRACKET</b>	German designed Eccentric bottom bracket width adjustable and tension adjustable design with Shimano integrated sealed cartridge	<b>CHAIN</b>	Gates Centretrack belt
<b>HEADSET</b>	A-head semi integrated 1-1/8" with cartridge bearings, 10mm cone spacer	<b>PEDALS</b>	Low profile high impact resin	<b>BRAKES</b>	Shimano BR-M505 servo wave hydraulic disc brakes with 160mm rotors
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 600mm, sweep: 6°	<b>F. DERAILLEUR</b>	Nil	<b>WHEELS</b>	XM25 disc specific double wall rims, 32 hole F/V, Alfine 11 internal gear rear hub
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	Internal hub gears	<b>TYRES</b>	CST Sensamo 700 x 40c 60tpi, puncture protection belt and reflective side walls
<b>HEADSTEM</b>	3D forged 4 bolt alloy stem, 31.8mm, L: S=80mm M=90mm, L=100mm, XL=110	<b>SHIFT LEVERS</b>	Shimano Alfine 11 speed Rapidfire with internal gear rear hub	<b>SADDLE</b>	Factor Ergotech dual density saddle
				<b>SEATPOST / CLAMP</b>	Alloy twin bolt micro adjust 27.2mm
				<b>EXTRAS</b>	N/A



## TRACE 45 HI-VIZ

700C CITY - 8 SPEED WITH GATES BELT DRIVE AND  
ECCENTRIC BOTTOM BRACKET

MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

700c light weight butted Alloy Frame, with Apollo's performance geometry, and eccentric BB, perfect for commuting.

Hi-Viz painting, with reflective decals on the rear stay and fork.

Alloy integrated fork with steel steer tube.

Alloy hubs, with Weinmann double wall rims.

700c x 40c slick tyres with reflective sidewall.

Shimano Alfine Inner-8 geared hub.

Gates mud port Belt Drive system.

Powerful Promax Hydraulic disc brakes, with 160mm rotors.

Apollo custom comfort grip and oversized handlebar and stem.

## CODES

	S	M	L	XL
Gloss Orange / Gloss Teal / Reflective	16132	16133	16134	16135

## GEOMETRY

	S	M	L	XL
STACK	530	555	576	595
REACH	393	411	424	432
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	130	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1039	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	60	60	60	60
FORK RAKE	45	45	45	45
AXLE TO CROWN	385	385	385	385
REAR DROPOUT SPACING	135	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	Butted 6061 alloy frame with smooth welding. Belt drive compatible, integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>CRANKSET</b>	Forged crank with Gates CDC Mudport 46T chainring L: S/M/L/XL=175mm	<b>BRAKES</b>	Promax Decipher hydraulic disc brakes with 160mm rotors
<b>FORK</b>	Alloy 700c disc specific post mount fork with rack and fender mounts, Hi VIZ reflective decals	<b>BOTTOM BRACKET</b>	German designed Eccentric bottom bracket, width adjustable and tension adjustable design with Shimano integrated sealed cartridge	<b>WHEELS</b>	XM25 disc specific double wall rims with Hi VIZ reflective decals, 32 hole F/V, Alloy disc front hub, Shimano Alfine internal 8 speed rear hub
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	CST Sensamo 700 x 40c 60tpi, puncture protection belt and reflective side walls
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 600mm, sweep: 6°	<b>F. DERAILLEUR</b>	Nil	<b>SADDLE</b>	Factor Ergotech dual density saddle
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	Internal hub gears	<b>SEATPOST / CLAMP</b>	Alloy twin bolt micro adjust 27.2mm
<b>HEADSTEM</b>	4 bolt alloy stem, 31.8mm, S=90mm, M/L/XL=105mm	<b>SHIFT LEVERS</b>	Shimano Alfine 8 speed Rapidfire with Alfine internal gear rear hub	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Gates CDC Mudport 24T sprocket for belt drive		
		<b>CHAIN</b>	Gates CDC Mudport belt		

MTB

ROAD

LIFESTYLE

YOUTH



### KEY FEATURES

700c light weight butted Alloy Frame, with Apollo's performance geometry, and eccentric BB, perfect for commuting.

Alloy integrated fork with steel steer tube.

Alloy hubs, with Weinmann double wall rims.

700c x 40c slick tyres with reflective sidewall.

Shimano Alfine Inner-8 geared hub.

Gates mud port Belt Drive system.

Powerful Hayes MX Comp mechanical disc brakes, with 160mm rotors.

Apollo custom comfort grip and oversized handlebar and stem.

### CODES

	S	M	L	XL
Matte Charcoal / Matte Black	16136	16137	16138	16139

### GEOMETRY

	S	M	L	XL
STACK	530	555	576	595
REACH	393	411	424	432
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	130	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1039	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	60	60	60	60
FORK RAKE	45	45	45	45
AXLE TO CROWN	385	385	385	385
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Butted 6061 alloy frame with smooth welding. Belt drive compatible, integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>CRANKSET</b>	Forged crank with Gates CDC Mudport 46T chainring L: S/M/L/XL=175mm	<b>CHAIN</b>	Gates CDC Mudport belt
<b>FORK</b>	700c disc specific hi-ten rigid integrated trekking fork with rack and fender mounts	<b>BOTTOM BRACKET</b>	German designed Eccentric bottom bracket, width adjustable and tension adjustable design with Shimano integrated sealed cartridge	<b>BRAKES</b>	Hayes MX Comp mechanical disc brakes with 160mm rotors
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	Low profile high impact resin	<b>WHEELS</b>	XM25 double wall disc specific rims, 32 hole F/V, Alloy disc front hub, Shimano Alfine internal 8 speed rear hub
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 600mm, sweep: 6°	<b>F. DERAILEUR</b>	Nil	<b>TYRES</b>	CST Sensamo 700 x 40c 60tpi, puncture protection belt and reflective side walls
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILEUR</b>	Internal hub gears	<b>SADDLE</b>	Factor Ergotech dual density saddle
<b>HEADSTEM</b>	4 bolt alloy stem, 31.8mm, S=90mm, M/L/XL=105mm	<b>SHIFT LEVERS</b>	Shimano Alfine 8 speed Rapidfire with Alfine internal gear rear hub	<b>SEATPOST / CLAMP</b>	Alloy twin bolt micro adjust 27.2mm
		<b>CASSETTE</b>	Gates CDC Mudport 24T sprocket for belt drive	<b>EXTRAS</b>	N/A



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c light weight butted Alloy Frame, with Apollo's performance geometry, perfect for commuting.

Alloy integrated fork with alloy steer tube.

Alloy hubs, with Weinmann double wall rims.

700c x 40c slick tyres with reflective sidewall.

SRAM X-5 2 x 10 shifting.

Powerful Promax Decipher Hydraulic disc brakes, with 160mm rotors.

Apollo custom comfort grip and oversized handlebar and stem.

### CODES

	S	M	L	XL
Matte Navy Blue / Gloss Black	16140	16141	16142	16143

### GEOMETRY

	S	M	L	XL
STACK	530	555	576	595
REACH	393	411	424	432
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	130	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1040	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	60	60	60	60
FORK RAKE	45	45	45	45
AXLE TO CROWN	385	385	385	385
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Triple butted 6061 frame with smooth welding. Integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>CRANKSET</b>	SUV-500 alloy 48 x 34T L: S/M=170mm, L/XL=175mm	<b>BRAKES</b>	Promax Decipher hydraulic disc brakes with 160mm rotors
<b>FORK</b>	700c disc specific, full alloy commuter fork with and rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	XM25 disc specific double wall rims, 32 hole F/V, alloy quick release disc hubs with stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	CST Sensamo 700 x 40c 60tpi, puncture protection belt and reflective side walls
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 600mm, sweep: 6°	<b>F. DERAILLEUR</b>	SRAM X-5 10 speed low clamp for 31.8, for 48T	<b>SADDLE</b>	Factor Ergotech dual density saddle
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	SRAM X-5 10 speed mid cage	<b>SEATPOST / CLAMP</b>	Alloy twin bolt micro adjust 27.2mm
<b>HEADSTEM</b>	3D forged 4 bolt alloy stem, 31.8mm, L: S=80mm, M=90mm, L=100mm, XL=110mm	<b>SHIFT LEVERS</b>	SRAM X-5 20 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	SRAM 10 speed cassette 11-32T		
		<b>CHAIN</b>	KMC X-10		

MTB

ROAD

LIFESTYLE

YOUTH



### KEY FEATURES

700c Alloy Frame, with Apollo's performance geometry, perfect for commuting.

Alloy integrated fork with steel steer tube.

Alloy hubs, with Weinmann double wall rims.

700c x 40c slick tyres with reflective sidewall.

24 speed Shimano rapid-fire shifting with cassette.

Powerful Promax Dechiper Hydraulic disc brakes, with 160mm rotors.

Apollo custom comfort grip and oversized handlebar and stem.

### CODES

	S	M	L	XL
Matte Charcoal / Matte Silver / Matte Orange	16144	16145	16146	16147

### GEOMETRY

	S	M	L	XL
STACK	530	555	576	595
REACH	393	411	424	432
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	130	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1040	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	60	60	60	60
FORK RAKE	45	45	45	45
AXLE TO CROWN	385	385	385	385
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Triple butted 6061 frame with smooth welding. Integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>CRANKSET</b>	Suntour XCE 48 x 38 x 28T L: S/M=170mm, L/XL=175mm	<b>WHEELS</b>	Weinmann XM25 double wall disc specific rims, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>FORK</b>	Alloy 700c disc specific commuter fork with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>TYRES</b>	CST Sensamo 700 x 40c 30tpi, puncture protection belt and reflective side walls
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	Low profile high impact resin	<b>SADDLE</b>	Factor Ergotech dual density saddle
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 600mm, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano M191 8 speed for 31.8	<b>SEATPOST / CLAMP</b>	Alloy twin bolt micro adjust 27.2mm
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	Shimano Alivio 8 speed	<b>EXTRAS</b>	N/A
<b>HEADSTEM</b>	4 bolt alloy stem, 31.8mm, S=90mm, M/L/XL=105mm	<b>SHIFT LEVERS</b>	Shimano Altus 24 speed Rapid Fire		
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		
		<b>CHAIN</b>	KMC Z-7		
		<b>BRAKES</b>	Promax Decipher hydraulic disc brakes with reach adjust, 160mm rotors		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c Alloy Frame, with Apollo's performance Women specific geometry, perfect for commuting.

Alloy integrated fork with steel steer tube.

Alloy hubs, with Weinmann double wall rims.

700c x 40c slick tyres with reflective sidewall.

24 speed Shimano rapid-fire shifting with cassette.

Women specific Saddle for maximum riding comfort.

Powerful Promax Decipher Hydraulic disc brakes, with 160mm rotors.

Apollo custom comfort grip and oversized handlebar and stem.

### CODES

	XS	S	M
Gloss Slate / Gloss Blue / Gloss Chrome	16148	16149	16150

### GEOMETRY

	XS	S	M
STACK	535	554	563
REACH	382	391	403
EFFECTIVE TOP TUBE	540	555	570
SEAT TUBE (CENTRE TO TOP)	400	430	460
SEAT ANGLE	73.5°	73.5°	73.5°
HEAD TUBE LENGTH	130	150	160
HEAD ANGLE	71.0°	71.0°	71.0°
WHEEL BASE	1027	1043	1060
CHAIN STAY LENGTH	440	440	440
BB DROP	65	65	65
FORK RAKE	45	45	45
AXLE TO CROWN	385	385	385
REAR DROPOUT SPACING	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	Triple butted 6061 women's specific frame with smooth welding. Integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>CRANKSET</b>	Suntour XCE 48 x 38 x 28T L: XS/S/ M=170mm	<b>WHEELS</b>	Weinmann XM25 double wall disc specific rims, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>FORK</b>	Alloy 700c disc specific commuter fork with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>TYRES</b>	CST Sensamo 700 x 40c 30tpi, puncture protection belt and reflective side walls
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	Low profile high impact resin	<b>SADDLE</b>	Factor women's specific Ergotech dual density saddle
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 580mm, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano M191 8 speed for 31.8	<b>SEATPOST / CLAMP</b>	Alloy twin bolt micro adjust 27.2mm
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	Shimano Alivio 8 speed	<b>EXTRAS</b>	N/A
<b>HEADSTEM</b>	4 bolt alloy stem, 31.8mm, XS/S= 75mm, M=90mm	<b>SHIFT LEVERS</b>	Shimano Altus 24 speed Rapid Fire		
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		
		<b>CHAIN</b>	KMC Z-7		
		<b>BRAKES</b>	Promax Decipher hydraulic disc brakes with reach adjust, 160mm rotors		

MTB

ROAD

LIFESTYLE

YOUTH



### KEY FEATURES

700c Alloy Frame, with Apollo's performance geometry, perfect for commuting.

High Visibility painting and decals, with reflective decals on the rear stay and fork blades.

Hi-ten integrated steel fork.

Alloy hubs, with Weinmann double wall rims.

700c x 40c slick tyres with reflective sidewall.

24 speed Shimano EZ-fire shifting.

Powerful Hayes MX-Comp mechanical disc brakes, with 160mm rotors.

Apollo custom comfort grip.

### CODES

	S	M	L	XL
Gloss Blue / Gloss Red / Reflective	16151	16152	16153	16154

### GEOMETRY

	S	M	L	XL
STACK	530	555	576	595
REACH	393	411	424	432
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	130	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1040	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	60	60	60	60
FORK RAKE	45	45	45	45
AXLE TO CROWN	385	385	385	385
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy frame with integrated head tube, pannier mounts and replaceable derailleur hanger. HI VIZ reflective decals	<b>CRANKSET</b>	Suntour XCE 48 x 38 x 28T L: S/M=170mm, L/XL=175mm	<b>WHEELS</b>	Weinmann XM25 double wall disc specific rims with HI VIZ reflective decals, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>FORK</b>	700c disc specific hi-ten rigid integrated trekking fork with rack and fender mounts. HI VIZ reflective decals	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>TYRES</b>	CST Sensamo 700 x 40c 30tpi, puncture protection belt and reflective side walls
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	Low profile high impact resin	<b>SADDLE</b>	Factor Ergotech dual density saddle
<b>HANDLEBAR</b>	Alloy low riser, bore: 25.4mm, W: 600mm, sweep: 6°	<b>F. DERAILEUR</b>	Shimano MI91 8 speed for 31.8	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILEUR</b>	Shimano Acera 8 speed	<b>EXTRAS</b>	N/A
<b>HEADSTEM</b>	4 bolt alloy stem, 25.4mm, S=70mm, M/L=90mm, XL=105mm	<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed		
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		
		<b>CHAIN</b>	KMC Z-7		
		<b>BRAKES</b>	Hayes MX comp mechanical disc brakes with 160mm rotors		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c Alloy Frame, with Apollo's performance Women specific geometry, perfect for commuting.

High Visibility painting and decals, with reflective decals on the rear stay and fork blades.

Hi-ten integrated steel fork.

Alloy hubs, with Weinmann double wall rims.

700c x 40c slick tyres with reflective sidewall.

24 speed Shimano EZ-fire shifting.

Women specific Saddle for maximum riding comfort.

Powerful Hayes MX-Comp mechanical disc brakes, with 160mm rotors.

Apollo custom comfort grip.

### CODES

	XS	S	M
Gloss Purple / Gloss Blue / Reflective	16155	16156	16157

### GEOMETRY

	XS	S	M
STACK	535	554	563
REACH	382	391	403
EFFECTIVE TOP TUBE	540	555	570
SEAT TUBE (CENTRE TO TOP)	400	430	460
SEAT ANGLE	73.5°	73.5°	73.5°
HEAD TUBE LENGTH	130	150	160
HEAD ANGLE	71.0°	71.0°	71.0°
WHEEL BASE	1027	1043	1060
CHAIN STAY LENGTH	440	440	440
BB DROP	65	65	65
FORK RAKE	45	45	45
AXLE TO CROWN	385	385	385
REAR DROPOUT SPACING	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy women's specific frame with integrated head tube, pannier mounts and replaceable derailleur hanger. HI VIZ reflective decals	<b>CRANKSET</b>	Suntour XCE 48 x 38 x 28T L: XS/S/M=170mm	<b>WHEELS</b>	Weinmann XM25 double wall disc specific rims with HI VIZ reflective decals, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>FORK</b>	700c disc specific hi-ten rigid integrated trekking fork with rack and fender mounts. HI VIZ reflective decals	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>TYRES</b>	CST Sensamo 700 x 40c 30tpi, puncture protection belt and reflective side walls
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	Low profile high impact resin	<b>SADDLE</b>	Factor Ergotech dual density saddle
<b>HANDLEBAR</b>	Alloy low riser, bore: 25.4mm, W: 580mm, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano M191 8 speed for 31.8	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>EXTRAS</b>	N/A
<b>HEADSTEM</b>	4 bolt alloy stem, 25.4mm, XS/S=70mm, M=90mm	<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed		
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		
		<b>CHAIN</b>	KMC Z-7		
		<b>BRAKES</b>	Hayes MX comp mechanical disc brakes with 160mm rotors		



### KEY FEATURES

700c alloy frame, with Apollo's performance geometry, perfect for commuting.

Hi-ten integrated steel fork.

Alloy hubs, with Weinmann double wall rims.

700c x 38c slick tyres.

24 speed Shimano EZ-fire shifting.

Oversized 31.8mm handlebar and stem.

Powerful mechanical disc brakes, with 160mm rotors.

Apollo custom comfort grip.

### CODES

	S	M	L	XL
Matte Charcoal / Matte Black / Matte Red	17040	17041	17042	17043

### GEOMETRY

	S	M	L	XL
STACK	559	585	606	625
REACH	384	402	415	423
STAND OVER HEIGHT	392	431	465	498
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	130	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1040	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	60	60	60	60
FORK RAKE	45	45	45	45
AXLE TO CROWN	416	416	416	416
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy frame with integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>HEADSTEM</b>	Alloy, 31.8mm, S=70mm, M/L=90mm, XL=105mm	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	700c disc specific hi-ten rigid integrated trekking fork with rack and fender mounts	<b>CRANKSET</b>	Suntour XCE 48 x 38 x 28T L: S/M=170mm, L/XL=175mm	<b>BRAKES</b>	TEKTRO MD-280 mechanical disc brakes with 160mm rotors
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Weinmann U-26 double wall disc specific rims, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 600mm, sweep: 6°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Urban sport 700 x 38c wire bead
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano M191 8 speed for 31.8	<b>SADDLE</b>	Factor Ergotech dual density saddle
		<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		





### KEY FEATURES

700c alloy frame, with Apollo's performance Women's specific geometry, perfect for commuting.

Hi-ten integrated steel fork.

Alloy hubs, with Weinmann double wall rims.

700c x 38c slick tyres.

24 speed Shimano EZ-fire shifting.

Oversized 31.8mm handlebar and stem.

Women's specific saddle for maximum riding comfort.

Powerful mechanical disc brakes, with 160mm rotors.

Apollo custom comfort grip.

### CODES

	XS	S	M
Matte Pearl Black / Matte Charcoal / Matte Pink	17044	17045	17046

### GEOMETRY

	XS	S	M
STACK	564	583	593
REACH	373	382	394
STAND OVER HEIGHT	371	395	413
EFFECTIVE TOP TUBE	540	555	570
SEAT TUBE (CENTRE TO TOP)	400	430	460
SEAT ANGLE	73.5°	73.5°	73.5°
HEAD TUBE LENGTH	130	150	160
HEAD ANGLE	71.0°	71.0°	71.0°
WHEEL BASE	1027	1043	1060
CHAIN STAY LENGTH	440	440	440
BB DROP	65	65	65
FORK RAKE	45	45	45
AXLE TO CROWN	416	416	416
REAR DROPOUT SPACING	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy women's specific frame with integrated head tube, pannier mounts and replaceable derailleur hanger.	<b>CRANKSET</b>	Suntour XCE 48 x 38 x 28T L: XS/S/M=170mm	<b>BRAKES</b>	TEKTRO MD-280 mechanical disc brakes with 160mm rotors
<b>FORK</b>	700c disc specific hi-ten rigid integrated trekking fork with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Weinmann U-26 double wall disc specific rims, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Urban sport 700 x 38c wire bead
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W:580mm, sweep 6°	<b>F. DERAILLEUR</b>	Shimano M191 8 speed for 31.8	<b>SADDLE</b>	Factor women's specific Ergotech dual density saddle
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>HEADSTEM</b>	Alloy, 31.8mm, XS/S= 70mm, M=90mm	<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		
		<b>CHAIN</b>	KMC Z-7		



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

700c alloy frame, with Apollo's performance geometry, perfect for commuting.

Hi-ten steel fork.

Alloy hubs, with Weinmann double wall rims.

700c x 38c slick tyres.

21 speed Shimano EZ-fire shifting.

Oversized 31.8mm handlebar and stem.

Selle Royal saddle for maximum riding comfort.

Powerful Promax V-Brakes.

Apollo custom comfort grip.

## CODES

	S	M	L	XL
Matte Black / Matte Green / Matte Charcoal	17047	17048	17049	17050
Gloss White / Gloss Black / Gloss Blue	17051	17052	17053	17054

## GEOMETRY

	S	M	L	XL
STACK	559	585	606	625
REACH	384	402	415	423
STAND OVER HEIGHT	392	431	465	498
EFFECTIVE TOP TUBE	550	575	600	620
SEAT TUBE (CENTRE TO TOP)	400	457	508	560
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	130	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1040	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	60	60	60	60
FORK RAKE	45	45	45	45
AXLE TO CROWN	416	416	416	416
REAR DROPOUT SPACING	135	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy frame, pannier mounts and replaceable derailleur hanger.	<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L: S/M/L/ XL=170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>FORK</b>	700c hi-ten rigid integrated trekking fork with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Weinmann X-MI double wall alloy rims. 32 hole A/V, alloy quick release hubs with double seal system. Stainless spokes
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	High impact nylon	<b>TYRES</b>	Urban sport 700 x 38c wire bead
<b>HANDLEBAR</b>	Low riser, bore: 31.8mm, W:600mm, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano TX-800 top pull for 31.8mm	<b>SADDLE</b>	Factor Ergotech saddle
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	Shimano TY-300 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>HEADSTEM</b>	Alloy, 31.8mm, S=70mm, M/L=90mm, XL=105mm	<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel		
		<b>CHAIN</b>	KMC Z-51		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c alloy frame, with Apollo's performance Women's specific geometry, perfect for commuting.

Hi-ten steel fork.

Alloy hubs, with Weinmann double wall rims.

700c x 38c slick tyres.

21 speed Shimano EZ-fire shifting.

Oversized 31.8mm handlebar and stem.

Women's specific saddle for maximum riding comfort.

Powerful Promax V-Brakes.

Apollo custom comfort grip.

### CODES

	XS	S	M
Gloss Pearl White / Gloss Turquoise / Gloss Silver	17055	17056	17057
Matte Charcoal / Matte Lavender / Matte Silver	17058	17059	17060

### GEOMETRY

	XS	S	M
STACK	564	583	593
REACH	373	382	394
STAND OVER HEIGHT	371	395	413
EFFECTIVE TOP TUBE	540	555	570
SEAT TUBE (CENTRE TO TOP)	400	430	460
SEAT ANGLE	73.5°	73.5°	73.5°
HEAD TUBE LENGTH	130	150	160
HEAD ANGLE	71.0°	71.0°	71.0°
WHEEL BASE	1027	1043	1060
CHAIN STAY LENGTH	440	440	440
BB DROP	65	65	65
FORK RAKE	45	45	45
AXLE TO CROWN	416	416	416
REAR DROPOUT SPACING	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy women's specific frame, pannier mounts and replaceable derailleur hanger.	<b>HEADSTEM</b>	Alloy, 31.8mm, XS/S= 70mm, M=90mm	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	700c hi-ten rigid integrated trekking fork with rack and fender mounts	<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L: XS/S/M= 170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Weinmann X-M1 double wall alloy rims. 32 hole A/V, alloy quick release hubs with double seal system. Stainless spokes
<b>HANDLEBAR</b>	Low riser, bore: 31.8mm, W: 580mm, sweep: 6°	<b>PEDALS</b>	High impact nylon	<b>TYRES</b>	Urban sport 700 x 38c wire bead
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano TX-800 top pull for 31.8mm	<b>SADDLE</b>	Factor women's specific Ergotech saddle
		<b>R. DERAILLEUR</b>	Shimano TY-300 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel		

# EXCEED

## URBAN SPEED

A weekday commuter that is more relaxed and comfortable than a flat bar road bike, with increased stopping power, and a rigid fork with slick, wider tyres. Exceptional versatility to tackle any weekend getaway.

### **RIGID FORK**

Light and responsive handling.

### **FAST TYRES**

700 x 28/32 tyres for speed and agility on city roads.

### **DOUBLE WALL RIMS**

Greater strength for urban environments.

### **CARRIER & FENDER MOUNTS**

Easily customisable to suit your riding needs.

### **BUILT FOR SPEED**

Combining road bike geometry with a comfortable, easy-to-ride flat bar.



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c butted alloy flat bar road frame with comfort road geometry.

Carbon fork with alloy steerer tube.

Alloy hubs, with Weinmann double wall rims.

SRAM Via Centro 2 x 10 shifting with cassette

Powerful Promax mini V-Brakes.

Apollo custom comfort grip.

### CODES

	S	M	L	XL
Matte Black / Gloss White	16095	16096	16097	16098

### GEOMETRY

	S	M	L	XL
STACK	555	576	595	616
REACH	396	409	418	427
EFFECTIVE TOP TUBE	555	580	600	615
SEAT TUBE (CENTRE TO TOP)	450	500	530	560
SEAT ANGLE	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	130	150	170	190
HEAD ANGLE	72.0°	72.5°	72.5°	73.0°
WHEEL BASE	1025	1040	1055	1075
CHAIN STAY LENGTH	430	430	430	430
BB DROP	70	70	70	70
FORK RAKE	45	45	45	45
AXLE TO CROWN	397	397	397	397
REAR DROPOUT SPACING	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Superlite butted 6061 smooth welded aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger	<b>HEADSTEM</b>	Factor 4 bolt 3D forged alloy stem, bore: 31.8mm, L: S=90mm, M/L=100mm, XL=110mm	<b>CASSETTE</b>	SRAM 10 speed cassette 11 - 28T
<b>FORK</b>	Carbon 12k weave composite fork with straight blades, alloy steerer/crown 1-1/8" integrated with rack and fender mounts	<b>CRANKSET</b>	SRAM Via Centro 48 x 32T L: S/M=170mm, L/XL=175mm	<b>CHAIN</b>	KMC X-10
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	SRAM power spline bottom bracket	<b>BRAKES</b>	Mini alloy linear pull calipers
<b>HANDLEBAR</b>	Alloy double butted flat bar, bore: 31.8mm, W: 620mm, sweep: 5°	<b>PEDALS</b>	Low profile high impact resin	<b>WHEELS</b>	Custom Weinmann X Star 18 32 hole double wall F/V rims, alloy hubs and stainless spokes.
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	SRAM Via Centro high clamp 2 x 10	<b>TYRES</b>	Hutchinson Nitro 2 700 x 28c 27tpi wire bead
		<b>R. DERAILLEUR</b>	SRAM Apex mid cage 10 speed	<b>SADDLE</b>	Factor road saddle
		<b>SHIFT LEVERS</b>	SRAM Via Centro 20 speed flat bar shifters	<b>SEATPOST / CLAMP</b>	Factor alloy 27.2mm twin bolt micro adjust
				<b>EXTRAS</b>	N/A



### KEY FEATURES

700c butted alloy flat bar road frame with comfort road geometry.

Carbon fork with alloy steer tube.

Alloy hubs, with Weinmann double wall rims.

Shimano Nexus Inner-8 geared hub

Powerful Promax mini V-Brakes.

Apollo custom comfort grip.

Alloy colour match mud guards with stainless struts

Alloy rear carrier.

### CODES

CODES	S	M	L	XL
Matte Charcoal / Matte Red / Matte Black	16099	16100	16101	16102

### GEOMETRY

GEOMETRY	S	M	L	XL
STACK	555	576	595	616
REACH	396	414	423	437
EFFECTIVE TOP TUBE	555	585	605	625
SEAT TUBE (CENTRE TO TOP)	450	500	530	560
SEAT ANGLE	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	130	150	170	190
HEAD ANGLE	72.0°	72.5°	72.5°	73.0°
WHEEL BASE	1030	1050	1065	1080
CHAIN STAY LENGTH	430	430	430	430
BB DROP	70	70	70	70
FORK RAKE	45	45	45	45
AXLE TO CROWN	397	397	397	397
REAR DROPOUT SPACING	132	132	132	132

### SPECIFICATIONS

<b>FRAME</b>	Superlite butted 6061 smooth welded aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger	<b>HEADSTEM</b>	Alloy 4 bolt stem, bore: 25.4mm L: S=70mm, M/L=90mm, XL=105mm	<b>CHAIN</b>	KMC Z-610
<b>FORK</b>	Carbon 12k weave composite fork with straight blades, alloy steerer/crown 1-1/8" integrated with rack and fender mounts	<b>CRANKSET</b>	Cold forged 44T high polish classic series crank with double chain cover L: 170mm	<b>BRAKES</b>	Mini alloy linear pull calipers
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Custom Weinmann X Star 18 double wall rims with machined side walls, 32 hole F/V, Shimano Nexus internal rear hub, alloy front hub and stainless spokes.
<b>HANDLEBAR</b>	Alloy flat bar, bore: 25.4mm, W: 600mm, sweep: 5°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Hutchinson Nitro 2 700 x 28c 27tpi wire bead
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Factor contoured saddle
		<b>R. DERAILLEUR</b>	N/A	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano Nexus shift 8 speed	<b>EXTRAS</b>	Full length front and rear mudguards with alloy rear carrier
		<b>CASSETTE</b>	Shimano 20T freewheel		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c butted alloy flat bar road frame with comfort road geometry.

High Visibility painting and decals, with reflective decals on the rear stay and fork blades.

Carbon fork with alloy steer tube.

Upgraded Alloy hubs, with Weinmann double wall rims.

24 speed Shimano EZ-fire shifting with cassette

Powerful Promax mini V-Brakes.

Apollo custom comfort grip.

### CODES

	S	M	L	XL
Gloss Green / Gloss Black / Reflective	16103	16104	16105	16106

### GEOMETRY

	S	M	L	XL
STACK	555	576	595	616
REACH	396	414	423	437
EFFECTIVE TOP TUBE	555	585	605	625
SEAT TUBE (CENTRE TO TOP)	450	500	530	560
SEAT ANGLE	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	130	150	170	190
HEAD ANGLE	72.0°	72.5°	72.5°	73.0°
WHEEL BASE	1030	1050	1065	1075
CHAIN STAY LENGTH	430	430	430	430
BB DROP	70	70	70	70
FORK RAKE	45	45	45	45
AXLE TO CROWN	397	397	397	397
REAR DROPOUT SPACING	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Superlite butted 6061 aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger HI VIZ reflective decals	<b>HEADSTEM</b>	Alloy 4 bolt stem, bore: 25.4mm L: S=70mm, M/L=90mm, XL=105mm	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	Carbon 12k weave composite fork with straight blades, alloy steerer/crown 1-1/8" integrated with rack and fender mounts, Hi Viz reflective decals	<b>CRANKSET</b>	Suntour XCE 48x 38 x 28T L: S/M=170mm, L/XL=175mm	<b>BRAKES</b>	Forged alloy mini linear pull calipers
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Custom Weinmann X Star 18 rims with reflective decals, 32 hole double wall F/V rims, alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Alloy flat bar, bore: 25.4mm, W: 600mm, sweep: 5°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	700 x 32c 30tpi wire bead with puncture protection and reflective belt
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano M-191 8 speed top swing for 31.8	<b>SADDLE</b>	Factor contoured saddle
		<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		

MTB

ROAD



### KEY FEATURES

700c butted alloy flat bar road frame with comfort road geometry.

Lightweight Carbon fork with alloy steer tube.

Lightweight wheels with alloy hubs, with Weinmann double wall rims.

24 speed Shimano EZ-fire shifting with cassette

Powerful Promax mini V-Brakes.

Apollo custom comfort grip.

### CODES

	S	M	L	XL
Matte Black / Matte Silver / Matte Green	17019	17020	17021	17022

### GEOMETRY

	S	M	L	XL
STACK	553	574	593	614
REACH	397	415	424	437
STAND OVER HEIGHT	406	439	462	486
EFFECTIVE TOP TUBE	555	585	605	625
SEAT TUBE (CENTRE TO TOP)	450	500	530	560
SEAT ANGLE	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	130	150	170	190
HEAD ANGLE	72.0°	72.5°	72.5°	73.0°
WHEEL BASE	1030	1050	1065	1075
CHAIN STAY LENGTH	430	430	430	430
BB DROP	70	70	70	70
FORK RAKE	50	50	50	50
AXLE TO CROWN	397	397	397	397
REAR DROPOUT SPACING	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Superlite butted 6061 aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger	<b>HEADSTEM</b>	Alloy 4 bolt stem, bore: 31.8mm L: S=75mm, M/L=90mm, XL=105mm	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	Carbon 12k weave composite fork with straight blades, alloy steerer/crown 1-1/8" integrated with rack and fender mounts	<b>CRANKSET</b>	Suntour XCE 48x 38 x 28T L: S/M=170mm, L/XL=175mm	<b>BRAKES</b>	Mini alloy linear pull calipers
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Custom Weinmann X-M1 32 hole double wall A/V rims, alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Alloy flat bar, bore: 31.8mm, W: 600mm, sweep: 5°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	700 x 28c wire bead
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano M-191 8 speed top swing for 31.8	<b>SADDLE</b>	Factor contoured saddle
		<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		

LIFESTYLE

YOUTH





MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c butted alloy flat bar road frame with comfort road geometry.

Lightweight Carbon fork with alloy steer tube.

Lightweight wheels with alloy hubs, with Weinmann double wall rims.

24 speed Shimano EZ-fire shifting with cassette

Powerful Promax mini V-Brakes.

Apollo custom comfort grip.

### CODES

	S	M	L	XL
Gloss White / Gloss Slate / Gloss Blue	16107	16108	16109	16110

### GEOMETRY

	S	M	L	XL
STACK	555	576	595	616
REACH	396	414	423	437
EFFECTIVE TOP TUBE	555	585	605	625
SEAT TUBE (CENTRE TO TOP)	450	500	530	560
SEAT ANGLE	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	130	150	170	190
HEAD ANGLE	72.0°	72.5°	72.5°	73.0°
WHEEL BASE	1030	1050	1065	1075
CHAIN STAY LENGTH	430	430	430	430
BB DROP	70	70	70	70
FORK RAKE	45	45	45	45
AXLE TO CROWN	397	397	397	397
REAR DROPOUT SPACING	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Superlite butted 6061 aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger	<b>HEADSTEM</b>	Alloy 4 bolt stem, bore: 25.4mm L: S=70mm, M/L=90mm, XL=105mm	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	Carbon 12k weave composite fork with straight blades, alloy steerer/crown 1-1/8" integrated with rack and fender mounts	<b>CRANKSET</b>	Suntour XCE 48x 38 x 28T L: S/M=170mm, L/XL=175mm	<b>BRAKES</b>	Mini alloy linear pull calipers
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Custom Weinmann X Star 18 32 hole double wall F/V rims, alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Alloy flat bar, bore: 25.4mm, W: 600mm, sweep: 5°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	700 x 28c wire bead
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano M-191 8 speed top swing for 31.8	<b>SADDLE</b>	Factor contoured saddle
		<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		

MTB

ROAD



### KEY FEATURES

700c Women's specific butted alloy flat bar road frame with comfort road geometry.

Lightweight carbon fork with alloy steer tube.

Lightweight wheels with alloy hubs, with Weinmann double wall rims.

24 speed Shimano EZ-fire shifting with cassette

Powerful Promax mini V-Brakes.

Women's specific saddle for maximum riding comfort.

Apollo custom comfort grip.

### CODES

	XS	S	M
Matte Black / Matte Silver / Matte Pink	17023	17024	17025

### GEOMETRY

	XS	S	M
STACK	549	560	570
REACH	388	394	401
STAND OVER HEIGHT	361	385	407
EFFECTIVE TOP TUBE	545	555	575
SEAT TUBE (CENTRE TO TOP)	400	440	480
SEAT ANGLE	74.0°	74.0°	73.0°
HEAD TUBE LENGTH	130	140	150
HEAD ANGLE	71.0°	71.5°	71.5°
WHEEL BASE	1030	1035	1042
CHAIN STAY LENGTH	430	430	430
BB DROP	70	70	70
FORK RAKE	50	50	50
AXLE TO CROWN	397	397	397
REAR DROPOUT SPACING	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Superlite butted 6061 aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger	<b>HEADSTEM</b>	Alloy 4 bolt forged stem, bore: 31.8mm L: XS=75mm, S/M=90mm	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	Carbon 12k weave composite fork with straight blades, alloy steerer/crown 1-1/8" integrated with rack and fender mounts	<b>CRANKSET</b>	Suntour XCE 48x 38 x 28T L: XS/S/M=170mm	<b>BRAKES</b>	Mini alloy linear pull calipers
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Custom Weinmann X-M1 32 hole double wall A/V rims, alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Alloy flat bar, bore: 31.8mm, W: 580mm, sweep: 5°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	700 x 28c wire bead
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano M-191 8 speed top swing for 31.8	<b>SADDLE</b>	Factor women's specific Comfortech with cutout
		<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		

LIFESTYLE

YOUTH



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c Women's specific butted alloy flat bar road frame with comfort road geometry.

Lightweight carbon fork with alloy steer tube.

Lightweight wheels with alloy hubs, with Weinmann double wall rims.

24 speed Shimano EZ-fire shifting with cassette

Powerful Promax mini V-Brakes.

Women's specific saddle for maximum riding comfort.

Apollo custom comfort grip.

### CODES

	XS	S	M
Gloss Slate / Gloss Silver / Gloss Chrome	16111	16112	16113

### GEOMETRY

	XS	S	M
STACK	551	563	572
REACH	387	394	400
EFFECTIVE TOP TUBE	545	555	575
SEAT TUBE (CENTRE TO TOP)	400	440	480
SEAT ANGLE	74.0°	74.0°	73.0°
HEAD TUBE LENGTH	130	140	150
HEAD ANGLE	71.0°	71.5°	71.5°
WHEEL BASE	1030	1035	1042
CHAIN STAY LENGTH	430	430	430
BB DROP	70	70	70
FORK RAKE	45	45	45
AXLE TO CROWN	397	397	397
REAR DROPOUT SPACING	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Superlite butted 6061 aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger	<b>HEADSTEM</b>	Alloy 4 bolt forged stem, bore: 25.4mm L: XS=70mm, S/M=90mm	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	Carbon 12k weave composite fork with straight blades, alloy steerer/crown 1-1/8" integrated with rack and fender mounts	<b>CRANKSET</b>	Suntour XCE 48x 38 x 28T L: XS/S/M=170mm	<b>BRAKES</b>	Mini alloy linear pull calipers
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Custom Weinmann X Star 18 32 hole double wall F/V rims, alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Alloy flat bar, bore: 25.4mm, W: 580mm, sweep: 5°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	700 x 28c wire bead
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano M-191 8 speed top swing for 31.8	<b>SADDLE</b>	Factor women's specific Comfortech with cutout
		<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		



### KEY FEATURES

700c Alloy Flat bar Road frame with comfort road geometry.

Lightweight Alloy fork with alloy steer tube.

Lightweight wheels with alloy hubs, with Weinmann double wall rims.

21 speed Shimano EZ-fire shifting with cassette

Selle Royal saddle for maximum riding comfort.

Powerful Promax mini V-Brakes.

Apollo custom comfort grip.

### CODES

	S	M	L	XL
Matte Charcoal / Matte Black / Matte Red	17026	17027	17028	17029

### GEOMETRY

	S	M	L	XL
STACK	568	589	608	629
REACH	392	410	419	433
STAND OVER HEIGHT	415	448	470	495
EFFECTIVE TOP TUBE	555	585	605	625
SEAT TUBE (CENTRE TO TOP)	450	500	530	560
SEAT ANGLE	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	130	150	170	190
HEAD ANGLE	72.0°	72.5°	72.5°	73.0°
WHEEL BASE	1030	1050	1065	1075
CHAIN STAY LENGTH	430	430	430	430
BB DROP	70	70	70	70
FORK RAKE	40	40	40	40
AXLE TO CROWN	409	409	409	409
REAR DROPOUT SPACING	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Butted 6061 aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger
<b>FORK</b>	Full alloy ovalised straight blades with rack mounts
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer
<b>HANDLEBAR</b>	Alloy flat bar, bore: 31.8mm, W: 580mm, sweep: 5°
<b>GRIP</b>	Kraton ERGO comfort grip

<b>HEADSTEM</b>	Alloy 4 bolt stem, bore: 31.8mm L: S=75mm, M/L=90mm, XL=105mm
<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L: S/M/L/XL=170mm
<b>BOTTOM BRACKET</b>	Cartridge bottom bracket
<b>PEDALS</b>	High impact resin
<b>F. DERAILLEUR</b>	Shimano TX-800 top pull for 31.8mm
<b>R. DERAILLEUR</b>	Shimano TY-300 7 speed
<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed
<b>CASSETTE</b>	Shimano 7 speed cassette 12-28T

<b>CHAIN</b>	KMC Z-51
<b>BRAKES</b>	Mini alloy linear pull calipers
<b>WHEELS</b>	700c Custom Weinmann X-M1 32 hole double wall A/V rims, alloy hubs and stainless spokes.
<b>TYRES</b>	700 x 28c wire bead
<b>SADDLE</b>	Factor Ergotech saddle
<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>EXTRAS</b>	N/A



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c Alloy Flat bar Road frame with comfort road geometry.

Lightweight Alloy fork with alloy steer tube.

Lightweight wheels with alloy hubs, with Weinmann double wall rims.

21 speed Shimano EZ-fire shifting with cassette

Selle Royal saddle for maximum riding comfort.

Powerful Promax mini V-Brakes.

Apollo custom comfort grip.

### CODES

	S	M	L	XL
Matte Black / Matte Green	16114	16115	16116	16117
Gloss Red / Gloss White / Gloss Black	16118	16119	16120	16121

### GEOMETRY

	S	M	L	XL
STACK	555	576	595	616
REACH	396	414	423	437
STAND OVER HEIGHT	555	585	605	625
EFFECTIVE TOP TUBE	450	500	530	560
SEAT TUBE (CENTRE TO TOP)	74.0°	73.5°	73.0°	73.0°
SEAT ANGLE	130	150	170	190
HEAD TUBE LENGTH	72.0°	72.5°	72.5°	73.0°
HEAD ANGLE	1030	1050	1065	1075
WHEEL BASE	430	430	430	430
CHAIN STAY LENGTH	70	70	70	70
BB DROP	45	45	45	45
FORK RAKE	397	397	397	397
AXLE TO CROWN	130	130	130	130
REAR DROPOUT SPACING	130	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Butted 6061 aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger	<b>HEADSTEM</b>	Alloy 4 bolt stem, bore: 25.4mm L: S=70mm, M/L=90mm, XL=105mm	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	Full alloy ovalised straight blades with rack mounts	<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L: S/M/L/XL=170mm	<b>BRAKES</b>	Mini alloy linear pull calipers
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Custom Weinmann X Star 18 32 hole double wall A/V rims, alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Alloy flat bar, bore: 25.4mm, W: 580mm, sweep: 5°	<b>PEDALS</b>	High impact resin	<b>TYRES</b>	700 x 28c wire bead
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano TX-800 top pull for 31.8mm	<b>SADDLE</b>	Factor Ergotech saddle
		<b>R. DERAILLEUR</b>	Shimano Tourney 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 7 speed cassette 12-28T		

MTB

ROAD



### KEY FEATURES

700c Women's specific butted alloy flat bar road frame with comfort road geometry.

Lightweight Alloy fork with alloy steer tube.

Lightweight wheels with alloy hubs, with Weinmann double wall rims.

21 speed Shimano EZ-fire shifting with cassette

Women's specific saddle for maximum riding comfort.

Powerful Promax mini V-Brakes.

Apollo custom comfort grip.

### CODES

	XS	S	M
Gloss White / Gloss Silver / Gloss Turquoise	17030	17031	17032

### GEOMETRY

	XS	S	M
STACK	565	576	586
REACH	383	390	396
STAND OVER HEIGHT	369	394	415
EFFECTIVE TOP TUBE	545	555	575
SEAT TUBE (CENTRE TO TOP)	400	440	480
SEAT ANGLE	74.0°	74.0°	73.0°
HEAD TUBE LENGTH	130	140	150
HEAD ANGLE	71.0°	71.5°	71.5°
WHEEL BASE	1030	1035	1042
CHAIN STAY LENGTH	430	430	430
BB DROP	70	70	70
FORK RAKE	40	40	40
AXLE TO CROWN	409	409	409
REAR DROPOUT SPACING	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Butted 6061 aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger	<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L: XS/S/M=170mm	<b>BRAKES</b>	Mini alloy linear pull calipers
<b>FORK</b>	Full alloy ovalised straight blades with rack mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Custom Weinmann X-M1 32 hole double wall A/V rims, alloy hubs and stainless spokes.
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>PEDALS</b>	High impact resin	<b>TYRES</b>	700 x 28c wire bead
<b>HANDLEBAR</b>	Flat bar, bore: 31.8mm, W: 580mm, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano TX-800 top pull for 31.8mm	<b>SADDLE</b>	Factor Ergotech saddle
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	Shimano TY-300 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>HEADSTEM</b>	Alloy 4 bolt forged stem, bore: 31.8mm L: XS=75mm, S/M=90mm	<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 7 speed cassette 12-28T		
		<b>CHAIN</b>	KMC Z-51		

LIFESTYLE

YOUTH



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c Women's specific butted alloy flat bar road frame with comfort road geometry.

Lightweight Alloy fork with alloy steer tube.

Lightweight wheels with alloy hubs, with Weinmann double wall rims.

21 speed Shimano EZ-fire shifting with cassette

Women's specific saddle for maximum riding comfort.

Powerful Promax mini V-Brakes.

Apollo custom comfort grip.

### CODES

	XS	S	M
Gloss Chrome / Gloss Navy Blue / Gloss Pink	16122	16123	16124
Matte Charcoal / Silver	16125	16126	16127

### GEOMETRY

	XS	S	M
STACK	551	563	572
REACH	387	394	400
EFFECTIVE TOP TUBE	545	555	575
SEAT TUBE (CENTRE TO TOP)	400	440	480
SEAT ANGLE	74.0°	74.0°	73.0°
HEAD TUBE LENGTH	130	140	150
HEAD ANGLE	71.0°	71.5°	71.5°
WHEEL BASE	1030	1035	1042
CHAIN STAY LENGTH	430	430	430
BB DROP	70	70	70
FORK RAKE	45	45	45
AXLE TO CROWN	397	397	397
REAR DROPOUT SPACING	130	130	130

### SPECIFICATIONS

<b>FRAME</b>	Butted 6061 aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger	<b>HEADSTEM</b>	Alloy 4 bolt forged stem, bore: 25.4mm L: XS=70mm, S/M=90mm	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	Full alloy ovalised straight blades with rack mounts	<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L: XS/S/M=170mm	<b>BRAKES</b>	Mini alloy linear pull calipers
<b>HEADSET</b>	A-head semi integrated 1-1/8" with 10mm cone spacer	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Custom Weinmann X Star 18 32 hole double wall A/V rims, alloy hubs and stainless spokes.
<b>HANDLEBAR</b>	Flat bar, bore: 25.4mm, W: 580mm, sweep: 6°	<b>PEDALS</b>	High impact resin	<b>TYRES</b>	700 x 28c wire bead
<b>GRIP</b>	Kraton ERGO comfort grip	<b>F. DERAILLEUR</b>	Shimano TX-800 top pull for 31.8mm	<b>SADDLE</b>	Factor Ergotech saddle
		<b>R. DERAILLEUR</b>	Shimano Tourney 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 7 speed cassette 12-28T		

MTB

ROAD

LIFESTYLE

YOUTH



### KEY FEATURES

700c Alloy E-Bike frame, special design for Shimano STEPS pedal assist e-bike system.

Performance geometry that has been designed for commuting / city riding.

Shimano Steps power assistant pedalling with downtube mounted battery, which provides power assist up to 25km/h.

RST Neon suspension fork with Mechanical lockout.

700c x 38c semi slick tyres.

Oversized handlebar and a-head stem

8 speed Shimano rapid-fire shifting.

### CODES

Matte Black / Gloss Grey / Gloss Red

### ONE SIZE FITS MOST

16274

### GEOMETRY

### ONE SIZE FITS MOST

STACK	640
REACH	364
STAND OVER HEIGHT	451
EFFECTIVE TOP TUBE	560
SEAT TUBE (CENTRE TO TOP)	440
SEAT ANGLE	73.0°
HEAD TUBE LENGTH	150
HEAD ANGLE	71.0°
WHEEL BASE	1077
CHAIN STAY LENGTH	475
BB DROP	70
FORK RAKE	45
AXLE TO CROWN	470
REAR DROPOUT SPACING	135

## SPECIFICATIONS

<b>FRAME</b>	6061 alloy commuting geometry frame, designed for Shimano STEPS power assist system	<b>CRANKSET</b>	Shimano STEPS, Power Assist E-Bike System	<b>BRAKES</b>	Promax DSK 300 mechanical disc brakes with 160mm rotors
<b>FORK</b>	RST Neon Mechanical Lockout, 60mm Travel	<b>BOTTOM BRACKET</b>	Shimano STEPS, Power Assist E-Bike System	<b>WHEELS</b>	Weinmann XTB 26 double wall rims, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>HEADSET</b>	A-head semi integrated, semi-sealed 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Urban multi terrain, 700 x 38c wire bead
<b>HANDLEBAR</b>	Alloy low riser, bore: 31.8mm, W: 600mm, sweep: 6°	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Factor Ergotech dual density saddle
<b>GRIP</b>	Kraton ERGO comfort grip	<b>R. DERAILLEUR</b>	Shimano Alivio 8 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>HEADSTEM</b>	4 bolt alloy stem, ext=90mm	<b>SHIFT LEVERS</b>	Shimano Altus 8 speed Rapid Fire	<b>EXTRAS</b>	Shimano STEPS Battery mounted on the D/T
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		
		<b>CHAIN</b>	KMC Z-7		





### KEY FEATURES

700c Alloy E-Bike frame, special design for Shimano STEPS pedal assist e-bike system.

Comfort geometry that has been designed with a super low step through design for riders looking easy entry and exit.

Shimano Steps power assistant pedalling with rear rack mounted battery, which provides power assist up to 25km/h.

RST Neon suspension fork with Mechanical lockout.

700c x 38c semi slick tyres.

Adjustable quilled stem for maximum adjustability.

8 speed Shimano rapid-fire shifting.

Oversize saddle for maximised riding comfort.

### CODES

Gloss White / Gloss Silver /  
Gloss Blue

### ONE SIZE FITS MOST

16275

### GEOMETRY

### ONE SIZE FITS MOST

STACK	640
REACH	364
STAND OVER HEIGHT	293
EFFECTIVE TOP TUBE	560
SEAT TUBE (CENTRE TO TOP)	380
SEAT ANGLE	73.0°
HEAD TUBE LENGTH	150
HEAD ANGLE	71.0°
WHEEL BASE	1077
CHAIN STAY LENGTH	475
BB DROP	70
FORK RAKE	45
AXLE TO CROWN	470
REAR DROPOUT SPACING	135

### SPECIFICATIONS

<b>FRAME</b>	6061 alloy low step through "Comfort zone" geometry frame with optimised step through clearance and snake stays, designed for Shimano STEPS power assist system	<b>HEADSTEM</b>	Alloy adjustable quill stem	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	RST Neon Mechanical Lockout, 60mm Travel	<b>CRANKSET</b>	Shimano STEPS, Power Assist E-Bike System	<b>BRAKES</b>	Promax DSK 300 mechanical disc brakes with 160mm rotors
<b>HEADSET</b>	A-head semi integrated, semi-sealed 1-1/8"	<b>BOTTOM BRACKET</b>	Shimano STEPS, Power Assist E-Bike System	<b>WHEELS</b>	Weinmann XTB 26 double wall rims, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>HANDLEBAR</b>	Alloy comfort bars, R: 40mm, W: 600mm, Sweep 10°	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	Urban multi terrain, 700 x 38c wire bead
<b>GRIP</b>	Kraton gel dual density comfort grip	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Factor Comfortech women's specific
		<b>R. DERAILLEUR</b>	Shimano Alivio 8 speed	<b>SEATPOST / CLAMP</b>	Alloy suspension post with new improved elastomer, 27.2mm
		<b>SHIFT LEVERS</b>	Shimano Altus 8 speed Rapid Fire	<b>EXTRAS</b>	Shimano STEPS carry mount battery
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		



### KEY FEATURES

700c Alloy Frame with comfort geometry.

Comfort suspension fork with preload and lockout.

24 speed Shimano EZ-Fire shifting with cassette

Alloy quill adjustable stem for maximum comfort.

Extra large comfort saddle.

Powerful Promax V-Brakes.

Alloy hubs with Weinmann double wall rims for extra strength.

### CODES

Gloss Black / Gloss Blue /  
Gloss Chrome

**S**

16249

**M**

16250

**L**

16251

**XL**

16252

### GEOMETRY

	<b>S</b>	<b>M</b>	<b>L</b>	<b>XL</b>
STACK	615	624	634	648
REACH	368	385	389	404
STAND OVER HEIGHT	417	432	462	497
EFFECTIVE TOP TUBE	580	600	620	640
SEAT TUBE (CENTRE TO TOP)	420	460	500	560
SEAT ANGLE	71.0°	71.0°	70.0°	70.0°
HEAD TUBE LENGTH	140	150	160	170
HEAD ANGLE	69.5°	69.5°	69.5°	70.5°
WHEEL BASE	1073	1093	1100	1109
CHAIN STAY LENGTH	460	460	460	460
BB DROP	70	70	70	70
FORK RAKE	43	43	43	43
AXLE TO CROWN	460	460	460	460
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy "Comfort zone" geometry frame with snake stays
<b>FORK</b>	Apollo Suspension fork with 30mm travel with preload and lockout. Alloy crown and lowers.
<b>HEADSET</b>	Threaded semi-sealed 1-1/8"
<b>HANDLEBAR</b>	Alloy comfort bars, R: 40mm, W: 600mm, Sweep 10°
<b>GRIP</b>	Kraton gel dual density comfort grip

<b>HEADSTEM</b>	Alloy adjustable quill stem
<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L: 170mm
<b>BOTTOM BRACKET</b>	Cartridge bottom bracket
<b>PEDALS</b>	TPR two tone non-slip
<b>F. DERAILLEUR</b>	Shimano TX-51 top pull for 31.8mm
<b>R. DERAILLEUR</b>	Shimano Acera 8 speed
<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed
<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T

<b>CHAIN</b>	KMC Z-7
<b>BRAKES</b>	Alloy linear pull brakes
<b>WHEELS</b>	Weinmann Zac 19 double wall alloy rims. 32 hole A/V, Alloy quick release hubs with double seal system. Stainless spokes
<b>TYRES</b>	700 x 38c wire bead
<b>SADDLE</b>	Factor Comfortech
<b>SEATPOST / CLAMP</b>	Alloy suspension post with new improved elastomer, 27.2mm
<b>EXTRAS</b>	Alloy kickstand



### KEY FEATURES

700c Low step through alloy frame with comfort geometry.

Comfort suspension fork with preload and lockout.

24 speed Shimano EZ-Fire shifting with cassette

Alloy quill adjustable stem for maximum comfort.

Extra large comfort saddle.

Powerful Promax V-Brakes.

Alloy hubs with Weinmann double wall rims for extra strength.

### CODES

	XS	S	M
Gloss Charcoal / Gloss Pink / Gloss White	17118	17119	17120

### GEOMETRY

	XS	S	M
STACK	617	631	648
REACH	347	363	374
STAND OVER HEIGHT	218	227	235
EFFECTIVE TOP TUBE	560	580	610
SEAT TUBE (CENTRE TO TOP)	355	406	457
SEAT ANGLE	71.0°	71.0°	70.0°
HEAD TUBE LENGTH	140	155	170
HEAD ANGLE	69.5°	69.5°	70.0°
WHEEL BASE	1050	1070	1079
CHAIN STAY LENGTH	460	460	460
BB DROP	70	70	70
FORK RAKE	38	38	38
AXLE TO CROWN	460	460	460
REAR DROPOUT SPACING	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy women's step through "Comfort zone" geometry frame with optimised step through clearance and snake stays	<b>HEADSTEM</b>	Alloy adjustable quill stem	<b>CHAIN</b>	KMC Z-7
<b>FORK</b>	Apollo Suspension fork with 30mm travel with preload and lockout. Alloy crown and lowers.	<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L: 170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	Threaded semi-sealed 1-1/8"	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Weinmann X-M1 double wall alloy rims. 32 hole A/V, Alloy quick release front and nutted rear hubs. Stainless spokes
<b>HANDLEBAR</b>	Alloy comfort bars, R: 40mm, W: 600mm, Sweep 10°	<b>PEDALS</b>	TPR two tone non-slip	<b>TYRES</b>	700 x 38c wire bead
<b>GRIP</b>	Kraton gel dual density comfort grip	<b>F. DERAILLEUR</b>	Shimano TX-51 top pull for 31.8mm	<b>SADDLE</b>	Factor Comfortech women's specific
		<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SEATPOST / CLAMP</b>	Alloy suspension post with new improved elastomer, 27.2mm
		<b>SHIFT LEVERS</b>	Shimano EF-51 Ez Fire 24 speed	<b>EXTRAS</b>	Alloy kickstand
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T		

MTB

ROAD

LIFESTYLE

YOUTH



### KEY FEATURES

700c Alloy Frame with comfort geometry.

Comfort suspension fork with preload.

21 speed Shimano EZ-Fire shifting.

Alloy quill adjustable stem for maximum comfort.

Extra large comfort saddle.

Powerful Promax V-Brakes.

Alloy hubs with Weinmann double wall rims for extra strength.

### CODES

	S	M	L	XL
Gloss Silver / Gloss Blue / Gloss Black	16256	16257	16258	16259
Gloss Burgundy / Gloss Red / Gloss Chrome	16260	16261	16262	16263

### GEOMETRY

	S	M	L	XL
STACK	615	624	634	648
REACH	368	385	389	404
STAND OVER HEIGHT	417	432	462	497
EFFECTIVE TOP TUBE	580	600	620	640
SEAT TUBE (CENTRE TO TOP)	420	460	500	560
SEAT ANGLE	71.0°	71.0°	70.0°	70.0°
HEAD TUBE LENGTH	140	150	160	170
HEAD ANGLE	69.5°	69.5°	69.5°	70.5°
WHEEL BASE	1073	1093	1100	1109
CHAIN STAY LENGTH	460	460	460	460
BB DROP	70	70	70	70
FORK RAKE	43	43	43	43
AXLE TO CROWN	460	460	460	460
REAR DROPOUT SPACING	135	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy "Comfort zone" geometry frame with snake stays	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Weinmann Zac 19 double wall alloy rims. 32 hole A/V, Alloy quick release hubs with double seal system. Stainless spokes
<b>FORK</b>	Apollo suspension fork with 30mm travel with preload, alloy crown and legs	<b>PEDALS</b>	Comfort non-slip with rubber insert	<b>TYRES</b>	700 x 38c wire bead
<b>HEADSET</b>	Threaded semi-sealed 1-1/8"	<b>F. DERAILLEUR</b>	Shimano TX-51 top pull for 31.8mm	<b>SADDLE</b>	Factor Comfortech
<b>HANDLEBAR</b>	Alloy comfort bars, R: 40mm, W: 600mm, Sweep 10°	<b>R. DERAILLEUR</b>	Shimano Altus 7 speed	<b>SEATPOST / CLAMP</b>	Alloy suspension post with new improved elastomer, 27.2mm
<b>GRIP</b>	Kraton gel dual density comfort grip	<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed	<b>EXTRAS</b>	Alloy kickstand
<b>HEADSTEM</b>	Alloy adjustable quill stem	<b>CASSETTE</b>	Shimano HG20 7 speed cassette 12-28T		
<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L: 170mm	<b>CHAIN</b>	KMC Z-51		
		<b>BRAKES</b>	Alloy linear pull brakes		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

700c Low step through alloy frame with comfort geometry.

Comfort suspension fork with preload.

21 speed Shimano EZ-Fire shifting.

Alloy quill adjustable stem for maximum comfort.

Extra large comfort saddle.

Powerful Promax V-Brakes.

Alloy hubs with Weinmann double wall rims for extra strength.

### CODES

	XS	S	M
Gloss Pearl White / Gloss Purple	17129	17130	17131
Gloss Slate / Gloss Blue	17132	17133	17134

### GEOMETRY

	XS	S	M
STACK	617	631	648
REACH	347	363	374
STAND OVER HEIGHT	218	227	235
EFFECTIVE TOP TUBE	560	580	610
SEAT TUBE (CENTRE TO TOP)	355	406	457
SEAT ANGLE	71.0°	71.0°	70.0°
HEAD TUBE LENGTH	140	155	170
HEAD ANGLE	69.5°	69.5°	70.0°
WHEEL BASE	1050	1070	1079
CHAIN STAY LENGTH	460	460	460
BB DROP	70	70	70
FORK RAKE	38	38	38
AXLE TO CROWN	460	460	460
REAR DROPOUT SPACING	135	135	135

### SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy women's step through "Comfort zone" geometry frame with optimised step through clearance and snake stays	<b>HEADSTEM</b>	Alloy adjustable quill stem	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	Apollo suspension fork with 30mm travel with preload, alloy crown and legs	<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L: 170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	Threaded semi-sealed 1-1/8"	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Weinmann X-M1 double wall alloy rims. 32 hole A/V, Alloy quick release front and nutted rear hubs. Stainless spokes
<b>HANDLEBAR</b>	Alloy comfort bars, R: 40mm, W: 600mm, Sweep 10°	<b>PEDALS</b>	Comfort non-slip with rubber insert	<b>TYRES</b>	700 x 38c wire bead
<b>GRIP</b>	Kraton gel dual density comfort grip	<b>F. DERAILLEUR</b>	Shimano TX-51 top pull for 31.8mm	<b>SADDLE</b>	Factor Comfortech women's specific
		<b>R. DERAILLEUR</b>	Shimano Altus 7 speed	<b>SEATPOST / CLAMP</b>	Alloy suspension post with new improved elastomer, 27.2mm
		<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed	<b>EXTRAS</b>	Alloy kickstand
		<b>CASSETTE</b>	Shimano HG20 7 speed cassette 12-28T		



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

700c Low step through Alloy Frame with comfort geometry.

Hi-ten Steel fork.

7 speed Shimano Revo-Shift.

Alloy quill adjustable stem for maximum comfort.

Extra large comfort saddle.

Powerful Promax V-Brakes.

Alloy hubs with Weinmann double wall rims for extra strength.

Upgraded sealed bearing cartridge BB.

## CODES

	XS	S	M
Gloss Pearl White / Gloss Turquoise	17135	17136	17137
Gloss Navy Blue / Gloss Silver	17138	17139	17140

## GEOMETRY

	XS	S	M
STACK	617	631	648
REACH	347	363	374
STAND OVER HEIGHT	218	227	235
EFFECTIVE TOP TUBE	560	580	610
SEAT TUBE (CENTRE TO TOP)	355	406	457
SEAT ANGLE	71.0°	71.0°	70.0°
HEAD TUBE LENGTH	140	155	170
HEAD ANGLE	69.5°	69.5°	70.0°
WHEEL BASE	1050	1070	1079
CHAIN STAY LENGTH	460	460	460
BB DROP	70	70	70
FORK RAKE	38	38	38
AXLE TO CROWN	460	460	460
REAR DROPOUT SPACING	135	135	135

## SPECIFICATIONS

<b>FRAME</b>	6061 butted alloy women's step through "Comfort zone" geometry frame with optimised step through clearance and snake stays	<b>HEADSTEM</b>	Alloy adjustable quill stem	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	700c rigid hi-tensile steel	<b>CRANKSET</b>	Alloy crank with 44T single chainwheel with double chain guide L: 170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	Threaded semi-sealed 1-1/8"	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Weinmann X-M1 double wall alloy rims. 32 hole A/V. Alloy quick release front and nutted rear hubs. Stainless spokes
<b>HANDLEBAR</b>	Alloy comfort bars, R: 40mm, W: 580mm, Sweep 10°	<b>PEDALS</b>	Comfort non-slip with rubber insert	<b>TYRES</b>	700 x 38c wire bead
<b>GRIP</b>	Kraton comfort grip	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Factor Comfortech women's specific
		<b>R. DERAILLEUR</b>	Shimano Tourney 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust with alloy clamp
		<b>SHIFT LEVERS</b>	Shimano Revoshift 7 speed.	<b>EXTRAS</b>	Alloy kickstand
		<b>CASSETTE</b>	Shimano 7 speed 14-34T freewheel		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

New 700c City / Commuting inspired traditional light weight Cro-Mo steel frame

New Hi-ten traditional steel fork for disc brakes

Shimano Nexus Inner-8 speed shifting.

700c x 42c brown wall tyres.

Alloy hubs with Weinmann double wall rims for extra strength.

A-head Alloy stem with riser handlebar.

Powerful Promax V-Brakes.

Alloy colour match mudguards with stainless steel struts.

Rear carrier standard.

### CODES

	S	M	L	XL
Gloss Charcoal / Gloss Cream / Gloss Red	17086	17087	17088	17089

### GEOMETRY

	S	M	L	XL
STACK	535	556	576	595
REACH	382	410	424	432
EFFECTIVE TOP TUBE	540	575	600	620
SEAT TUBE (CENTRE TO TOP)	500	530	560	590
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	135	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1027	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	65	65	65	65
FORK RAKE	45	45	45	45
AXLE TO CROWN	380	380	380	380
REAR DROPOUT SPACING	120	120	120	120

### SPECIFICATIONS

<b>FRAME</b>	Cromoly steel commuter frame with rack and fender mounts	<b>CRANKSET</b>	Cold forged 44T crank with double chain cover L: 170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>FORK</b>	700c Hi-ten 1-1/8" straight blade fork with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Double wall rims with machined side walls, 32 hole F/V, Shimano Nexus internal rear hub, alloy front hub and stainless spokes.
<b>HEADSET</b>	A-head 1-1/8" threadless with semi cartridge bearings	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	700 x 40c 60tpi wire bead with puncture protection
<b>HANDLEBAR</b>	Oversize alloy low riser bar, bore: 31.8mm, W: 580mm, sweep: 5°	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Classic series saddle with brass rivets
<b>GRIP</b>	Leather look tape grip	<b>R. DERAILLEUR</b>	N/A	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>HEADSTEM</b>	Alloy 4 bolt stem, bore: 31.8mm L: S / M=90mm, L=105mm, XL=120mm	<b>SHIFT LEVERS</b>	Shimano Nexus shift 8 speed	<b>EXTRAS</b>	Alloy full length front and rear mudguards, alloy pannier rack
		<b>CASSETTE</b>	Shimano 20T freewheel		
		<b>CHAIN</b>	KMC Z-610		



### KEY FEATURES

New 700c City / Commuting inspired traditional Hi-ten steel frame

New Hi-ten traditional steel fork for disc brakes

Shimano Nexus Inner-3 speed shifting.

700c x 42c brown wall tyres.

Alloy hubs with Weinmann double wall rims for extra strength.

A-head Alloy stem with riser handlebar.

Powerful Promax V-Brakes.

Alloy colour match mudguards with stainless steel struts.

Rear carrier standard.

### CODES

	S	M	L	XL
Gloss Navy Blue / Gloss Cream / Gloss Orange	17090	17091	17092	17093

### GEOMETRY

	S	M	L	XL
STACK	535	556	576	595
REACH	382	410	424	432
EFFECTIVE TOP TUBE	540	575	600	620
SEAT TUBE (CENTRE TO TOP)	500	530	560	590
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	135	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1027	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	65	65	65	65
FORK RAKE	45	45	45	45
AXLE TO CROWN	380	380	380	380
REAR DROPOUT SPACING	120	120	120	120

### SPECIFICATIONS

<b>FRAME</b>	Hi tensile commuter frame with rack and fender mounts	<b>CRANKSET</b>	Cold forged High polish 38T alloy crank with guard L: 170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>FORK</b>	700c Hi-ten 1-1/8 straight blade fork with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	700c Double wall alloy rims. 32 hole A/V, alloy hubs with double seal system. Stainless spokes
<b>HEADSET</b>	A-head threadless 1-1/8"	<b>PEDALS</b>	High impact dual compound resin	<b>TYRES</b>	700 x 40c 60tpi wire bead with puncture protection
<b>HANDLEBAR</b>	Alloy low riser, bore: 25.4mm, W: 580mm, sweep: 6°	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Classic series saddle with brass rivets
<b>GRIP</b>	Leather look tape grip	<b>R. DERAILLEUR</b>	3 Speed internal hub gears	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
<b>HEADSTEM</b>	Alloy 2 bolt stem, 25.4mm, S/M=90mm, L/XL=105mm	<b>SHIFT LEVERS</b>	Shimano Nexus shift 3 speed	<b>EXTRAS</b>	Alloy full length front and rear mudguards, alloy pannier rack
		<b>CASSETTE</b>	Shimano 18T freewheel		
		<b>CHAIN</b>	KMC Z-610		





MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

New 700c City / Commuting inspired traditional Hi-ten steel frame

New Hi-ten traditional steel fork for disc brakes

8 speed Shimano rapid-fire shifting.

700c x 42c brown wall tyres.

Alloy hubs with Weinmann double wall rims for extra strength.

A-head Alloy stem with riser handlebar.

Powerful Disc brakes with 160mm rotors front and rear.

### CODES

	S	M	L	XL
Gloss Slate / Gloss Sky Blue / Gloss Red	17094	17095	17096	17097
Gloss Navy Blue / Gloss Cream / Gloss Red	16215	16216	16217	16218

### GEOMETRY

	S	M	L	XL
STACK	535	556	576	595
REACH	382	410	424	432
EFFECTIVE TOP TUBE	540	575	600	620
SEAT TUBE (CENTRE TO TOP)	500	530	560	590
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	135	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1027	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	65	65	65	65
FORK RAKE	45	45	45	45
AXLE TO CROWN	380	380	380	380
REAR DROPOUT SPACING	120	120	120	120

### SPECIFICATIONS

<b>FRAME</b>	Hi tensile disc specific commuter frame with rack and fender mounts	<b>CRANKSET</b>	Cold forged 44T crank with double chain cover L: 170mm	<b>BRAKES</b>	Tektro MD-280 mechanical disc brakes with 160mm rotors
<b>FORK</b>	700c Hi-ten disc specific 1-1/8 straight blade fork with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>BRAKES (ALT. COLOUR)</b>	Promax DSK 300 mechanical disc brakes with 160mm rotors
<b>HEADSET</b>	A-head threadless 1-1/8"	<b>PEDALS</b>	Low profile high impact resin	<b>WHEELS</b>	700c Double wall rims, 32 hole A/V, alloy quick release disc hubs with stainless spokes
<b>HANDLEBAR</b>	Alloy low riser, bore: 25.4mm, W: 580mm, sweep: 6°	<b>F. DERAILLEUR</b>	N/A	<b>TYRES</b>	700 x 40c wire bead
<b>GRIP</b>	Leather look tape grip	<b>R. DERAILLEUR</b>	Shimano Acera 8 speed	<b>SADDLE</b>	Classic series saddle with brass rivets
<b>HEADSTEM</b>	Alloy 2 bolt stem, 25.4mm, S/M=90mm, L/XL=105mm	<b>SHIFT LEVERS</b>	Shimano Acera Rapid fire 8 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>CASSETTE</b>	Shimano 8 speed cassette 12-32T	<b>EXTRAS</b>	N/A
		<b>CHAIN</b>	KMC Z-7		



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

New 700c City / Commuting inspired traditional Hi-ten steel frame

New Hi-ten traditional steel fork

21 speed Shimano EZ-fire shifting.

700c x 42c brown wall tyres.

Alloy hubs with Weinmann double wall rims for extra strength.

A-head Alloy stem with riser handlebar.

Powerful Promax V-Brakes.

## CODES

	S	M	L	XL
Gloss Orange / Gloss Sky Blue / Gloss Black	17098	17099	17100	17101
Gloss Black / Gloss Sky Blue / Gloss Bronze	16219	16220	16221	16222

## GEOMETRY

	S	M	L	XL
STACK	535	556	576	595
REACH	382	410	424	432
EFFECTIVE TOP TUBE	540	575	600	620
SEAT TUBE (CENTRE TO TOP)	500	530	560	590
SEAT ANGLE	73.5°	73.5°	73.0°	72.5°
HEAD TUBE LENGTH	135	155	175	195
HEAD ANGLE	71.0°	71.5°	72.0°	72.0°
WHEEL BASE	1027	1060	1075	1090
CHAIN STAY LENGTH	440	440	440	440
BB DROP	65	65	65	65
FORK RAKE	45	45	45	45
AXLE TO CROWN	380	380	380	380
REAR DROPOUT SPACING	120	120	120	120

## SPECIFICATIONS

<b>FRAME</b>	Hi tensile commuter frame with rack and fender mounts	<b>CRANKSET</b>	Alloy crank with 48 x 38 x 28T L=170mm	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	700c Hi-ten 1-1/8 straight blade fork with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	A-head threadless 1-1/8"	<b>PEDALS</b>	High impact nylon	<b>WHEELS</b>	700c Double wall alloy rims. 32 hole A/V, alloy hubs with double seal system. Stainless spokes
<b>HANDLEBAR</b>	Low riser, bore: 25.4mm, W:580mm, sweep: 6°	<b>F. DERAILLEUR</b>	Shimano TX-800 top pull for 31.8mm	<b>TYRES</b>	700 x 40c wire bead
<b>GRIP</b>	Leather look tape grip	<b>R. DERAILLEUR</b>	Shimano TY-300 7 speed	<b>SADDLE</b>	Classic series saddle with brass rivets
<b>HEADSTEM</b>	Alloy 2 bolt stem, 25.4mm, S/M=90mm, L/XL=105mm	<b>R. DERAILLEUR (ALT. COLOUR)</b>	Shimano TX 35 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust
		<b>SHIFT LEVERS</b>	Shimano EF-41 Ez Fire 21 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

Classic Hi-ten Steel Low step through frame designed for city use.

Easy shifting 7 speed Shimano Nexus Inner-7 hub gears.

Powerful Promax V-Brakes.

Alloy hubs with Weinmann double wall rims for extra strength.

Quilled stem for maximum adjustability.

Alloy colour match mudguards with stainless steel struts.

Soft Comfortable oversized saddle with coil springs.

Wicker like front basket.

### CODES

	S	M
Gloss Cream / Gloss Red / Gloss Charcoal	16223	16224

### GEOMETRY

	S	M
STACK	583	601
REACH	408	416
EFFECTIVE TOP TUBE	575	600
SEAT TUBE (CENTRE TO TOP)	420	470
SEAT ANGLE	74.0°	73.0°
HEAD TUBE LENGTH	150	170
HEAD ANGLE	69.0°	69.0°
WHEEL BASE	1101	1114
CHAIN STAY LENGTH	450	450
BB DROP	70	70
FORK RAKE	45	45
AXLE TO CROWN	419	419
REAR DROPOUT SPACING	130	130

### SPECIFICATIONS

<b>FRAME</b>	Mixtie twin down tube classic styled frame in Hi Ten tubing with rack and fender mounts	<b>CRANKSET</b>	Cold forged high polish classic series crank with double chain cover L: 170mm	<b>BRAKES</b>	Dual pivot classic series calipers
<b>FORK</b>	700c Hi-Ten 1" with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Double wall rims with machined side walls, 32 hole A/V, Shimano Nexus 7 speed internal rear hub, alloy front hub and stainless spokes.
<b>HEADSET</b>	Threaded 1"	<b>PEDALS</b>	Low profile high impact resin	<b>TYRES</b>	700 x 38c gum wall
<b>HANDLEBAR</b>	Classic moustache bar, bore: 25.4mm, W: 580mm, sweep: 27°	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Classic Series female specific comfort saddle
<b>GRIP</b>	Dual density leather look grip	<b>R. DERAILLEUR</b>	7 Speed internal hub gears	<b>SEATPOST / CLAMP</b>	High polish steel 28.6mm
<b>HEADSTEM</b>	High polish quill stem	<b>SHIFT LEVERS</b>	Shimano Nexus shift 7 speed	<b>EXTRAS</b>	Full length alloy mudguards, front mount wicker style basket, alloy kickstand
		<b>CASSETTE</b>	Shimano 18T freewheel		
		<b>CHAIN</b>	KMC Z-610		

MTB

ROAD

LIFESTYLE

YOUTH



### KEY FEATURES

Classic Hi-ten Steel Low step through frame designed for city use.

Easy shifting 8 speed Shimano Claris shifting with cassette

Powerful Promax disc brakes with 160mm rotors front and rear.

Alloy hubs with Weinmann double wall rims for extra strength.

Oversized alloy a-head stem with oversized bar.

Alloy colour match mudguards with stainless steel struts.

Soft Comfortable oversized saddle with coil springs.

Wicker like front basket.

### CODES

CODES	S	M
Gloss Sky Blue / Gloss Red / Gloss Navy Blue	16225	16226

### GEOMETRY

GEOMETRY	S	M
STACK	583	601
REACH	408	416
EFFECTIVE TOP TUBE	575	600
SEAT TUBE (CENTRE TO TOP)	420	470
SEAT ANGLE	74.0°	73.0°
HEAD TUBE LENGTH	150	170
HEAD ANGLE	69.0°	69.0°
WHEEL BASE	1101	1114
CHAIN STAY LENGTH	450	450
BB DROP	70	70
FORK RAKE	45	45
AXLE TO CROWN	419	419
REAR DROPOUT SPACING	135	135

### SPECIFICATIONS

<b>FRAME</b>	Disc specific mixtie twin down tube classic styled frame in Hi Ten tubing with rack and fender mounts	<b>CRANKSET</b>	Cold forged high polish classic series crank with double chain cover L: 170mm	<b>BRAKES</b>	Promax DSK 300 mechanical disc brakes with 160mm rotors
<b>FORK</b>	700c Hi-Ten 1" with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Double wall rims, 32 hole A/V with quick release hubs and stainless steel spokes
<b>HEADSET</b>	A-head threadless 1"	<b>PEDALS</b>	High impact dual compound resin	<b>TYRES</b>	700 x 38c gum wall
<b>HANDLEBAR</b>	Classic sweeper bar, Bore: 31.8mm, W: 580mm, sweep:38°, Rise: 38	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Classic Series female specific comfort saddle
<b>GRIP</b>	Dual density leather look grip	<b>R. DERAILLEUR</b>	Shimano Claris 8 speed	<b>SEATPOST / CLAMP</b>	High polish steel 28.6mm
<b>HEADSTEM</b>	Oversize alloy 2 bolt stem, 31.8mm	<b>SHIFT LEVERS</b>	Shimano Claris 8 speed flat bar shifter	<b>EXTRAS</b>	Full length alloy painted mudguards, front mount wicker style basket, alloy kickstand
		<b>CASSETTE</b>	Shimano 8 speed cassette 12 - 32T		
		<b>CHAIN</b>	KMC Z-7		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

Classic Hi-ten Steel Low step through frame designed for city use.

Easy shifting 8 speed Shimano Claris shifting.

Powerful Promax V-Brakes.

Alloy hubs with Weinmann double wall rims for extra strength.

Quilled stem for maximum adjustability.

Alloy colour match mudguards with stainless steel struts.

Soft Comfortable oversized saddle with coil springs.

Wicker like front basket.

### CODES

	S	M
Gloss Charcoal / Gloss Cream / Gloss Purple	16227	16228

### GEOMETRY

	S	M
STACK	583	601
REACH	408	416
EFFECTIVE TOP TUBE	575	600
SEAT TUBE (CENTRE TO TOP)	420	470
SEAT ANGLE	74.0°	73.0°
HEAD TUBE LENGTH	150	170
HEAD ANGLE	69.0°	69.0°
WHEEL BASE	1101	1114
CHAIN STAY LENGTH	450	450
BB DROP	70	70
FORK RAKE	45	45
AXLE TO CROWN	419	419
REAR DROPOUT SPACING	130	130

### SPECIFICATIONS

<b>FRAME</b>	Mixtie twin down tube classic styled frame in Hi Ten tubing with rack and fender mounts	<b>CRANKSET</b>	Cold forged high polish classic series crank with double chain cover L: 170mm	<b>BRAKES</b>	Dual pivot classic series calipers
<b>FORK</b>	700c Hi-Ten 1" with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Double wall rims, 32 hole A/V with polished quick release front and nutted rear hubs and stainless steel spokes
<b>HEADSET</b>	Threaded 1"	<b>PEDALS</b>	High impact dual compound resin	<b>TYRES</b>	700 x 38c gum wall
<b>HANDLEBAR</b>	Classic moustache bar, bore: 25.4mm, W: 580mm, sweep: 27°	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Classic Series female specific comfort saddle
<b>GRIP</b>	Dual density leather look grip	<b>R. DERAILLEUR</b>	Shimano Claris 8 speed	<b>SEATPOST / CLAMP</b>	High polish steel 28.6mm
<b>HEADSTEM</b>	High polish quill stem	<b>SHIFT LEVERS</b>	Shimano Claris 8 speed flat bar shifter	<b>EXTRAS</b>	Full length alloy painted mudguards, front mount wicker style basket, alloy kickstand
		<b>CASSETTE</b>	Shimano 8 speed cassette 12 - 32T		
		<b>CHAIN</b>	KMC Z-7		



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

Classic Hi-ten Steel Low step through frame designed for city use.

Easy shifting 3 speed Shimano Nexus Inner-3 shifting.

Powerful Promax V-Brakes on the front and a quiet and efficient Shimano roller brake on the rear.

Alloy hubs with Weinmann double wall rims for extra strength.

Quilled stem for maximum adjustability.

Alloy colour match mudguards with stainless steel struts.

Soft Comfortable oversized saddle with coil springs.

Wicker like front basket.

## CODES

	S	M
Gloss Cream / Gloss Orange / Gloss Slate	16229	16230
Gloss White / Gloss Green / Gloss Slate	16231	16232

## GEOMETRY

	S	M
STACK	583	601
REACH	408	416
EFFECTIVE TOP TUBE	575	600
SEAT TUBE (CENTRE TO TOP)	420	470
SEAT ANGLE	74.0°	73.0°
HEAD TUBE LENGTH	150	170
HEAD ANGLE	69.0°	69.0°
WHEEL BASE	1101	1114
CHAIN STAY LENGTH	450	450
BB DROP	70	70
FORK RAKE	45	45
AXLE TO CROWN	419	419
REAR DROPOUT SPACING	120	120

## SPECIFICATIONS

<b>FRAME</b>	Mixtie twin down tube classic styled frame in Hi Ten tubing with rack and fender mounts	<b>CRANKSET</b>	Cold forged high polish classic series crank with double chain cover L: 170mm	<b>BRAKES</b>	Linear pull front brake. Shimano Nexus roller rear brake.
<b>FORK</b>	700c Hi-Ten 1" with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Double wall alloy rims. 32 hole A/V, alloy hubs with double seal system. Stainless spokes
<b>HEADSET</b>	Threaded 1"	<b>PEDALS</b>	High impact dual compound resin	<b>TYRES</b>	700 x 38c gum wall
<b>HANDLEBAR</b>	Classic moustache bar, bore: 25.4mm, W: 580mm, sweep: 27°	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Classic Series female specific comfort saddle
<b>GRIP</b>	Dual density leather look grip	<b>R. DERAILLEUR</b>	3 Speed internal hub gears	<b>SEATPOST / CLAMP</b>	High polish steel 28.6mm
<b>HEADSTEM</b>	High polish quill stem	<b>SHIFT LEVERS</b>	Shimano Nexus shift 3 speed	<b>EXTRAS</b>	Full length alloy painted mudguards, front mount wicker style basket, alloy kickstand
		<b>CASSETTE</b>	Shimano 18T freewheel		
		<b>CHAIN</b>	KMC Z-610		



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

Classic design Low step through Alloy frame designed for city use.

Easy shifting 3 speed Shimano Nexus Inner-3 hub gears.

Powerful Promax V-Brakes on the front and a quite and efficient Shimano roller brake on the rear.

Alloy hubs with Weinmann double wall rims for extra strength.

Quilled stem for maximum adjustability.

Alloy colour match mudguards with stainless steel struts.

Soft Comfortable oversized saddle with coil springs.

Wicker like front basket.

### CODES

	S	M
Gloss Green	16233	16234
Gloss Light Pink / Gloss Pink	16237	16238

### GEOMETRY

	S	M
STACK	590	609
REACH	360	378
EFFECTIVE TOP TUBE	575	600
SEAT TUBE (CENTRE TO TOP)	420	470
SEAT ANGLE	70.0°	70.0°
HEAD TUBE LENGTH	160	180
HEAD ANGLE	69.0°	69.0°
WHEEL BASE	1081	1094
CHAIN STAY LENGTH	460	460
BB DROP	70	70
FORK RAKE	45	45
AXLE TO CROWN	417	417
REAR DROPOUT SPACING	120	120

### SPECIFICATIONS

<b>FRAME</b>	Ladies classic style low step through alloy commuter frame with rack and fender mounts and classic comfort geometry	<b>CRANKSET</b>	High polish 38T alloy crank with guard L: 170mm	<b>BRAKES</b>	Linear pull front brake. Shimano Nexus roller rear brake.
<b>FORK</b>	700c Hi-Ten 1" with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Weinmann Zac 19 double wall alloy rims. 32 hole A/V, alloy hubs with double seal system. Stainless spokes
<b>HEADSET</b>	Threaded 1"	<b>PEDALS</b>	High impact dual compound resin	<b>TYRES</b>	700 x 38c gum wall
<b>HANDLEBAR</b>	Classic Sweeper bar, Raise: 66mm, bore: 25.4mm, W: 610mm, sweep: 43°	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Classic Series female specific comfort saddle
<b>GRIP</b>	Dual density leather look grip	<b>R. DERAILLEUR</b>	3 Speed internal hub gears	<b>SEATPOST / CLAMP</b>	High polish steel 27.2mm
<b>HEADSTEM</b>	High polish quill stem	<b>SHIFT LEVERS</b>	Shimano Nexus shift 3 speed	<b>EXTRAS</b>	Full length painted mudguards, rear carrier, front mount wicker style basket and alloy kickstand
		<b>CASSETTE</b>	Shimano 18T freewheel		
		<b>CHAIN</b>	KMC Z-610		



MTB

ROAD

LIFESTYLE

YOUTH

## KEY FEATURES

Classic design Low step through Alloy frame designed for city use.

Easy shifting 7 speed Shimano Revo-Shift.

Powerful Promax V-Brakes.

Alloy hubs with Weinmann double wall rims for extra strength.

Quilled stem for maximum adjustability.

Alloy colour match mudguards with stainless steel struts.

Soft Comfortable oversized saddle with coil springs.

Wicker like front basket.

## CODES

	S	M
Gloss Purple / Gloss Blue	16239	16240
Gloss Navy Blue / Gloss Cream	16241	16242

## GEOMETRY

	S	M
STACK	590	609
REACH	360	378
EFFECTIVE TOP TUBE	575	600
SEAT TUBE (CENTRE TO TOP)	420	470
SEAT ANGLE	70.0°	70.0°
HEAD TUBE LENGTH	160	180
HEAD ANGLE	69.0°	69.0°
WHEEL BASE	1081	1094
CHAIN STAY LENGTH	460	460
BB DROP	70	70
FORK RAKE	45	45
AXLE TO CROWN	417	417
REAR DROPOUT SPACING	135	135

## SPECIFICATIONS

<b>FRAME</b>	Ladies classic style low step through alloy commuter frame with rack and fender mounts and classic comfort geometry	<b>CRANKSET</b>	High polish classic series crank with double chain cover L: 170mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>FORK</b>	700c Hi-Ten 1" with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	Weinmann Zac 19 double wall alloy rims. 32 hole A/V, Alloy hubs with double seal system. Stainless spokes
<b>HEADSET</b>	Threaded 1"	<b>PEDALS</b>	High impact dual compound resin	<b>TYRES</b>	700 x 38c gum wall
<b>HANDLEBAR</b>	Classic Sweeper bar, Raise: 66mm, bore: 25.4mm, W: 610mm, sweep: 43°	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Classic Series female specific comfort saddle
<b>GRIP</b>	Dual density leather look grip	<b>R. DERAILLEUR</b>	Shimano Tourney 7 speed	<b>SEATPOST / CLAMP</b>	High polish steel 27.2mm
<b>HEADSTEM</b>	High polish quill stem	<b>SHIFT LEVERS</b>	Shimano Revoshift 7 speed.	<b>EXTRAS</b>	Full length alloy painted mudguards, front mount wicker style basket, alloy kickstand
		<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel		
		<b>CHAIN</b>	KMC Z-51		





MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

26" Alloy Beach Cruiser frame, with Apollo cruising geometry

Alloy hubs with Alex Zuma beach cruiser rim.

26" x 2.35 Whitewall tyres

Shimano Nexus Inner-3 Shifting with rear coaster brake.

Powerful Promax V-Brakes on the front.

Steel mudguard custom painted to match with stainless struts

Steel Chain guard custom painted to match

Large comfortable cruisers saddle, with leather like grip.

### CODES

Gloss Navy Blue / Gloss Pink

### ONE SIZE FITS MOST

16276

### GEOMETRY

### ONE SIZE FITS MOST

STACK	521
REACH	420
EFFECTIVE TOP TUBE	620
SEAT TUBE (CENTRE TO TOP)	444
SEAT ANGLE	69.0°
HEAD TUBE LENGTH	150
HEAD ANGLE	68.0°
WHEEL BASE	1139
CHAIN STAY LENGTH	486
BB DROP	58
FORK RAKE	45
AXLE TO CROWN	370
REAR DROPOUT SPACING	120

### SPECIFICATIONS

<b>FRAME</b>	Ladies alloy cruiser	<b>CRANKSET</b>	High polish 44T alloy crank with full length chain guard L: 165mm	<b>BRAKES</b>	Linear pull front brake. Shimano Nexus rear coaster foot brake.
<b>FORK</b>	Hi-Ten 1" with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	36 hole alloy cruiser rims. Alloy hubs with double seal system and nutted axles. Stainless spokes
<b>HEADSET</b>	Threaded 1-1/8"	<b>PEDALS</b>	Resin cruiser pedals	<b>TYRES</b>	26 x 2.35" white wall balloon tyre
<b>HANDLEBAR</b>	Cruiser bar W: 640mm, R: 75mm, sweep: 50°	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Cruiser saddle with spring rail
<b>GRIP</b>	Dual density leather look grip	<b>R. DERAILLEUR</b>	N/A	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm
<b>HEADSTEM</b>	High polish quill stem	<b>SHIFT LEVERS</b>	Shimano Nexus shift 3 speed	<b>EXTRAS</b>	Full length chain and full length painted mudguards and alloy kickstand
		<b>CASSETTE</b>	Shimano 18T freewheel		
		<b>CHAIN</b>	KMC Z-610		

MTB

ROAD



### KEY FEATURES

26" Alloy Beach Cruiser frame, with Apollo cruising geometry

Alloy hubs with Alex Zuma beach cruiser rim.

26" x 2.35 Whitewall tyres

7-speed Shimano EZ-fire shifting.

Steel mudguard custom painted to match with stainless struts

Steel Chain guard custom painted to match

Large comfortable cruisers saddle, with leather like grip.

Powerful Promax V-Brakes.

### CODES

Gloss Ice Blue / Gloss Blue

### ONE SIZE FITS MOST

16277

### GEOMETRY

### ONE SIZE FITS MOST

STACK	521
REACH	420
EFFECTIVE TOP TUBE	620
SEAT TUBE (CENTRE TO TOP)	444
SEAT ANGLE	69.0°
HEAD TUBE LENGTH	150
HEAD ANGLE	68.0°
WHEEL BASE	1139
CHAIN STAY LENGTH	486
BB DROP	58
FORK RAKE	45
AXLE TO CROWN	370
REAR DROPOUT SPACING	135

## SPECIFICATIONS

<b>FRAME</b>	Ladies alloy cruiser	<b>CRANKSET</b>	High polish 44T alloy crank with full length chain guard L: 165mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>FORK</b>	Hi-Ten 1" with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	36 hole alloy cruiser rims. Alloy hubs with double seal system and nutted axles. Stainless spokes
<b>HEADSET</b>	Threaded 1-1/8"	<b>PEDALS</b>	Resin cruiser pedals	<b>TYRES</b>	26 x 2.35" white wall balloon tyre
<b>HANDLEBAR</b>	Cruiser bar W: 640mm, R: 75mm, sweep: 50°	<b>F. DERAILEUR</b>	N/A	<b>SADDLE</b>	Cruiser saddle with spring rail
<b>GRIP</b>	Dual density leather look grip	<b>R. DERAILEUR</b>	Shimano TX35 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm
<b>HEADSTEM</b>	High polish quill stem	<b>SHIFT LEVERS</b>	Shimano Revoshift 7 speed.	<b>EXTRAS</b>	Full length chain and full length painted mudguards and alloy kickstand
		<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel		
		<b>CHAIN</b>	KMC Z-51		

LIFESTYLE

YOUTH



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

26" Alloy Beach Cruiser frame, with Apollo cruising geometry

Alloy hubs with Alex Zuma beach cruiser rim.

26" x 2.35 Whitewall tyres

7-speed Shimano EZ-fire shifting.

Steel mudguard custom painted to match with stainless struts

Steel Chain guard custom painted to match

Large comfortable cruisers saddle, with leather like grip.

Powerful Promax V-Brakes.

### CODES

Matte Black / Matte Red

### ONE SIZE FITS MOST

16278

### GEOMETRY

### ONE SIZE FITS MOST

STACK	539
REACH	433
EFFECTIVE TOP TUBE	640
SEAT TUBE (CENTRE TO TOP)	510
SEAT ANGLE	69.0°
HEAD TUBE LENGTH	170
HEAD ANGLE	68.0°
WHEEL BASE	1147
CHAIN STAY LENGTH	486
BB DROP	58
FORK RAKE	45
AXLE TO CROWN	370
REAR DROPOUT SPACING	135

### SPECIFICATIONS

<b>FRAME</b>	Men's alloy cruiser	<b>CRANKSET</b>	High polish 44T alloy crank with full length chain guard L: 165mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>FORK</b>	Hi-Ten 1" with rack and fender mounts	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	36 hole alloy cruiser rims. Alloy hubs with double seal system and nutted axles. Stainless spokes
<b>HEADSET</b>	Threaded 1-1/8"	<b>PEDALS</b>	Resin cruiser pedals	<b>TYRES</b>	26 x 2.35" white wall balloon tyre
<b>HANDLEBAR</b>	Cruiser bar W: 640mm, R: 75mm, sweep: 50°	<b>F. DERAILLEUR</b>	N/A	<b>SADDLE</b>	Cruiser saddle with spring rail
<b>GRIP</b>	Dual density leather look grip	<b>R. DERAILLEUR</b>	Shimano Tourney 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm
<b>HEADSTEM</b>	High polish quill stem	<b>SHIFT LEVERS</b>	Shimano Revoshift 7 speed.	<b>EXTRAS</b>	Full length chain and full length painted mudguards and alloy kickstand
		<b>CASSETTE</b>	Shimano 7 speed 14-28T freewheel		
		<b>CHAIN</b>	KMC Z-51		



## KEY FEATURES

7005 Alloy Tandem frame, Designed to strong and comfortable for the riders.

Heavy Duty cro-mo Steel Fork for extra strength.

Super powerful upgraded Hayes MX Comp mechanical disk brakes, with 180mm rotors from and rear

27 speed Shimano EZ-Fire shifting with Cassette

oversized alloy handlebars and stems.

Alloy hubs and Weinmann double wall rims with eyelets for extra strength.

## CODES

Gloss White / Gloss Slate /  
Gloss Lime

## ONE SIZE FITS MOST

16273

## GEOMETRY

	FRONT	REAR
EFFECTIVE TOP TUBE	580	615
SEAT TUBE (CENTRE TO TOP)	496	400
SEAT ANGLE	71.5°	72.0°
HEAD TUBE LENGTH	140	-
HEAD ANGLE	71.0°	71.5°
WHEEL BASE	1677	
CHAIN STAY LENGTH	-	450
BB DROP	70	70
FORK RAKE	45	-
AXLE TO CROWN	375	-
REAR DROPOUT SPACING	135	135

## SPECIFICATIONS

<b>FRAME</b>	Double diamond design tandem frame with eccentric bottom bracket	<b>HEADSTEM</b>	Front: Alloy 31.8mm A-head stem L=100mm. Rear: Adjustable length 31.8mm alloy stem R: 35mm, 155mm-200mm adjustment	<b>CASSETTE</b>	Shimano HG20 9 speed cassette 11-32T
<b>FORK</b>	Oversized 700c 1-1/8 full Cro-mo rigid straight blade fork, disc brake mounts	<b>CRANKSET</b>	(timing cranks) 3/32x39T 170mm alloy crank, (rear) alloy 44/32/22T	<b>CHAIN</b>	KMC Z-99
<b>HEADSET</b>	A-head semi integrated, semi-sealed 1-1/8"	<b>BOTTOM BRACKET</b>	Front: Eccentric bottom bracket, Rear:sealed cartridge	<b>BRAKES</b>	Hayes MX comp mechanical disc brakes with 180mm rotors
<b>HANDLEBAR</b>	Front: Alloy low rise bar, W: 600mm, Bore: 31.8mm, Sweep: 6° Rear: Alloy flat bar, W: 600mm, Bore: 31.8mm	<b>PEDALS</b>	Low profile high impact resin	<b>WHEELS</b>	Weinmann XM25 alloy double wall disc F/V rims with eyelets, 36 hole, anodised disc hubs and stainless spokes
<b>GRIP</b>	Kraton gel dual density grip	<b>F. DERAILLEUR</b>	Shimano M370 Altus 9 speed, top pull for 31.8mm	<b>TYRES</b>	700 x 38c wire bead
		<b>R. DERAILLEUR</b>	Shimano Alivio 9 speed	<b>SADDLE</b>	Factor dual density MTB sport saddle
		<b>SHIFT LEVERS</b>	Shimano Altus Ez Fire 27 speed	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm micro adjust twin bolt post with alloy clamp
				<b>EXTRAS</b>	N/A



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

Full featured commuter with mudguards, rear carrier and adjustable kickstand.

Lightweight alloy frame folds for easy carrying and storage.

Reliable Shimano shifting for worry-free commuting.

Double wall rims for added durability.

Comfortable Factor Ergotech saddle.

### CODES

Gloss Charcoal / Gloss Red /  
Gloss Black

### ONE SIZE FITS MOST

16411

### GEOMETRY

### ONE SIZE FITS MOST

EFFECTIVE TOP TUBE	565
SEAT TUBE (CENTRE TO TOP)	290
SEAT ANGLE	74.0°
HEAD TUBE LENGTH	90
HEAD ANGLE	72.0°
WHEEL BASE	997
CHAIN STAY LENGTH	395
BB DROP	41
FORK RAKE	35
AXLE TO CROWN	310
REAR DROPOUT SPACING	135

### SPECIFICATIONS

<b>FRAME</b>	6061 alloy folding with replaceable derailleur hanger	<b>CRANKSET</b>	Prowheel 546 alloy 46T with double guard, L: 170mm	<b>CHAIN</b>	KMC Z-30
<b>FORK</b>	Unicrown hi-tensile	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>BRAKES</b>	Tektro Alloy linear pull brakes
<b>HEADSET</b>	Semi-sealed 1-1/8" standard	<b>PEDALS</b>	Comfort non slip Hi-Impact PP, foldable	<b>WHEELS</b>	Alloy Double Wall 20 hole rims with alloy hubs. Black Spokes
<b>HANDLEBAR</b>	Alloy comfort, R: 30mm	<b>F. DERAILLEUR</b>	N/A	<b>TYRES</b>	20 x 1.75" Semi-Slick
<b>GRIP</b>	TPR Grip	<b>R. DERAILLEUR</b>	Shimano ALTUS	<b>SADDLE</b>	Factor Ergotech Saddle
<b>HEADSTEM</b>	Alloy foldable	<b>SHIFT LEVERS</b>	Shimano Revoshift 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 34mm with quick release clamp
		<b>CASSETTE</b>	Shimano TZ-21 7 speed 14-28T	<b>EXTRAS</b>	Mudguards, Carrier and Adjustable Kickstand

MTB

ROAD

LIFESTYLE



### KEY FEATURES

Rear carrier and adjustable kickstand add functionality to a compact commuter design.

Lightweight alloy frame folds for easy carrying and storage.

Reliable Shimano shifting for worry-free commuting.

Double wall rims for added durability.

Comfortable Factor Ergotech saddle.

### CODES

Gloss White / Gloss Black /  
Gloss Silver

### ONE SIZE FITS MOST

16412

### GEOMETRY

### ONE SIZE FITS MOST

EFFECTIVE TOP TUBE	565
SEAT TUBE (CENTRE TO TOP)	290
SEAT ANGLE	74.0°
HEAD TUBE LENGTH	90
HEAD ANGLE	72.0°
WHEEL BASE	997
CHAIN STAY LENGTH	395
BB DROP	41
FORK RAKE	35
AXLE TO CROWN	310
REAR DROPOUT SPACING	135

### SPECIFICATIONS

<b>FRAME</b>	6061 alloy folding with replaceable derailleur hanger	<b>CRANKSET</b>	Prowheel 546 alloy 46T with double guard, L: 170mm	<b>CHAIN</b>	KMC HV500
<b>FORK</b>	Unicrown hi-tensile	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	Semi-sealed 1-1/8" standard	<b>PEDALS</b>	Comfort non slip Hi-Impact PP, foldable	<b>WHEELS</b>	Alloy 20 hole rims. Black Spokes
<b>HANDLEBAR</b>	Alloy comfort, R: 30mm	<b>F. DERAILLEUR</b>	N/A	<b>TYRES</b>	20 x 1.75" Semi-Slick
<b>GRIP</b>	TPR Grip	<b>R. DERAILLEUR</b>	Shimano RD-TX35	<b>SADDLE</b>	Factor Ergotech Saddle
<b>HEADSTEM</b>	Alloy foldable	<b>SHIFT LEVERS</b>	Shimano Revoshift 7 speed	<b>SEATPOST / CLAMP</b>	Alloy 34mm with quick release clamp
		<b>CASSETTE</b>	Shimano TZ-21 7 speed 14-28T	<b>EXTRAS</b>	Mudguards, Carrier and Adjustable Kickstand

YOUTH

# YOUTH RANGE

---

For the child just wanting to ride in the park by the house, to the young ripper who is starting to explore the local trails, Apollo has you covered. Our 24" youth bikes are perfectly designed for children, with low stand over heights, high level build quality and quality parts, an Apollo youth bicycle will last you and your child for years. We have designed both girls and boys specific models so that you can find the bike that fits your child and their riding ability perfectly.





### KEY FEATURES

Kids specific geometry with lower stand over height for disc brakes.

Durable and Light RST Capa suspension fork.

21 speed, Shimano EZ-fire shifting with cassette freewheel

Mechanical Disc Brakes front and rear provide maximum braking efficiency.

Kids specific Selle Royal saddle for maximum riding comfort.

Light weight alloy rims.

24" x 1.95" Knobby MTB tyres for greater control in the dirt.

### CODES

Gloss Blue / Gloss Black /  
Gloss Red

16402

### GEOMETRY

STACK	514
REACH	369
STAND OVER HEIGHT	366
EFFECTIVE TOP TUBE	526
SEAT TUBE (CENTRE TO TOP)	318
SEAT ANGLE	73.0°
HEAD TUBE LENGTH	110
HEAD ANGLE	70.0°
WHEEL BASE	1000
CHAIN STAY LENGTH	410
BB DROP	30
FORK RAKE	38
AXLE TO CROWN	421
REAR DROPOUT SPACING	135

### SPECIFICATIONS

<b>FRAME</b>	6061 24" disc specific aluminium gusseted MTB frame. 50mm bi-oval top and down tubes, snake stays	<b>CRANKSET</b>	Suntour XCC-T202 alloy 42 x 32 x 22T L: 152mm	<b>BRAKES</b>	Tektro MD-M280 mechanical disc brakes with 160mm rotors
<b>FORK</b>	RST CAPA-24, Alloy crown and lowers, coil sprung, 50mm travel	<b>BOTTOM BRACKET</b>	Cartridge bottom bracket	<b>WHEELS</b>	24" Weinmann X-M1 alloy 32 hole disc specific rims. Alloy quick release hubs with cassette rear, stainless spokes
<b>HEADSET</b>	Semi-sealed 1-1/8" A-head	<b>PEDALS</b>	NEW low profile high impact nylon	<b>TYRES</b>	24 x 1.95"
<b>HANDLEBAR</b>	Flat bar. W: 580mm	<b>F. DERAILLEUR</b>	Shimano TY-500	<b>SADDLE</b>	Selle Royal Kids Specific
<b>GRIP</b>	Kraton grips	<b>R. DERAILLEUR</b>	Shimano Altus	<b>SEATPOST / CLAMP</b>	Alloy micro adjust 27.2mm, with alloy QR clamp
<b>HEADSTEM</b>	A-head 2 Bolt MTB stem with Rise: 10° Bore: 25.4mm, L: 75mm.	<b>SHIFT LEVERS</b>	Shimano EF-41 EZ FIRE 21 speed	<b>EXTRAS</b>	N/A
		<b>CASSETTE</b>	Shimano 7 speed cassette 12-28T		
		<b>CHAIN</b>	KMC Z-51		





MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

Kids specific geometry with lower stand over height.

Front Suspension for maximum riding comfort.

Alloy A-head stem, with threadless steer tube.

21 speed, Shimano EZ-fire shifting.

Kids specific Selle Royal saddle for maximum riding comfort.

Light weight alloy rims.

24" x 1.95" Knobby tyres.

### CODES

Gloss Black / Gloss Red / Gloss Orange	17235
Gloss Blue / Gloss Lime / Gloss Green	17236

### GEOMETRY

STACK	496
REACH	374
STAND OVER HEIGHT	359
EFFECTIVE TOP TUBE	526
SEAT TUBE (CENTRE TO TOP)	318
SEAT ANGLE	73.0°
HEAD TUBE LENGTH	110
HEAD ANGLE	68.0°
WHEEL BASE	1014
CHAIN STAY LENGTH	410
BB DROP	30
FORK RAKE	38
AXLE TO CROWN	410
REAR DROPOUT SPACING	135

### SPECIFICATIONS

<b>FRAME</b>	Alloy butted 6061 24" frame with 50mm bi-oval down tube	<b>CRANKSET</b>	Alloy 42 x 32 x 22T L: 152mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>FORK</b>	Suspension fork with 50mm travel with alloy crown and lowers	<b>BOTTOM BRACKET</b>	Nutted bottom bracket	<b>WHEELS</b>	24" Alloy 32 hole rims with alloy nutted hubs and stainless spokes
<b>HEADSET</b>	Semi-sealed 1-1/8" A-head	<b>PEDALS</b>	High impact nylon	<b>TYRES</b>	24 x 1.95"
<b>HANDLEBAR</b>	Low riser bar W: 560mm	<b>F. DERAILLEUR</b>	Shimano TZ-30	<b>SADDLE</b>	Selle Royal Kids Specific
<b>GRIP</b>	Kraton grips	<b>R. DERAILLEUR</b>	Shimano TY-300	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm with alloy QR clamp
<b>HEADSTEM</b>	A-head 2 Bolt MTB stem with Rise: 10° Bore: 25.4mm, L: 75mm.	<b>SHIFT LEVERS</b>	Shimano EF-41 EZ FIRE 21 speed	<b>EXTRAS</b>	Kickstand
		<b>CASSETTE</b>	Shimano freewheel 7 speed 14-28T		
		<b>CHAIN</b>	KMC Z-51		



### KEY FEATURES

Kids specific geometry with lower stand over height.

Front Suspension for maximum riding comfort.

Quilled stem for maximum adjustability.

Easy shifting 7 speed Shimano.

Kids specific Selle Royal saddle for maximum riding comfort.

Light weight alloy rims.

24" x 1.95" Knobby tyres.

### CODES

Gloss Black / Gloss Blue / Gloss Lime	17237
Gloss Lime / Gloss Black / Gloss Blue	17238

### GEOMETRY

STACK	496
REACH	374
STAND OVER HEIGHT	359
EFFECTIVE TOP TUBE	526
SEAT TUBE (CENTRE TO TOP)	318
SEAT ANGLE	73.0°
HEAD TUBE LENGTH	110
HEAD ANGLE	68.0°
WHEEL BASE	1014
CHAIN STAY LENGTH	410
BB DROP	30
FORK RAKE	38
AXLE TO CROWN	410
REAR DROPOUT SPACING	135

### SPECIFICATIONS

<b>FRAME</b>	Alloy butted 6061 24" frame with 50mm bi-oval down tube	<b>CRANKSET</b>	Alloy 36T with double chainguard L: 152mm	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	40mm travel with pressed crown and alloy lowers	<b>BOTTOM BRACKET</b>	Nutted bottom bracket	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	Semi-sealed 1-1/8" threaded	<b>PEDALS</b>	High impact nylon	<b>WHEELS</b>	24" Alloy 32 hole rims with nutted hubs stainless spokes
<b>HANDLEBAR</b>	Low riser bar W: 560mm	<b>F. DERAILLEUR</b>	N/A	<b>TYRES</b>	24 x 1.95"
<b>GRIP</b>	Kraton grips	<b>R. DERAILLEUR</b>	Shimano TY-300	<b>SADDLE</b>	Selle Royal Kids Specific
<b>HEADSTEM</b>	Quill stem	<b>SHIFT LEVERS</b>	Shimano Revoshift 7 speed rear	<b>SEATPOST / CLAMP</b>	27.2mm with alloy QR clamp
		<b>CASSETTE</b>	Shimano freewheel 7 speed 14-28T	<b>EXTRAS</b>	Kickstand



MTB

ROAD

LIFESTYLE

YOUTH

### KEY FEATURES

Kids specific geometry with lower stand over height.

Front Suspension for maximum riding comfort.

Alloy A-head stem, with threadless steer tube.

21 speed, Shimano EZ-fire shifting.

Kids specific Selle Royal saddle for maximum riding comfort.

Light weight alloy rims.

Easy rolling semi slick tyres.

### CODES

Gloss White / Gloss Pink / Gloss Lavender	17239
Gloss Lavender / Gloss White	17240

### GEOMETRY

STACK	496
REACH	374
STAND OVER HEIGHT	313
EFFECTIVE TOP TUBE	526
SEAT TUBE (CENTRE TO TOP)	318
SEAT ANGLE	73.0°
HEAD TUBE LENGTH	110
HEAD ANGLE	68.0°
WHEEL BASE	1013
CHAIN STAY LENGTH	410
BB DROP	30
FORK RAKE	38
AXLE TO CROWN	410
REAR DROPOUT SPACING	135

### SPECIFICATIONS

<b>FRAME</b>	Butted alloy 6061 24" step through girls aluminium frame with snake stays	<b>CRANKSET</b>	Alloy 42 x 32 x 22T L: 152mm	<b>BRAKES</b>	Alloy linear pull brakes
<b>FORK</b>	Suspension fork with 50mm travel with alloy crown and lowers	<b>BOTTOM BRACKET</b>	Nutted bottom bracket	<b>WHEELS</b>	24" Alloy 32 hole rims with alloy nutted hubs and stainless spokes
<b>HEADSET</b>	Semi-sealed 1-1/8" A-head	<b>PEDALS</b>	High impact nylon	<b>TYRES</b>	Semi-slick 24 x 1.75" dual tread
<b>HANDLEBAR</b>	Low riser bar W: 560mm	<b>F. DERAILLEUR</b>	Shimano TZ-30	<b>SADDLE</b>	Selle Royal Kids Specific
<b>GRIP</b>	Kraton grips	<b>R. DERAILLEUR</b>	Shimano TY-300	<b>SEATPOST / CLAMP</b>	Alloy 27.2mm with alloy QR clamp
<b>HEADSTEM</b>	A-head 2 Bolt MTB stem with Rise: 10° Bore: 25.4mm, L: 75mm.	<b>SHIFT LEVERS</b>	Shimano EF-41 EZ FIRE 21 speed	<b>EXTRAS</b>	Kickstand
		<b>CASSETTE</b>	Shimano freewheel 7 speed 14-28T		
		<b>CHAIN</b>	KMC Z-51		



## KEY FEATURES

Kids specific geometry with lower stand over height.

Front Suspension for maximum riding comfort.

Quilled stem for maximum adjustability.

Easy shifting 7 speed Shimano.

Kids specific Selle Royal saddle for maximum riding comfort.

Light weight alloy rims.

Easy rolling semi slick tyres.

## CODES

Gloss White / Gloss Lavender / Gloss Blue	17241
Gloss Pink / Gloss White	17242

## GEOMETRY

STACK	496
REACH	374
STAND OVER HEIGHT	313
EFFECTIVE TOP TUBE	526
SEAT TUBE (CENTRE TO TOP)	318
SEAT ANGLE	73.0°
HEAD TUBE LENGTH	110
HEAD ANGLE	68.0°
WHEEL BASE	1013
CHAIN STAY LENGTH	410
BB DROP	30
FORK RAKE	38
AXLE TO CROWN	410
REAR DROPOUT SPACING	135

## SPECIFICATIONS

<b>FRAME</b>	Butted alloy 6061 24" step through girls aluminium frame with snake stays	<b>CRANKSET</b>	Alloy 36T with double chainguard L: 152mm	<b>CHAIN</b>	KMC Z-51
<b>FORK</b>	40mm travel with pressed crown and alloy lowers	<b>BOTTOM BRACKET</b>	Nutted bottom bracket	<b>BRAKES</b>	Alloy linear pull brakes
<b>HEADSET</b>	Semi-sealed 1-1/8" threaded	<b>PEDALS</b>	High impact nylon	<b>WHEELS</b>	24" Alloy 32 hole rims with nutted hubs and stainless spokes
<b>HANDLEBAR</b>	Low riser bar W: 560mm	<b>F. DERAILLEUR</b>	N/A	<b>TYRES</b>	Semi-slick 24 x 1.75" dual tread
<b>GRIP</b>	Kraton grips	<b>R. DERAILLEUR</b>	Shimano TY-300	<b>SADDLE</b>	Selle Royal Kids Specific
<b>HEADSTEM</b>	Quill stem	<b>SHIFT LEVERS</b>	Shimano Revoshift 7 speed rear	<b>SEATPOST / CLAMP</b>	27.2mm with alloy QR clamp
		<b>CASSETTE</b>	Shimano freewheel 7 speed 14-28T	<b>EXTRAS</b>	Kickstand